

# Non-Insulated Stranded Conductor for Lightning Protection – LPA100250



- Provides a path to ground for lightning currents



Part Number	LPA100250
Certification Details	UL® 96
Material	Aluminum
UL Conductor Class	Class I
Conductor Type	Smooth Weave
Number of Wires	24
Wire Diameter	0.064"
Diameter	0.48"
Length	250'
Cross Section	98.64 kcmil
Unit Weight	0.102 lb
Certifications	cULus
Standard Packaging Quantity	250'
UPC	78285661316

Equivalent Conductor Size		
Part Number	Conductor Size	
LPC134xxx	2/0	
LPC136xxx	3/0	
LPC137xxx	4/0	

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.