
Replacement Module for UTB, Intrinsic Safe – UTB15MEX



- Multi-stage protection and fine over-voltage protection helps ensure lowest residual surge voltages reach sensitive equipment
- Surge rating to 20 kA 8/20 µs is ideal for exposed wiring
- For use in intrinsically safe areas







Part Number	UTB15MEX
Nominal System Voltage (Un)	3 - 10 VAC 5 - 15 VDC
Max Continuous Operating Voltage (Uc)	12 VAC 17 VDC
Rated Load Current (IL)	400 mA
Frequency	1 MHz
Loop Resistance	1 Ω
Max Discharge Current (Imax), Per Mode	20 kA 8/20 μs
Protection Modes	Common Differential
Technology	Gas Discharge Tube (GDT) Silicon Avalanche Diode (SAD)
Voltage Protection Level (Up), L-L	25 V @ 3 kA
Temperature	-4 to 149 °F
Enclosure Material	UL® 94V-0 Thermoplastic
Depth (D)	1.92"
Height (H)	1.78"
Width (W)	0.7"
Unit Weight	0.05 lb
Complies With	ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C
Certifications	CE
Standard Packaging Quantity	1 pc
UPC	78285665906





ANSI is a registered trademark of American National Standards Institute. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC. WARNING Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty. © 2017 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

ERICO

PENTAIR