


Stainless Steel Ground Rod, Threaded – 685880S



- Utilizes a cut thread for highly corrosive soil



Part Number	685880S
Material	Stainless Steel 302 (EN 1.4324) Stainless Steel 304 (EN 1.4301)
Tensile Strength	70,000 psi Min
Ground Rod Diameter, Nominal	5/8"
Ground Rod Diameter, Actual (Ø)	0.625"
Thread Size (TS)	5/8 UNC
Length (L)	8'
Unit Weight	7.8 lb
Certifications	RUS UL
Standard Packaging Quantity	1 pc
UPC	78285635829

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.