


TSF Replacement Module – TSF24MDSD



- Replacement module for Transient Surge Filter



Part Number	TSF24MDSD
Nominal System Voltage (Un)	24 VAC
Max Continuous Operating Voltage (Uc)	30 VAC/38 VDC
Nominal Discharge Current (In)	3 kA 8/20 μ s
Enclosure Material	UL® 94V-0 Thermoplastic
Temperature	-40 to 176 °F
Module Width	1 M
Depth (D)	1.92"
Height (H)	1.78"
Width (W)	0.71"
Unit Weight	0.15 lb
Certifications	CE cURus
Standard Packaging Quantity	1 pc
UPC	78285685318
EAN-13	0782856853183

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.