TSF Replacement Module – TSF240MTDS



Replacement module for Transient Surge Filter





| | TOFOLOUTRO |
|---------------------------------------|-------------------------|
| Part Number | TSF240MTDS |
| Nominal System Voltage (Un) | 220 - 240 VAC |
| Max Continuous Operating Voltage (Uc) | 275 VAC |
| Nominal Discharge Current (In) | 3 kA 8/20 μs |
| Enclosure Material | UL® 94V-0 Thermoplastic |
| Temperature | -40 to 176 °F |
| Module Width | 1 M |
| Depth (D) | 1.92" |
| Height (H) | 1.78" |
| Width (W) | 0.71" |
| Unit Weight | 0.15 lb |
| Certifications | CE |
| | cURus |
| Standard Packaging Quantity | 1 pc |
| UPC | 78285685320 |
| EAN-13 | 0782856853206 |

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved
Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.
All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



