


Compact TDX Panel Protector, 100 kA – TDX100C240



- Built-in features include TD Technology, thermal protection and short circuit current fusing
- Compact NEMA®-4 enclosure design can be flush mounted or installed in a small space
- LED status indication and voltage-free contacts provide remote status monitoring
- 100 kA 8/20 μ s maximum surge rating provides protection suitable for main-distribution panels and an extended operational life



Part Number	TDX100C240
Nominal System Voltage (Un)	240 VAC
Distribution System	1Ph 2W+G
Max Continuous Operating Voltage (Uc)	276 VAC
Stand-off Voltage	480 VAC
Frequency	50 – 60 Hz
Short Circuit Current Rating (SCCR)	200 kA
Nominal Discharge Current (In)	40 kA 8/20 μ s
Max Discharge Current (Imax), Per Phase	100 kA 8/20 μ s
Impulse Current (Iimp), Per Mode	12.5 kA 10/350 μ s
Voltage Protection Rating (VPR), L-N	1,000 V @ 3 kA 1,800 V @ 20 kA
Protection Modes	L-N L-PE N-PE
Remote Contacts	Yes
Status Indication	LED
Surge Counter	No
Technology	Over-current fusing TD technology with thermal disconnect
Lead Size	#10
Lead Length	30"
Ground Lead Length	36"
Temperature	-40 to 176 °F
Enclosure Material	Metal

Part Number	TDX100C240
Enclosure Rating	IP 65 NEMA®-4
Mounting	3/4" straight nipple
Depth (D)	3.07"
Height (H)	6.02"
Width (W)	3.31"
Unit Weight	1.76 lb
Certification Details	UL® 1449 Edition 3 Type 1/2, 20 kA Mode
Complies With	ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 1, 20 kA 8/20 µs, 2 kA 10/350 µs
Certifications	CE C-Tick
Standard Packaging Quantity	1 pc
UPC	78285659319

ANSI is a registered trademark of American National Standards Institute. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.