CADDY SWIFT CLIP Threaded Rod Attachment – TRC150











- Snap-on and twist installation requires no tools
- Easily adjusts by rotating up or down on the threaded rod
- For support and positioning of refrigeration, A/C tubing, PEX piping, conduit and cabling
- Secures pipe and insulation without any breaks
- Compliant with UL® 2043 and suitable for use in air handling (plenum) spaces

| Part Number | TRC150 |
|-----------------------------|---------------|
| Material | Polyamide |
| Working Temperature | -40 to 284 °F |
| Outer Diameter | 1 1/2" |
| Rod Size | 3/8" |
| Standard Packaging Quantity | 25 pc |
| UPC | 78285678863 |

Clip must be installed with temperature at or above 14 $^{\circ}$ F (-10 $^{\circ}$ C).

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



