



Spark Gap Diverter Replacement Module – SGD125M



Part Number	SGD125M
Measured Limiting Voltage (MLV)	2,420 VAC
Voltage Protection Level (Up)	1,600 V @ 20 kA
Max Discharge Current (Imax), Per Mode	60 kA 8/20 μ s
Impulse Current (Iimp)	25 kA 10/350 μ s
Follow Current Extinguishing Capability	100 A @ 0.5 MA
Max Operating Current	0.5 mA
Frequency	50 – 60 Hz
Short Circuit Current Rating (SCCR)	25 kA
Enclosure Material	UL® 94V-0 Thermoplastic
Temperature	-40 to 176 °F
Module Width	1 M
Depth (D)	1.92"
Height (H)	1.78"
Width (W)	0.69"
Unit Weight	0.05 lb
Certifications	CE cULus
Standard Packaging Quantity	1 pc
UPC	78285662253
EAN-13	8711893097153

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.