



# TDS Replacement Module – TDS150M440



- Replacement module for TDS Din Rail Series and TDX Modular Series



Part Number	TDS150M440
Max Discharge Current (I <sub>max</sub> )	50 kA 8/20 μs
Nominal System Voltage (U <sub>n</sub> )	420 - 440 VAC
Max Continuous Operating Voltage (U <sub>c</sub> )	480 VAC
Voltage Protection Rating (VPR)	1,500.0 V @ 3 kA 2,200.0 V @ 20 kA
Nominal Discharge Current (I <sub>n</sub> )	20 kA 8/20 μs
Frequency	0 - 100 Hz
Enclosure Material	UL® 94V-0 Thermoplastic
Temperature	-40 to 176 °F
Module Width	1 M
Depth (D)	1.91"
Height (H)	1.78"
Width (W)	0.71"
Unit Weight	0.15 lb
Certifications	CE cURus
Standard Packaging Quantity	1 pc
UPC	78285668487

Remove black pin when using with TDX modular units.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.