

Non-Insulated Stranded Conductor for Lightning Protection – LPC120L250



- Provides a path to ground for lightning currents



| | |
|-----------------------------|--------------|
| Part Number | LPC120L250 |
| Certification Details | UL® 96 |
| Material | Copper |
| Finish | Tinned |
| UL Conductor Class | Class I |
| Conductor Type | Smooth Weave |
| Number of Wires | 29 |
| Wire Diameter | 0.045" |
| Diameter | 0.44" |
| Length | 250' |
| Cross Section | 59.45 kcmil |
| Unit Weight | 0.192 lb |
| Certifications | UL |
| Standard Packaging Quantity | 250' |
| UPC | 78285664452 |

| Equivalent Conductor Size | |
|---------------------------|----------------|
| Part Number | Conductor Size |
| LPC134xxx | 2/0 |
| LPC136xxx | 3/0 |
| LPC137xxx | 4/0 |

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.