

DT2 DIN Rail Surge Protection Replacement Module – DT2350M



| | |
|---------------------------------------|-----------------------------|
| Part Number | DT2350M |
| Nominal System Voltage (Un) | 277 V |
| Max Continuous Operating Voltage (Uc) | 350 V |
| Nominal Discharge Current (In), IEC | 20 kA 8/20 μs |
| Max Discharge Current (Imax), IEC | 50 kA 8/20 μs |
| Nominal Discharge Current (In), UL | 20 kA 8/20 μs |
| Frequency | 50 – 60 Hz |
| Temperature | -31 to 185 °F |
| Enclosure Material | UL® 94V-0 Thermoplastic |
| Certifications | CE, ERICO DT2 Series VDE |
| Standard Packaging Quantity | 1 pc |
| UPC | 78285693853 |

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC. VDE is a registered trademark of VDE Verband Deutscher Elektrotechniker e.V. Corporation.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.