



Replacement Module for DSD, 20 kA – DSD1201S24M



Part Number	DSD1201S24M
Nominal System Voltage (Un)	24 VDC
Max Continuous Operating Voltage (Uc)	28 VDC
Nominal Discharge Current (In), Per Mode	10 kA 8/20 μ s
Max Discharge Current (Imax), Per Mode	20 kA 8/20 μ s
Voltage Protection Level (Up)	40 V @ 3 kA
Frequency	0 – 60 Hz
Technology	Gas Discharge Tube (GDT) Silicon Avalanche Diode (SAD)
Enclosure Material	UL® 94V-0 Thermoplastic
Status Indication	Mechanical flag
Temperature	-40 to 176 °F
Module Width	1 M
Depth (D)	1.92"
Height (H)	1.78"
Width (W)	0.71"
Unit Weight	0.15 lb
Certifications	CE
Standard Packaging Quantity	1 pc
UPC	78285647267
EAN-13	8711893014624

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.