
Service Entrance Suppressor, 200 kA – SES200120208



- 200kA 8/20µs primary protection rated for service entrance applications
- Modular design allows easy replacement of surge modules
- Built-in disconnect and fusing eliminates need for external fusing
- Transient Discriminating (TD) Technology provides increased service life





Part Number	SES200120208
Nominal System Voltage (Un)	120/208 V
Distribution System	3Ph Y 4W+G
Max Continuous Operating Voltage (Uc)	170/295 VAC
Stand-off Voltage	240/415 V
Frequency	50 – 60 Hz
Short Circuit Current Rating (SCCR)	200 kA
Nominal Discharge Current (In), Per Mode	80 kA 8/20 µs
Max Discharge Current (Imax), Per Mode	100 kA 8/20 μs
Voltage Protection Rating (VPR)	600.0 V @ 3 kA L-N 800.0 V @ 20 kA L-N
Aggregate Surge Rating	200 kA 8/20 μs
Impulse Current (limp)	20 kA 10/350 μs
Max Operating Current	25 mA
Protection Modes	All modes protected
Status Indication	5 segment LED bar graph per phase
Technology	TD technology with thermal disconnect
Lead Size	#12 - #2
Temperature	14 – 140 °F
Enclosure Material	Polycarbonate
Enclosure Rating	IP 66 NEMA®-4X
Mounting	Wall mount
Depth (D)	7 1/2"
Height (H)	16"



Part Number	SES200120208
Width (W)	12"
Unit Weight	17.64 lb
Certification Details	UL® 1449 Edition 3 Type 1/2, 20 kA Mode
Complies With	ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 3, 100 kA 8/20 μs, 10 kA 10/350 μs
Certifications	NOM
Standard Packaging Quantity	1 pc
UPC	78285663686

ANSI is a registered trademark of American National Standards Institute. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



