


2-, 3- and 4-Point Ground Resistance Tester Kit – EST4630



- Measures ground resistance (2- and 3-Point) Fall-of-Potential method and soil resistivity (4-Point)
- Fuse protection of 0.1A, >250V, 0.25 x 1.25" with 30kA Interrupt Capacity
- Both models will perform over 2,000 measurements of the 15-second tests between recharging or battery replacement
- Provides a response time of approximately four to eight seconds for a stabilized measurement
- Step voltage tests and touch potential measurements
- Auto-ranging: automatically selects the optimum resistance range and test current
- Designed to reject high levels of noise and interference
- Extremely simple to operate: connect – press – hold – read
- May also be used for continuity tests on bonding
- Large easy-to-read backlit display
- LED on faceplate informs operator of high input noise, high auxiliary rod resistance and fault connections
- Rugged dustproof and rainproof field case
- Color-coded terminals
- Low battery indication



Part Number	EST4630
Soil Resistivity Test	Yes
Measurement Range	0 – 2,000 Ω
Resolution	10 m Ω – 1 Ω
Open Voltage	42 V Max
Test Current	10.0 – 0.1 mA
Operating Frequency	128 Hz square wave
Accuracy	2% of Reading +/- 1ct 5% of Reading +/- 3ct
Auxillary Electrode Influence	3 – 50 k Ω
Withstanding Voltage	250 VAC 100 VDC
Power Source	AC-powered with rechargeable NiMH battery pack
Unit Weight	35 lb
Certifications	CE Qualifoudre
Standard Packaging Quantity	1 pc
UPC	78285663899
EAN-13	8711893056808

Kit includes: Two 300' (91.4 m) color-coded leads on spools (red and blue), two 5' (1.5 m) color-coded leads (red and blue), two 100' (30.5 m) color-coded leads (green and black), four 14.5" (368 mm) T-shaped auxiliary ground electrodes, one set of five-spaded lugs, one 100' (30.5 m) tape measure, and one carrying bag.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.