

## Non-Insulated Stranded Conductor for Lightning Protection – LPC122L250



- Provides a path to ground for lightning currents



Part Number	LPC122L250
Certification Details	UL® 96
Material	Copper
Finish	Tinned
UL Conductor Class	Class I
Conductor Type	Smooth Weave
Number of Wires	32
Wire Diameter	0.045"
Diameter	0.48"
Length	250'
Cross Section	65.6 kcmil
Unit Weight	0.22 lb
Certifications	UL
Standard Packaging Quantity	250'
UPC	78285664457

Equivalent Conductor Size	
Part Number	Conductor Size
LPC134xxx	2/0
LPC136xxx	3/0
LPC137xxx	4/0

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

### WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.