



Non-Insulated Stranded Conductor for Lightning Protection – LPC137LCT0



- Provides a path to ground for lightning currents



Part Number	LPC137LCT0
Certification Details	UL® 96
Material	Copper
UL Conductor Class	Class II
Conductor Type	Concentric
Number of Wires	37
Wire Diameter	0.076"
Diameter	0.53"
Cross Section	211.6 kcmil
Unit Weight	0.653 lb
Certifications	UL
Standard Packaging Quantity	1 pc
UPC	78285673504

Equivalent Conductor Size	
Part Number	Conductor Size
LPC134xxx	2/0
LPC136xxx	3/0
LPC137xxx	4/0

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.