



# Replacement Module for DSD, 40 kA – DSD140M440



Part Number	DSD140M440
Nominal System Voltage (Un)	380 V
Max Continuous Operating Voltage (Uc)	440 VAC 580 VDC
Nominal Discharge Current (In), Per Mode	20 kA 8/20 $\mu$ s
Max Discharge Current (Imax), Per Mode	40 kA 8/20 $\mu$ s
Voltage Protection Level (Up)	1,400 V @ 3 kA 2,200 V @ 20 kA
Frequency	0 – 60 Hz
Short Circuit Current Rating (SCCR)	25 kA
Technology	MOV with thermal disconnect
Enclosure Material	UL® 94V-0 Thermoplastic
Status Indication	Mechanical flag
Temperature	-40 to 176 °F
Module Width	1 M
Depth [D]	1.91"
Height [H]	1.78"
Width [W]	0.71"
Unit Weight	0.1 lb
Certifications	CE
Standard Packaging Quantity	1 pc
UPC	78285658204
EAN-13	8711893041569

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.