

CONNECT AND PROTECT

Rail Electrical Products


nvent

ERICO

nVent Engineered Electrical & Fastening Solutions is a leading global manufacturer and marketer of superior engineered products for niche electrical, mechanical and concrete applications. These nVent products are sold globally under a variety of market-leading brands: nVent ERICO welded electrical connections, facility electrical protection, and rail and industrial products; nVent CADDY fixing, fastening and support products; nVent ERIFLEX low voltage power and grounding connections; and nVent LENTON engineered systems for concrete reinforcement.

For more information on nVent ERICO, CADDY, ERIFLEX and LENTON, please visit nVent.com.

NVENT CADDY FIXINGS, FASTENERS AND SUPPORTS FOR ELECTRICAL APPLICATIONS

Specialty clips, clamps, hangers and straps for electrical and information transport system installations.

NVENT CADDY FIXINGS, FASTENERS AND SUPPORTS FOR MECHANICAL APPLICATIONS

Hangers, fasteners and support products for plumbing, HVAC, fire protection and seismic systems.

NVENT ERIFLEX LOW VOLTAGE PANEL COMPONENTS

Current carrying connectors, supports and other non-active electric panel components.

nVent ERIFLEX Flexibar flexible insulated busbar.

NVENT ERICO ELECTRICAL PRODUCTS

Products for grounding, bonding, surge protection and lightning protection that are designed to offer a coordinated system approach to facility electrical protection.

nVent ERICO Cadweld welded electrical connections

nVent ERICO grounding and bonding products, lightning protection systems, surge protection devices

NVENT LENTON CONCRETE REINFORCEMENT PRODUCTS

Rebar splicing systems and other reinforcing products utilized to connect steel reinforcement rods in concrete.

RAIL AND INDUSTRIAL PRODUCTS

Connecting and bonding products based on exothermic connection technology

Cadweld welded connections

nVent ERICO surge protection devices

Table of Contents

TYPICAL APPLICATIONS

Signal Bonding

Joint Head Bond	5
Fouling Circuit	5
Web Bonding	5

Track Clips

Track Retainer Clip	6
Rail Clip and Concrete Tie Clip	6
Clip, Bootleg, Track Connector	6

Concrete Tie Clips

Concrete Tie Clip Bootleg Riser 4-Wire Kit	7
Concrete Tie Clip Applications	7

CADWELD BONDING PRODUCTS

Bonds

Joint Head Bonds	8
Track Connectors - Web	12
Jumper, Switch and Bootleg Bonds	12

Welders and Molds

Rail Head Welders and Molds	9
Replacement Mold Covers for T6 & T7 Welders	10
Web (Field and Factory Made)	13
Extension Clamps on Rail Head & Rail Web	13
Frog and Special Track Work	11

Field Made Bonds

Tab-Style Terminals	11
---------------------------	----

MECHANICAL CONNECTORS

Bonds

Plug Bonds	14
Track Connectors "Chicken Heads"	15
Multi-Purpose Bonds	15

Associated Materials

Sleeves - Compression Type	16
No-Oxide Grease	16
Bond Removal Punch	16

Related Materials

Bond Strand	17
Miscellaneous Bonding Items	17

Temporary Connectors

Temporary Track Connector	18
Temporary Signal Bond, 3/16"	18

Track Circuit Shunts

Dual Shunt	19
Single Shunt	19

Table of Contents

CABLE CLIPS

Retainer Clips

Electroplated Spring Steel	20
Electroplated Steel	20
PVC Cable Keeper	20

Retainer Clip Assemblies

Below Rail Base	21
Rail Base	21
Web	21

“Snap-on” Styles

Stainless Steel Rail Type	22
Concrete Tie Clips	22

Glued Rail Clip

Cable Clip Kit for Concrete Rail Ties	23
---	----

GRINDERS AND BONDING ACCESSORIES

Rail Grinders

SBG141 Pedestal Rail Grinder (Gas Powered)	24
Drill Attachment Parts	24
SBG150 Portable Grinder (Gas Powered) 2 cycle	25
SBG200 Grinder (Gas Powered) 4 cycle	26
SBG100 Grinder (Battery Powered)	26

Grinders & Drilling Machines

Portable Drilling Machine (Gas Powered) 2 cycle	27
Portable Drilling Machine (Gas Powered) 4 cycle	27
Portable Drilling Machine (Battery Powered)	28
Portable Drilling Machine (Electro Powered)	28
Clamping Devices	29
Rail Drilling Accessories	29

Tools & Bonding Accessories

Stripping Tools 2 x 2	30
Blades	30
Stripping Tools 4 x 4	31
Replacement & Additional Bushings	31
Miscellaneous Tools	32
Flint Ignitor Extension	32

TOTAL FACILITY PROTECTION

Production for High Frequency

Low Impedance, Path to Ground

4 Terminal Block	33
------------------------	----

SOLUTIONS TO POWER

QUALITY PROBLEMS	34-35
------------------------	-------

Table of Contents

PRIMARY SURGE PROTECTION

EPD Power Surge Devices.....

ETSP Track Circuit Protection Devices.....

36

37

SECONDARY SURGE PROTECTION

EPD Power Surge Devices.....

38

PERIPHERAL POWER PROTECTION

Dinline Surge Filters

Din Surge Diverters.....

39

39

COMMUNICATIONS & DATA EQUIPMENT PROTECTION

Control Signal Equipment Protection

Universal Transient Barrier (UTB and UTBTA)

Rail Transient Barrier (RTB).....

Radio Communcations Protection

Coaxial Surge Protectors - CSP.....

40

40

41

GROUNDING

Ground Rods

Chemical Ground Rod Kit.....

nVent ERICO Cadweld One Shot Connections

Cable-To-Ground Rod.....

Cable-To-Cable

GEM Ground Enhancement Material.....

Ground Testers.....

Aluminum-Copper Grounding Stud

Aluminum Signal Mast.....

Aluminum Signal Case.....

Cadweld Connections

Cable to Cable.....

Cable-To-Steel Structures

Flat Vertical Surface

Round Vertical Surface

Horizontal Flat Surface

42

42

43

43

44

44

45

45

46

47

47

48

ALPHA-NUMERIC LISTING.....

49-53


PRODUCT LITERATURE.....

54-55


Typical Applications

SIGNAL BONDING


JOINT HEAD BOND



FOULING CIRCUIT




WEB BONDING




Typical Applications

TRACK CLIPS


TRACK RETAINER CLIP



RAIL CLIP AND CONCRETE TIE CLIP (CONTACT NVENT)




CLIP, BOOTLEG, TRACK CONNECTOR





Typical Applications

CONCRETE TIE CLIPS

CONCRETE TIE CLIP BOOTLEG RISER 4-WIRE KIT



CONCRETE TIE CLIP APPLICATIONS




Cadweld Bonding Products

BONDS

JOINT HEAD BONDS

Order in boxes of 100 - Includes one pair of replacement molds, flint ignitor and necessary F80 formulation welding material.



Bond	6-1/2"	7"	7-1/2"	9-3/4"	9-3/4"
3/16" Dia.					
XS Style	SBS24882		SBS24883	SBS24884	
XS Style Tinned Conductor					
Tab Style	SBXSHU2		SBXSHU3	SBXSHU4	
Head Free Rail	SB20104		SB20136	SB20108	
	SB20112		SB20128	SB20116	
5/16" Dia.					
Tab Style		SB20175			SB20118
Head Free Rail		SB20175HF			

Also available as bond only.


Cadweld rail head joint bonds provide:

- Maximum broken rail protection
- Unchanging electrical resistance
- Maximum corrosion resistance
- Easy installation, minimum installer skill required
- Simple and highly portable installation equipment
- Versatility, equally usable on old, worn, or new rail
- Durability, not destroyed by rail end build up

Bonding Products


WELDERS AND MOLDS

RAIL HEAD WELDERS AND MOLDS



T-6 Style

With Molds Bond	T-6 Style One-Piece Rail Welder Complete			
	6-1/2"	7"	7-1/2"	9-3/4"
3/16" Dia.				
XS Style	SBXST6A		SBXST6C	SBXST6D
Tab Style	SBTBT6A		SBTBT6C	SBTBT6D
Head Free Style	SBHFT6A		SBHFT6C	SBHFT6D
5/16" Dia.				
Tab Style		SBTBT6B		SBTBT6E
Head Free		SBHFT6B		



T-7 Style

3/16" Dia. Bonds			5/16" Dia. Bonds	
T-7 Style Bond Terminal	Welder Pair	Molds Only (Pair)	Welder Pair	Molds Only (Pair)
3/4" XS	SBXST7D	SBM456		
3/4" Tab	SBTBT7F	SBS5838		
1" Tab	SBTBT7G	SBS5839	SBTBT7B	SBS898
Head Free	SBHFT7E	SBS925	SBHFT7K	SBB492

T-7 Welders are a convenient means of attaching rail head bonds wherever the standard T-6 Welder will not fit properly such as transposed rail and compromised joints.


Bonding Products

WELDERS AND MOLDS

RAIL HEAD WELDERS AND MOLDS CONTINUED

Bond	Replacement Parts		Bond Clips
	Molds Only (Pair)	Molds With Mounting Parts And Clips	
3/16" Dia.			
XS Style	SBM456	SBM456F	S2659
Tab Style	SBS5838	SBS5838F	S2659
Head Free Style	SBS925	SBS925F	S2044
5/16" Dia.			
Tab Style	SBS898	SBS898F	S119
Head Free	SBB492	SBB492F	B194D

REPLACEMENT MOLD COVERS FOR T-6 AND T-7 WELDERS



Part Number	Description
SBB2516A	Single Replacement Cover
SBB2516APRWH	Pair of Replacement Covers with Hardware


REPLACEMENT MOLD COVERS FOR T21 AND TB5 WELDERS

Part Number	Description
B30174	Single Replacement Cover
B2516C1	Single Replacement Cover Hardware
B2516C	Single Replacement Cover with Hardware

Bonding Products

WELDERS AND MOLDS




FROG AND SPECIAL TRACK WORK

 TB-4 Hold Down			
Terminal Style	TB-4 Welder Hold Down	Frame Only	Replace- ment Mold
3/16" Dia.			
3/4" XS	SBXSTB4A	B323L	SBB343A
3/4" Tab	SBTBTB4B	B323L	SBB343B
1" Tab	SBTBTB4C	B323L	SBB343C
1-1/2" Tab	SBTBTB4D	B323L	SBB343D
5/16" Dia.			
1" Tab	SBTBTB4E	B323L	SBB343E

(Not to be used on base of load bearing rail)

FIELD MADE BONDS

TAB-STYLE TERMINALS

 Tab Style				 Hammer Die		 Sleeve	
--	--	--	--	--	--	---	--

		Sleeves			Hammer Dies	F80 Welding Material	
Cable Size	Terminal Length	Part Number	Std. Pkg.		Part Number	Part Number	Std. Pkg.
#6 Sol	1"	SBS10	100		NA	SB25	50
3/16"	3/4"	SBS11C	100				
	1"	SBS12C	100		SBD50	SB25	50
	1-1/2"	SBS13C	100				
5/16"	1"	SBS09C	100		SBD51	SB32	50


Cable - supplied by nVent in 3/16" and 5/16" copper alloy stranded signal cable (bare) and 3/16" signal cable with 4/64" and 6/64" PVC insulation. Available in 100' coils, 500' and 1000' reels. See page 17.

Bonding Products

BONDS

TRACK CONNECTORS - WEB

Order in boxes of 100 - Includes one pair of replacement molds, flint ignitor and necessary F80 formulation welding material.


	
Tab Style	
Part Number	Description
SBTBBU4A	3/16" Dia. x 1" Tab x 4" Long Bootleg
SBTBCU412	3/16" Dia. x 1" Tab x 12" Long Bootleg

For complete Welder (SBTBT21C) see page 13 and compression tool (SBT031DJ) see page 16.

The Cadweld track connector from nVent is used when the advantages of a welded connection to the rail web are desired and standard compression connection to track wire is required. The connector provides flexibility and resistance to vibration fatigue by incorporating a length of bond strand between the Cadweld connection and the sleeved end. The SBTBBU4A and SBTBCU412 are 3/16" tinned copper alloy. (Other lengths available.)

JUMPER, SWITCH AND BOOTLEG BONDS

Substitute desired length of bond in even inches for 'X'. Replacement molds sold separately. All Cadweld bonds are furnished with the necessary F80 formulation welding material.


			
Jumper			
Switch			
Bootleg			
Diameter	Jumper	Switch	Bootleg
3/16" Dia.			
3/4" XS Style	SBXSJ33"X"	SBXSS33"X"	SBXSB33"X"
3/4" Tab	SBTBJ33"X"	SBTBS33"X"	SBTBB33"X"
1" Tab	SBTBJ34"X"	SBTBS34"X"	SBTBB34"X"
1-1/2" Tab	SBTBJ36"X"	SBTBS36"X"	SBTBB36"X"
5/16" Dia.			
1" Tab	SBTBJ54"X"	SBTBS54"X"	SBTBB54"X"

Also available as bond only.
STD Packs of 10 or 25


Bonding Products

WELDERS AND MOLDS

WEB (FIELD MADE AND FACTORY MADE)



TB-5 Hand Held




T-21 Clamping

Terminal Style	TB-5 Welder		T-21 Welder		Replace-ment Mold
	Hand Held	Frame Only	Clamping	Frame Only	
3/16" Dia.					
3/4" XS	SBXSTB5A		SBXST21A		SBB200A
3/4" Tab	SBTBTB5B		SBTBT21B		SBB200B
1" Tab	SBTBTB5C	M22	SBTBT21C	C105B	SBB200C
1-1/2" Tab	SBTBTB5D		SBTBT21D		SBB200D
5/16" Dia.					
1" Tab	SBTBTB5E	M22	SBTBT21E	C105B	SBB200E

TB-5 & T-21 Web welders are for installation of track circuits and jumper bonds to the neutral axis.

TB-5 & T-21 Welders and replacement molds are supplied in pairs. Welder frames are sold as pairs.

EXTENSION CLAMPS ON RAIL HEAD AND RAIL WEB



SBC105R Special Track Work

Part No.	Description	Mold
SBC105S	Head Ext. Clamp	See T-7 Style Molds
SBC105SA	Head Ext. Clamp w/ Mold Cover	See T-7 Style Molds
SBC105R	Web Ext. Clamp	See TB-5 / T-21 Style Molds

- Adjusts for wide span usage - e.g. frogs, switches, etc. (25-1/2" Max. Span)
- Easy to use and lightweight.
- Can be used with existing head and web molds.
- Can also be used on standard (single) rail.


Mechanical Connectors

BONDS

PLUG BONDS

Standard Package 50

Specify bond length as a suffix to part number (XX), i.e., SBPAJA24 is an S-1 cable type, 24" long.



Part Number	Cable Type AREMA ⁺ Drawing 8.1.25-#1	Description	Bare Dia. Inches
SBPAJA"XX"	S-1	1 Copper, 6 Galvanized Steel	0.3270
SBPAJB"XX"	S-5	3 Copper, 16 Galvanized Steel	0.3300
SBPAJC"XX"	7-#10	7-40% Copper-bonded	0.3060
SBPAJD"XX"	7-#12	7-40% Copper-bonded	0.2430
SBPAJ3"XX"	S-8	133 Cadmium Bronze	0.1875
SBPAJR"XX"	S-8 Insul	133 Cadmium Bronze w/ 4/64" PVC Insulation	0.1875
SBPAJG"XX"	S-12	42 Cadmium Bronze, 91 Hard Drawn Stain, Steel	0.2510
AREMA Drawing 8.1.25-#2			
SBPAJP"XX"	DS-1		
SBPAJN"XX"	14-#12		

XX= Lengths 24, 30, 34, 36, 42, 48, 60, 72, and 96.


nVent ERICO plug bonds are designed for application to the rail web. Plug bonds are hammered into a 3/8" diameter hole drilled through the rail web (driven from same side hole was drilled). This recommended method of installation requires a bond 12 inches longer than the splice bar.

Mechanical Connectors

BONDS

TRACK CONNECTORS “CHICKEN HEADS”


Standard Package 200



Part Number	Cable	Connector
SBPAC3A	3/16"	3/16" - #6 str
SBPAC3G		#8 str/#6sol
SBPAC3R		#9 str/#8sol
SBPAC3Y		#10 str/#9sol
SBPAW35		3/8" tapered plug
SBPACGBJ4	1/4"	3/16" - #6 str

The nVent ERICO track connector is used when bond strand is being utilized for track connections, fouling circuits, and even bonding around the splice bar. The plug terminal is hammered into a 3/8" diameter hole drilled through the rail web (driven from same side hole was drilled).

Compression tool (SBT031DJ) sold separately. See page 16.



MULTI-PURPOSE BONDS

Standard Package 48



Part Number	Cable Type
SBPMJ3 "X"	Bare - 3/16" S-8
SBPMJR "X"	Black Insul. - 3/16" S-8
SBPMJS "X"	Orange Insul. - 3/16" S-8

Substitute length for "X" (10", 12", or 14")


The nVent ERICO multi-purpose bond is used when a standard plug bond cannot be installed from the field side of rail due to tight areas such as frogs and switches.

Mechanical Connectors

ASSOCIATED MATERIAL

SLEEVES - COMPRESSION TYPE

Standard Package 100




Part Number	3/16" Bond Strand To: Description
A2314J	#9 solid or #10 str
A2364J	#8 solid or #9 str
A2363J	#6 solid or #8 str
A2367J	#3/16" or #6 str
A2412J	1/4" Binding Post, Lug
SBT031DJ	Compression Tool

NO-OXIDE GREASE

Part Number	Description
T369	1 ounce tube

BOND REMOVAL PUNCH




Part Number	Description
SBT382B	Punch Only
SBT408	Plastic Handle Only
SBT382BWH	Punch w/Handle
SBT382BWPH	Punch w/Plastic Handle

Mechanical Connectors

RELATED MATERIALS

BOND STRAND



Part Number			Description
100' Coil	500' Reel	1000' Reel	
SBS8CINSUL	SBS8LINSUL	SBS8INSUL	S-8, 3/16", Black 4/64 PVC
SBS8CINORG	SBS8LINSORG	SBS8INORG	S-8, 3/16", Orange 4/64 PVC
SBS8TCINS	SBS8TDINSUL	SBS8TINSUL	S-8, 3/16" Tinned, Black 4/64 PVC
SBS8TCINS664	SBS8TLINS664		S-8, 3/16" Tinned, Black 6/64 PVC
SBS8TCINSRD		SBS8TINSRD	S-8, 3/16" Tinned, Red 6/64 PVC
SBS8CBARE SBS17CBARE	SBS8LBARE	SBS8BARE	S-8, 3/16", Bare S-17, 5/16", Bare
A806A12F100		A806A12F1000	S-8, 3/16" Tinned, Orange 6/64 PVC


MISCELLANEOUS BONDING ITEMS

Part Number	Description	Std. Pkg.
B154A	3/8" Straight head plug terminal	25
B101AA	Lug - 1/16" x 1/2", 1-hole (1/4" stud)	25
SBK012A	1/4" split stud kit	10
SBK012B	1/4" split stud kit	100
SB25	Rail Welding Material F80	50
SB32	Rail Welding Material F80	50

Mechanical Connectors

TEMPORARY CONNECTORS

TEMPORARY TRACK CONNECTOR




Part Number	Description
A140	Bolt Type
A140WT	T-Handle Type

Standard Package 4

Makes temporary signal bonds and track circuit connections using your cable.

- Accepts cable sizes #6 thru 1/0, including 3/16" and 5/16" diameter bond strand.
- Hardened contact points on clamps bite through rust and scale.

TEMPORARY SIGNAL BOND 3/16"




Part Number	Description
SBS3086S48	3/16" Orange Insul. 48" long
SBS3086S48WT	3/16" Orange Insul. w/T-handle 48" long
SBS3086R48	3/16" Black Insul. 48" long
SBS3086R48WT	3/16" Black Insul. w/T-handle 48" long

- Lightweight - made from 3/16" PVC insulated bond strand.
- PVC insulation available in black or orange.
- Hardened contact points on clamps bite through rust and scale.
- Cable welded to terminal for electrical reliability.

Mechanical Connectors

TRACK CIRCUIT SHUNTS

DUAL SHUNT



Part Number	Description
SBB2721S	Dual Shunt (0.06 ohm/hard) Base style 2 pt. clamp
SBB2721T	Dual Shunt (0.06 ohm/hard) Head style 2 pt. clamp
SBB2721G	Dual Shunt (0.06 ohm/hard) Head style 3 pt. clamp
SBB2721B	Dual Shunt (0.06 ohm/hard) Base style 3 pt. clamp
SBB2721V	Dual Shunt (0.06 ohm/hard) Head style 2 pt. clamp with locking hardware

- One easy-to-carry assembly.
- No resistor to fail. Product is pre-engineered to provide permanent 0.06 ohm shunting.
- 100% tested and tagged to assure reliability.
- Hardened contact points on clamps bite through rust and scale.
- 0.06 ohm clamps painted red for easy identification.

SINGLE SHUNT



Part Number	Description
SBB2721F	0.06 ohm Shunt only, Base style, 3 pt. clamp
SBB2721H	0.06 ohm Shunt only, Head style, 2 pt. clamp
SBB2721CS72	Hard Shunt only, Base style, 3 pt. clamp
SBB2721JS72	Hard Shunt only, Head style, 3 pt. clamp
SBB2721VS72	Hard Shunt only, Base style, 2 pt. clamp
SBB2721JS72SP	Hard Shunt only, Head style, 2 pt. clamp with locking hardware
SBB2721WS300	Hard Shunt only, Head style, 2 pt. clamp, 25 foot length
SBB2721WS600	Hard Shunt only, Head style, 2 pt. clamp, 50 foot length

Two shunt assemblies are available - "hard" zero ohm or 0.06 ohm.

- 0.06 ohm style has no resistor to fail. Product is pre-engineered to provide permanent 0.06 ohm shunting.
- Hardened contact points on clamps bite through rust and scale.
- Bright orange insulation on "Hard" shunt for high visibility and easy identification.


Cable Clips

RETAINER CLIPS


DESIGN FEATURES

- Spring steel and “snap-on” designs mean no more holes to drill.
- Flexibility - wide range of clips fit all standard rails and a variety of conductors.
- Versatility - nVent now enables you to secure cables — reducing maintenance and improving wayside safety.


ELECTROPLATED SPRING STEEL

			
Part Number	Max Cable Diameter	Position on Rail Base	Standard Packaging
A248B	3/8"	Perpendicular	50
A251	3/8"	Double Parallel	50

ELECTROPLATED STEEL

			
Part Number	Max Cable Diameter	Position on Rail Base	Standard Packaging
A154	5/16"	Perpendicular	50
A203	5/16"	Parallel	100
A205	1/2"	Parallel	100
SBA206	1/2"	Perpendicular	50
A219	5/16"	Double Parallel	100


PVC CABLE KEEPER

	
Part Number	Description
T375	7/16" Diameter Cable Keeper – 2 Holes w/nails

Cable Clips


RETRAINER CLIP ASSEMBLIES

BELOW RAIL BASE




Part Number	Description	Standard Packaging
SBA2510B	3/4" Dia.	50
SBA2511B	1" Dia.	50
SBA2512B	1-1/4" Dia.	50

RAIL BASE



Part Number	Description	Standard Packaging
SBA252S0	3/4" Dia.	50
SBA252S1	1" Dia.	50
SBA252S2	1-1/4" Dia.	50

WEB





Part Number	Description	Standard Packaging
SBA254A1	3/8" Dia.	25
SBA255D1	1/2" Dia.	25

Cable Clips


“SNAP-ON” STYLES

STAINLESS STEEL RAIL TYPE



Part Number	Description	Std Pack
SBA258A1	6" Rail Base – Two 3/8"	25
SBA258B1	5.5" Rail Base – Two 3/8"	25
SBA258D1	5.5" Rail Base – One .5" Cable	25
SBA260A	6" Rail Base – Perpendicular Cable - One 3/8" Cable	25

CONCRETE TIE CLIPS “SNAP-ON” STYLE STAINLESS STEEL




Flexible configurations

Contact nVent with Application Information & Concrete Tie Dimensions

Cable Clips



GLUED RAIL CLIPS

CABLE CLIP KIT FOR CONCRETE RAIL TIES



Part Number	Description	Std Pack		Max. clips per base
		Base	Clips	
GCHSC67	Cable Dia. 0.24-0.28 in	30	120	4
GCHSC78	Cable Dia. 0.28-0.31 in	30	120	4
GCHSC89	Cable Dia. 0.31-0.35 in	30	120	4
GCHSC910	Cable Dia. 0.35-0.39 in	30	120	4
GCHSC1011	Cable Dia. 0.39-0.43 in	30	120	4
GCHSC1214	Cable Dia. 0.47-0.55 in	30	120	4
GCHSC1518	Cable Dia. 0.59-0.71 in	30	90	3
GCHSC1924	Cable Dia. 0.75-0.94 in	30	90	3
GCHSC2530	Cable Dia. 0.98-1.19 in	30	60	2

- Each kit includes one container of adhesive. Additional containers available upon request with part no. GCGLUE.
- Glue container suitable for a 10 oz. dispensing gun.
- Usable for longitudinal or transversal cable applications.



Grinders & Bonding Accessories


RAIL GRINDERS

PEDESTAL RAIL GRINDER (GAS POWERED)



Part Number	Description
SBG141	3.5 HP (Briggs & Stratton® I/C) Grinder with 6' Shaft & Housing Base Plate Shaft Adapter Straight Spindle 6" Wheel & Guard Dressing Stone

SBG141 DRILL ATTACHMENT PARTS




Part Number	Description
SBL165	Drill Attachment – complete with angle spindle & drill chuck
SBL165SA	Drill Attachment – Frame Only
SB22127	Angle spindle – 10:1 ratio
SB22127A	Replacement gear kit for Angle spindle
SBS2171A	Drill chuck – 1/8" to 5/8" key type
SBS2171AK	Drill chuck key
SBT385B	3/8" Bonding bit / round shank

Grinders & Bonding Accessories

RAIL GRINDERS

PORTABLE GRINDER (2 CYCLE GASOLINE POWERED)



Part Number	Description
SBG150	Rail Grinder – 39cc, 6,000 rpm, 18 lbs.
SBG150WC	Rail Grinder with Storage Case
SBS2333	6" Grinding Wheel – 3/4" original replacement
SB22122	6" Grinding Wheel – 1" replacement
S2129	6" Beveled Grinding Wheel – Head Free Rail
SBK104	Slotting Wheel Kit – Includes 6" x 1/8" slotting wheel, spacer, depth gauge, insulation
22128	6" Slotting Wheel with mounting spacer
22128P	6" Slotting Wheel
SBT365	Silicon Rubber Insulation – 3 oz tube

Grinders & Bonding Accessories

RAIL GRINDERS

PORTABLE GRINDER (4 CYCLE GASOLINE POWERED)



Part Number	Description
SBG200	Rail Grinder – 1.1 hp,10,500 rpm, 13 lbs.
SBG20015	Cup Style Wheel for SBG200
SBG20018	Plug Style Wheel for SBG200
SBG200COFF	Cutting Adapter, Guard, and Cutting Wheel
SBG20027	Cutting Wheel replacement (std. package of 5)

PORTABLE GRINDER (BATTERY POWERED)



Part Number	Description
SBG100	Rail Grinder, 18 volt, 6,500 rpm, 7 lbs
SBG20025	Cleaning Wheel, 4.5" x .25" Depressed center, designed for right angle use (std. package of 5)
SBG20027	Cutting Wheel, Disk type, 4.5" x .08" (std. package of 5)
SBG20046	Cleaning and Cutting Wheel, Depressed center, designed for right angle use (std. package of 5)

Grinders & Drilling Machines


RAIL DRILLING MACHINES

PORTABLE DRILLING MACHINE (2 CYCLE GASOLINE POWERED)



Part Number	Description
715685	Rail Drilling Machine SBV-VS, 28 lbs for drill hole dia. 3/8" up to 1-3/8", 267 rpm

PORTABLE DRILLING MACHINE (QUIET 4 CYCLE GASOLINE POWERED)



Part Number	Description
715412	Rail Drilling Machine SBV-V4, 28 lbs for drill hole dia. 3/8" up to 7/8", 267 rpm

Grinders & Drilling Machines

RAIL DRILLING MACHINES

PORTABLE DRILLING MACHINE (BATTERY POWERED)



Part Number	Description
715400	Rail Drilling Machine SBM-E391, 28 lbs, 48V for drill hole dia. 3/8" up to 7/8", 390 rpm

PORTABLE DRILLING MACHINE (AC ELECTRIC POWERED)



Part Number	Description
715404	Rail Drilling Machine SBM-E230, 28 lbs for drill hole dia. 3/8" up to 1-3/8", 280 rpm, requires 220/230V AC

Grinders & Drilling Machines

RAIL DRILLING MACHINES

CLAMPING DEVICES



Part Number	Description
715360	BSK1 head clamping for normal rails, 7 lbs.
715370	BSK2 head clamping for grooved rails, 9 lbs.
715380	BSF1 rail foot clamping device, 9 lbs.


RAIL DRILLING ACCESSORIES



Part Number	Description
716207	Rail Drilling Template 90 LB, 2.58 in.
716204	Rail Drilling Template 100 LB, 2.63 in.
716203	Rail Drilling Template 115 LB, 2.98 in.
716211	Rail Drilling Template 132 RE, 3.20 in.
716212	Rail Drilling Template 136 LB, 3.36 in.
716213	Rail Drilling Template 141 AB, 3.47 in.
XXXXXX	Other Drilling Templates available on request
715075	Drilling Coolant Concentrate, 2.64 gal. (10 ltr.)
715375	Coolant Tank & Pump

Tools & Bonding Accessories

STRIPPING TOOLS 2 X 2



Part Number	Description	
	Bushing 1	Bushing 2
SBRT36100106	3/16" Bond Strand, 4/64" Insulation	#6 Solid, Concentric 8/64" Insulation
SBRT36100134	3/16" Bond Strand, 6/64" Insulation	#6 Concentric, 5/64" Insulation
SBRT36100135	3/16" Bond Strand, 4/64" Insulation	#9 Solid, 10/64" Insulation
SBRT36100136	3/16" Bond Strand, 4/64" Insulation	3/16" Bond Strand, 6/64" Insulation
SBRT36100138	3/16" Bond Strand, 6/64" Insulation	#6 Solid, Concentric 8/64" Insulation
SBRT36100139	3/16" Bond Strand, 4/64" Insulation	#6 Solid, 11/64" Insulation
SBRT36100140	3/16" Bond Strand, 6/64" Insulation	#6 Solid, 11/64" Insulation
SBRT36100142	#6 Solid, 1/64" Insulation	#6 Solid, 12/64" Insulation
SBRT36100147	3 Conductor, 6/64" Insulation	#6 Solid, 6/64" Insulation
SBRT36100148	7 Conductor, 6/64" Insulation	#9 Solid, 6/64" Insulation
SBRT36100149	3/16" Bond Strand, 6/64" Insulation	#6 Solid, 7/64" Insulation
SBRT36100150	5 Conductor, 6/64" Insulation	#9 Solid, 6/64" Insulation
SBRT36100152	10 Conductor, 6/64" Insulation	12 Conductor, 6/64" Insulation
SBRT36100177	3/16" Bond Strand, 4/64" Insulation	#6 Solid, 12/64" Insulation

BLADES


Part Number	Description
SBRTCB6667	Replacement Blades-Pkg of 5

ACCESSORY

Part Number	Description
SBRT36024	2 x 2 Tool Driver Adapter

Tools & Bonding Accessories

STRIPPING TOOLS 4 X 4




Part Number	Description	
	Bushing 1	Bushing 2
SBRT36000906	3/16" Bond Strand, 4/64" Insulation	#6 Solid, 11/64" Insulation
SBRT36000907	3/16" Bond Strand, 4/64" Insulation	#6 Solid, 11/64" Insulation
SBRT360001004	3/16" Bond Strand, 4/64" Insulation	#6 Solid, 11/64" Insulation
SBRT360001010	3/16" Bond Strand, 6/64" Insulation	3/16" Bond Strand, 6/64" Insulation
	Bushing 3	Bushing 4
SBRT36000906	#6 Solid, 12/64" Insulation	#9 Solid, 10/64" Insulation
SBRT36000907	#6 Solid, 12/64" Insulation	2/0 Ropelay, 6/64" Insulation
SBRT360001004	#6 Solid, 12/64" Insulation	3/16" Bond Strand, 6/64" Insulation
SBRT360001010	#6 Solid, 11/64" Insulation	#6 Solid, 12/64" Insulation

REPLACEMENT & ADDITIONAL BUSHINGS

Part Number	Description
SBRT1034048	3/16" Bond Strand, 4/64 Insul.
SBRT1040075	3/16" Bond Strand, 6/64 Insul.
SBRT1037590	#6 Solid, 7/64" Insulation
SBRT10450110	#6 Solid, Concentric 8/64" Insul.
SBRT10515145	#6 Solid, 11/64" Insulation
SBRT10550162	#6 Solid, 12/64" Insulation
SBRT1030075	#9 Solid, 6/64" Insulation
SBRT10430135	#9 Solid, 10/64" Insulation
SBRT1036060	#6 Concentric, 5/64" Insulation
SBRT11102575	3 Conductor, 6/64" Insulation
SBRT11100075	5 Conductor, 6/64" Insulation
SBRT11105075	7 Conductor, 6/64" Insulation
SBRT1187575	10 Conductor, 6/64" Insulation
SBRT1197575	12 Conductor, 6/64" Insulation
SBRT1067575	2/0 Ropelay, 6/64" Insulation


Tools & Bonding Accessories

MISCELLANEOUS TOOLS



Part Number	Description
T304	Slip Joint Pliers
T305	Screw Driver
T313	Card Cloth Brush
T320	Flint Ignitor
T320A	Replacement Flints (10 each/package)
T328	Disk Container
T332	Engineers Hammer, 3 lb. size
T334	Adjustable 6" Wrench for Welder
SBB394C	T-34 Rail Head and Web Cleaner, One Universal Tool
SBA127A	Replacement Cutting Disk for T-34
B136D	Mold Cleaner
T403	Mold Sealer - 2 Pound Tub
B32130	Flint Ignitor Extension (30")

FLINT IGNITOR EXTENSION




Total Facility Protection

PRODUCTS FOR HIGH FREQUENCY, LOW IMPEDANCE, PATH TO GROUND

- Meets AAR Recommendations
- Modular Design for Field Assembly and Future Expansion
- Pre-Engineered and Manufactured Panels
- Design Assistance for Special Applications
- Separation of “Clean” from “Dirty” Wiring
- Improved Arrester Performance

4 TERMINAL BLOCK

- Integrated Test Terminal
- Slot for Low Impedance Busbar
- Integral, High Current Busbar




Part Number	Description
SBB2700A2B10	Terminal Block - Box of 10
B2700A2C1WH	Terminal Block with AAR Hardware
B2700HC36T	Terminal Strip - 36"
B2700HC48T	Terminal Strip - 48"
B2700HC60T	Terminal Strip - 60"

Contact nVent For Design Assistance

Solutions to Power Quality Problems

TYPICAL SIGNAL BUNGALOW POWER PROTECTION LAYOUT




Part Number	Description
EPD120/240TDFL	120/240VAC primary surge protector, TD Technology, flying lead, 85kA
EPD100HZ120V	120VAC, 100HZ primary surge protector, fused, TD Technology, 120kA
EPD100HZ120240V	120/240VAC, 100HZ, primary surge protector, fused, TD Technology, 120kA
EPD100HZ240V	240VAC, 100HZ primary surge protector, fused, TD Technology, 120kA

Solutions to Power Quality Problems

USING PROTECTION DEVICES FROM NVENT FOR TOTAL FACILITY PROTECTION

DISCRIMINATING (TD) TECHNOLOGY




Part Number	Description
EPD1224ATAAR	12 & 24VDC secondary power protector, 30A max load
EPD120TDAARB	120VAC secondary power protector, 30A max load
EPD240TDAARB	240VAC secondary power protector, 30A max load
ETSP23050	50VDC / 35VAC Signal Protector, 30kA, 2 terminal arrestor
ETSP33050	50VDC / 35VAC Signal Protector, 30kA, 3 terminal arrestor
ETSP230170	170VDC / 120VAC Signal Protector, 30kA, 2 terminal arrestor
ETSP330170	170VDC / 120VAC Signal Protector, 30kA, 3 terminal arrestor

Primary Surge Protection

EPD POWER SURGE DEVICES

- Transient Discriminating Technology provides increased service life
- Parallel hybrid TVSS technology
- Low let-through voltage
- Visual status indication
- 5 year limited warranty



Part Number	Description
EPD120/240TDFL	120/240VAC primary surge protector, TD Technology, flying lead, 85kA

- Transient Discriminating Technology provides increased service life
- Series hybrid TVSS technology
- Optimal let-through voltage performance
- Visual status indication
- 5 year limited warranty


Part Number	Description
EPD100HZ120V	120VAC, 100HZ, primary surge protector, fused, TD Technology, 120kA
EPD100HZ120240V	120/240VAC, 100HZ, primary surge protector, fused, TD Technology, 120kA
EPD100HZ240V	240VAC, 100HZ, primary surge protector, fused, TD Technology, 120kA

Contact nVent for additional information on our full line of nVent ERICO surge protection devices.

Primary Surge Protection

ETSP TRACK CIRCUIT PROTECTION DEVICES

- Hybrid technology comprising gap-type voltage switching and varistor-type voltage clamping components
- Design helps ensure a fail-safe, open-circuit, failure mode
- Visual status indication to aid serviceability
- Device and cover plainly marked with voltage and part number to help ensure proper application
- 50kA maximum surge rating provides protection suitable for exposed trackside equipment
- Low let-through voltage
- Epoxy coating helps ensure stability of operation under adverse conditions and in locations of high humidity
- 5 year limited warranty



Part Number	Description
ETSP23050	50VDC/35VAC Signal Protector, 30kA, 2 terminal arrestor
ETSP33050	50VDC/35VAC Signal Protector, 30kA, 3 terminal arrestor
ETSP230170	170VDC/120VAC Signal Protector, 30kA, 2 terminal arrestor
ETSP330170	170VDC/120VAC Signal Protector, 30kA, 3 terminal arrestor

Secondary Surge Protection

EPD POWER SURGE DEVICES

- Series hybrid TVSS technology
- Universal design for 12VDC & 24VDC applications
- 30A series filter
- High surge rating provides a high level of protection and long operational life
- Low let-through voltage
- RFI/EMI filtering
- Visual status indication
- AAR terminals
- 5 year limited warranty




Part Number	Description
EPD1224ATAAR	12 & 24VDC secondary power protector, 30A max load
EPD120TDAARB	120VAC secondary power protector, 30A max load
EPD240TDAARB	240VAC secondary power protector, 30A max load

Peripheral Power Protection

DINLINE SURGE FILTERS

- Compact design – small footprint
- High efficiency sine wave filtering
- DIN rail mount
- Status indication
- High surge rating, 50kA (TDF), 8kA (DSF)
- TD technology

TRANSIENT DISCRIMINATING FILTER & DINLINE SURGE FILTER (TDF & DSF)



Part Number	Description
DSF6A30V	24VDC/30VAC 1 phase 2W+G, 6A series filter
TDF3A120V	120V 1 phase 2W+G, 50kA, 3A series filter
TDF3A240V	240V 1 phase 2W+G, 50kA, 3A series filter
TDF10A120V	120V 1 phase 2W+G, 50kA, 10A series filter
TDF10A240V	240V 1 phase 2W+G, 50kA, 10A series filter
TDF20A120V	120V 1 phase 2W+G, 50kA, 20A series filter
TDF20A240V	240V 1 phase 2W+G, 50kA, 3A series filter
557850	Din Rail, 2 meters in length, 7.5 mm height

DIN SURGE DIVERTER

- Photo Voltaic and Telepower distribution
- Surge rating to 40kA - Ideal for exposed wiring
- 24VDC & 48VDC distribution systems


Part Number	Description
DSD1402BR24/48	24/48VDC 36 mm DIN 43 880 Profile, 40kA 8/20μs

Communications & Data Equipment Protection

RADIO COMMUNICATIONS PROTECTION

- Robust design
- Simple plug-in installation
- CSP models to suit N and BNC cable terminations
- CSP bulkhead N-type versions available
- High impulse current rating (20kA 8/20µs)
- Wide operating frequency spectrum
- Low insertion and return loss
- Mounting bracket and ground lead included
- CE approved

COAXIAL SURGE PROTECTOR - CSP



Part Number	Description
CSPNMF90	N-Type M to F, 72-108V
CSPNMF600	N-Type M to F, 480-720V
CSP1BN90	BNC-Type M to F, 72-108V
CSPBNC600	BNC-Type M to F, 480-720V
CSPNB90	Bulkhead N-Type F to F, 72-108V
CSPNB600	Bulkhead N-Type F to F, 480-720V

How to Choose the Correct CSP

For RF circuit protection the CSP is available with a choice of two nominal clamping voltages. The selection of the CSP unit is based on the peak transmitting power of the communication circuit. From this the peak circuit voltage is calculated and the CSP with the next highest clamping voltage is selected.

The formula is:

$$V_{peak} = VSWR \times 1.4 \times \sqrt{50 \times \text{Transmit Power}}$$

Where VSWR is the Voltage Standing Wave Ratio (use 1.5 if unsure) and Transmit Power is in Watts.

If $V_{peak} < 72V$ use CSPxxx90

If $V_{peak} > 72V$ & $< 480V$ use CSPxxx600

Grounding

GROUND RODS





Figure 1



Figure 2

Part Number	Diameter	Figure	Standard Packaging	Length
Pointed Copper-Bonded Rods				
615850	5/8"	1	5	5'
615880	5/8"	1	5	8'
615800	5/8"	1	5	10'
613480	3/4"	1	5	8'
613400	3/4"	1	5	10'
Pointed Copper-Bonded Rod Couplings				
CC58	5/8"		25	
CC34	3/4"		25	
Sectional Copper-Bonded Rods				
635880	5/8"	2	5	8'
635800	5/8"	2	5	10'
633480	3/4"	2	5	8'
633400	3/4"	2	5	10'
Sectional Copper-Bonded Rod Couplers				
CR58	5/8"		25	
CR34	3/4"		25	

CHEMICAL GROUND ROD ELECTRODE KIT



Part Number	Description
ECRV10 "xx"4"y"	10' Vert. w/4' Pigtail, Backfill Material, Cover
ECRV12 "xx"4"y"	12' Vert. w/4' Pigtail, Backfill Material, Cover
ECRV15 "xx"4"y"	15' Vert. w/4' Pigtail, Backfill Material, Cover
ECRV20 "xx"4"y"	20' Vert. w/4' Pigtail, Backfill Material, Cover
ECRH10 "xx"4"y"	10' Horz. w/4' Pigtail, Backfill Material, Cover
ECRH12 "xx"4"y"	12' Horz. w/4' Pigtail, Backfill Material, Cover
ECRH15 "xx"4"y"	15' Horz. w/4' Pigtail, Backfill Material, Cover
ECRH20 "xx"4"y"	20' Horz. w/4' Pigtail, Backfill Material, Cover

"xx" – Cable code for specified pigtail conductor (4/0 conc typical)

"y" – Pigtail orientation: U-up, D-down

Extended "sectional" versions available for rods longer than 20 feet.

Grounding

CADWELD ONE SHOT


CONNECTIONS

The Cadweld One Shot consists of a ceramic mold, disk, F80 welding material and cover.


- Disposable ceramic unit eliminates graphite mold.
- Produces a permanent connection that will not loosen or corrode.
- Fits both plain or threaded copperclad and full size, steel and stainless steel rods.

Standard Package 6

CABLE-TO-GROUND ROD



Ground Rod Size	Conductor Size		Connector Part Number	
	Solid	Stranded	Type GR	Type GT
1/2"	#6, 8	#8	SBGR1141G	SBGT1141G
	3, 4	4, 6		SBGT1141L
	1, 2	2, 3		SBGT1141V
5/8"	6, 8	8	SBGR1161G	SBGT1161G
	3, 4	4, 6	SBGR1161L	SBGT1161L
	1, 2	2, 3	SBGR1161V	SBGT1161V
3/4"	6, 8	8	SBGR1181G	SBGT1181G
	3, 4	4, 6	SBGR1181L	SBGT1181L
	1, 2	2, 3	SBGR1181V	SBGT1181V



Ground Rod Size	Conductor Size		Connector Part Number	
	Solid	Stranded	Type NT	Type NX
1/2"	#6, 8	#8	SBNT1141G	
	3, 4	4, 6	SBNT1141L	
	1, 2	2, 3	SBNT1141V	
5/8"	6, 8	8	SBNT1161G	SBNX1161G
	3, 4	4, 6	SBNT1161L	SBNX1161L
	1, 2	2, 3	SBNT1161V	SBNX1161V
3/4"	6, 8	8	SBNT1181G	SBNX1181G
	3, 4	4, 6	SBNT1181L	SBNX1181L
	1, 2	2, 3	SBNT1181V	SBNX1181V

Other sizes available - Contact nVent with application.

Grounding

GEM GROUND

ENHANCEMENT MATERIAL




Part Number	Description
GEM25A	25 Pound Bag

A superior conductive material that helps solve the toughest grounding problems.

- Improves grounding effectiveness regardless of soil conditions.
- Can use where ground rods cannot be driven or where limited land area makes adequate grounding difficult with conventional methods.
- Unmatched for reducing earthing resistance and maintaining low resistance permanently.
- Effective - Typical resistivity 12-18 OHM cms (20 times lower than Bentonite clay)

GROUND TESTERS

EARTH SYSTEMS TESTER UNITS





Part Number	Description
EST3640	Fall-of-Potential, ground resistance (2 & 3 Point) measurements
EST4620	4-Point Fall-of-Potential, 2 & 3-Point Fall-of-Potential Step Voltage measurements
EST4630	4-Point Fall-of-Potential, 2 & 3-Point Fall-of-Potential, Step Voltage measurements
EST6472	4-Point Fall-of-Potential, 3-Point Fall-of-Potential, 3-Point Fall-of-Potential, 3-Point earth coupling measurements & frequency scan 40 to 513Hz noise





Grounding

ALUMINUM-COPPER GROUNDING STUD

ALUMINUM SIGNAL MAST

<div><div></div><div></div></div>		
<div><div>Figure 1</div><div>Figure 2</div></div>		
Part Number	Description (#6 Solid Copper Pigtail)	Figure Number
Aluminum-Copper Grounding Stud		
SBB855E1G72	with 72" long Pigtail	1
SBB855E1G96	with 96" long Pigtail	1
Signal Mast Grounding Clamp		
SBB852A8C1G48	with 48" long Pigtail - 3" to 8" Mast Dia.	2
SBB852A8C1G72	with 72" long Pigtail - 3" to 8" Mast Dia.	2
SBB852A12C1G96	with 96" long Pigtail - 3" to 12" Mast Dia.	2


ALUMINUM SIGNAL CASE

<div><div></div><div></div><div></div><div></div></div>		
<div><div>Figure 3</div><div>Figure 4</div><div>Figure 5</div><div>Figure 6</div></div>		
Part Number	Description	Figure Number
Aluminum-Copper Grounding Stud		
SBB855C1G36	with 36" long Pigtail, #6 Solid	3
SBB855C1G48	with 48" long Pigtail, #6 Solid	3
SBB855C1K48	with 48" long Pigtail, #4 Solid	3
SBB855F1G48	with 36" long Pigtail, #6 Solid	4
SBB855G1G30	with 30" long Pigtail, #6 Solid	5
Feed-Through Stud		
SBB853B	with Hardware	6
SBB853A72	with Hardware and 72" long Pigtail, #6 Solid	6


Other Pigtail sizes available.

Grounding

CADWELD CONNECTIONS CABLE-TO-CABLE



Cable Size	Welder Part No.	F80 Welding Material
#6 Sol	SB02SS6	SB25
4	SB03SS1L	SB25
2	SB10SS1V	SB32
3/16"	SB02SS3	SB25
3/16"	SB02SS3001	SB32



Cable Size		Welder Part No.	F80 Welding Material
Run	Tap		
#6 Sol	#6 Sol	SB10PC66	SB32
#6 Sol	#6 Sol	SB02SC66001	SB25
#6 Sol	5/16"	SB02SC65001	SB32
3/16"	#6 Sol	SB02SC36001	SB25
3/16"	3/16"	SB02SC33001	SB25


CADWELD ONE SHOT CONNECTIONS

The Cadweld One Shot consists of a ceramic mold, disk, F80 welding material and cover.

- Disposable ceramic unit eliminates graphite mold.
- Produces a permanent connection that will not loosen or corrode.

Standard Package 6

CABLE-TO-CABLE




Conductor Size	Stranded	Parallel Tap Part Number
Solid		
3, 4, 6	4, 6	SBPG11L

Grounding


CABLE-TO-STEEL STRUCTURES

FLAT VERTICAL SURFACE



Cable Size	Welder Part No.	F80 Welding Material
Sol 4	SB01VS4	SB25
Sol 6	SB01VS6	SB25
Sol 6	SB01VS6001	SB32
Sol 8	SB01VS8	SB25
3/16"	SB01VS3	SB25

ROUND VERTICAL SURFACE




Cable Size	Welder Part No.	F80 Welding Material
Sol 6	SB01VS6V5C	SB25
Sol 6	SB01VS6V5C01	SB32


Grounding

CADWELD CONNECTIONS CABLE-TO-STEEL STRUCTURES

HORIZONTAL FLAT SURFACE




Cable Size	Welder Part No.	F80 Welding Material
Sol 6	SB41HA6	SB32
Sol 6	SB41HA6001	SB25



Cable Size	Welder Part No.	F80 Welding Material
1/4" AAR	SB01HV10001	SB32
Split Stud	SB01HV10002	2-SB25
	SB01HX10002	SB32

SBK012 - 1/4" Split Stud Kit (Includes AAR thread stud, washer, clamping nut and binding nut)

OTHER TYPES AND SIZES AVAILABLE



Alpha-Numeric Listing

Part Number	Page	Part Number	Page
22128	25	B136D	32
22128P	25	B154A	17
557850	39, 40	B194D	10
613400	42	B2516C1	10
613480	42	B2516C	10
615800	42	B2700A2C1WH	33
615850	42	B2700HC36T	33
615880	42	B2700HC48T	33
633400	42	B2700HC60T	33
633480	42	B30174	10
635800	42	B32130	32
635880	42	B323L	11
715075	29	C105B	13
715360	29	CC34	42
715370	29	CC58	42
715375	29	CR34	42
715380	29	CR58	42
715400	28	CSPBNC600	41
715404	28	CSP1BN90	41
715412	27	CSPNB600	41
715685	27	CSPNB90	41
716203	29	CSPNMF600	41
716204	29	CSPNMF90	41
716207	29	DSD1402BR24/48	39
716211	29	DSF6A30V	39
716212	29	ECRH10"XX"4"Y"	42
716213	29	ECRH12"XX"4"Y"	42
A140	18	ECRH15"XX"4"Y"	42
A140WT	18	ECRH20"XX"4"Y"	42
A154	20	ECRV10"XX"4"Y"	42
A203	20	ECRV12"XX"4"Y"	42
A205	20	ECRV15"XX"4"Y"	42
A219	20	ECRV20"XX"4"Y"	42
A2314J	16	EPD100HZ120240V	34, 36
A2363J	16	EPD100HZ120V	34, 36
A2364J	16	EPD100HZ240V	34, 36
A2367J	16	EPD120/240TDFL	34, 36
A2412J	16	EPD120TDAARB	35, 38
A248B	20	EPD1224ATAAR	35, 38
A251	20	EPD240TDAARB	35, 38
A806A12F100	17	EST3640	44
A806A12F1000	17	EST4620	44
B101AA	17	EST4630	44

Alpha-Numeric Listing

Part Number	Page	Part Number	Page
EST6472	44	SB10SS1V	46
ETSP230170	35, 37	SB20104	8
ETSP23050	35, 37	SB20108	8
ETSP330170	35, 37	SB20112	8
ETSP33050	35, 37	SB20116	8
GCHSC67	23	SB20118	8
GCHSC78	23	SB20128	8
GCHSC89	23	SB20136	8
GCHSC910	23	SB20175	8
GCHSC1011	23	SB20175HF	8
GCHSC1214	23	SB22122	25
GCHSC1518	23	SB22127	24
GCHSC1924	23	SB22127A	24
GCHSC2530	23	SB25	11, 17, 46 - 48
GEM25A	44	SB32	11, 17, 46 - 48
M22	13	SB41HA6	48
RTB12S3	40	SB41HA6001	48
RTB30S3	40	SBA127A	32
RTB50S2	40	SBA206	20
RTB60S1	40	SBA2510B	21
S119	10	SBA2511B	21
S2044	10	SBA2512B	21
S2129	25	SBA252S0	21
S2659	10	SBA252S1	21
SB01HV10001	48	SBA252S2	21
SB01HV10002	48	SBA254A1	21
SB01HX10002	48	SBA255D1	21
SB01VS3	47	SBA258A1	22
SB01VS4	47	SBA258B1	22
SB01VS6	47	SBA258D1	22
SB01VS6001	47	SBA260A	22
SB01VS6V5C	47	SBB200A	13
SB01VS6V5C01	47	SBB200B	13
SB01VS8	47	SBB200C	13
SB02SC33001	46	SBB200D	13
SB02SC36001	46	SBB200E	13
SB02SC65001	46	SBB2516A	10
SB02SC66001	46	SBB2516APRWH	10
SB02SS3	46	SBB2700A2B10	33
SB02SS3001	46	SBB2721B	19
SB02SS6	46	SBB2721CS72	19
SB03SS1L	46	SBB2721F	19
SB10PC66	46	SBB2721G	19

Alpha-Numeric Listing

Part Number	Page	Part Number	Page
SBB2721H	19	SBG20046	26
SBB2721JS72	19	SBG200COFF	26
SBB2721JS72SP	19	SBGR1141G	43
SBB2721S	19	SBGR1161G	43
SBB2721T	19	SBGR1161L	43
SBB2721V	19	SBGR1161V	43
SBB2721VS72	19	SBGR1181G	43
SBB2721WS300	19	SBGR1181L	43
SBB2721WS600	19	SBGR1181V	43
SBB343A	11	SBGT1141G	43
SBB343B	11	SBGT1141L	43
SBB343C	11	SBGT1141V	43
SBB343D	11	SBGT1161G	43
SBB343E	11	SBGT1161L	43
SBB394C	32	SBGT1161V	43
SBB429F	10	SBGT1181G	43
SBB492	9, 10	SBGT1181L	43
SBB852A8C1G72	45	SBGT1181V	43
SBB852A8C1G48	45	SBHFT6A	9
SBB852A12C1G96	45	SBHFT6B	9
SBB853A72	45	SBHFT6C	9
SBB853B	45	SBHFT6D	9
SBB855C1G36	45	SBHFT7E	9
SBB855C1G48	45	SBHFT7K	9
SBB855C1K48	45	SBK012A	17
SBB855E1G72	45	SBK012B	17
SBB855E1G96	45	SBK104	25
SBB855F1G48	45	SBL165	24
SBB855G1G30	45	SBL165SA	24
SBC105R	13	SBM456	9, 10
SBC105SA	13	SBM456F	10
SBC105S	13	SBNT1141G	43
SBD50	11	SBNT1141L	43
SBD51	11	SBNT1141V	43
SBG100	26	SBNT1161G	43
SBG141	24	SBNT1161L	43
SBG150	25	SBNT1161V	43
SBG150WC	25	SBNT1181G	43
SBG200	26	SBNT1181L	43
SBG20015	26	SBNT1181V	43
SBG20018	26	SBNX1161G	43
SBG20025	26	SBNX1161L	43
SBG20027	26	SBNX1161V	43

Alpha-Numeric Listing

Part Number	Page	Part Number	Page
SBNX1181G	43	SBRT36100135	30
SBNX1181L	43	SBRT36100136	30
SBNX1181V	43	SBRT36100138	30
SBPAC3A	15	SBRT36100139	30
SBPAC3G	15	SBRT36100140	30
SBPAC3R	15	SBRT36100142	30
SBPAC3Y	15	SBRT36100147	30
SBPACGBJ4	15	SBRT36100148	30
SBPAJ3"XX"	14	SBRT36100149	30
SBPAJA"XX"	14	SBRT36100150	30
SBPAJB"XX"	14	SBRT36100152	30
SBPAJC"XX"	14	SBRT36100177	30
SBPAJD"XX"	14	SBRTCB6667	30
SBPAJG"XX"	14	SBS09C	11
SBPAJN"XX"	14	SBS10	11
SBPAJP"XX"	14	SBS11C	11
SBPAJR"XX"	14	SBS12C	11
SBPAW35	15	SBS13C	11
SBPG11L	46	SBS17CBARE	17
SBPMJ3"X"	15	SBS2171A	24
SBPMJR"X"	15	SBS2171AK	24
SBPMJS"X"	15	SBS2333	25
SBRT1030075	31	SBS24882	8
SBRT1034048	31	SBS24883	8
SBRT1036060	31	SBS24884	8
SBRT1037590	31	SBS3086R48	18
SBRT1040075	31	SBS3086R48WT	18
SBRT10430135	31	SBS3086S48	18
SBRT10450110	31	SBS3086S48WT	18
SBRT10515145	31	SBS5838	9, 10
SBRT10550162	31	SBS5838F	10
SBRT1067575	31	SBS5839	9
SBRT11100075	31	SBS898	9, 10
SBRT11102575	31	SBS898F	10
SBRT11105075	31	SBS8BARE	17
SBRT1187575	31	SBS8CBARE	17
SBRT1197575	31	SBS8CINORG	17
SBRT360001004	31	SBS8CINSUL	17
SBRT360001010	31	SBS8INORG	17
SBRT36000906	31	SBS8INSUL	17
SBRT36000907	31	SBS8LBARE	17
SBRT36024	30	SBS8LINSORG	17
SBRT36100106	30	SBS8LINSUL	17
SBRT36100134	30	SBS8TCINS	17

Alpha-Numeric Listing

Part Number	Page	Part Number	Page
SBS8TCINS664	17	SBTBTB4E	11
SBS8TCINSRD	17	SBTBTB5B	13
SBS8TDINSUL	17	SBTBTB5C	13
SBS8TINSRD	17	SBTBTB5D	13
SBS8TINSUL	17	SBTBTB5E	13
SBS8TLINS664	17	SBXSB33"X"	12
SBS925	9, 10	SBXSHU2	8
SBS925F	10	SBXSHU3	8
SBT031DJ	16	SBXSHU4	8
SBT365	25	SBXSJ33"X"	12
SBT382B	16	SBXSS33"X"	12
SBT382BWH	16	SBXST21A	13
SBT382BWPH	16	SBXST6A	9
SBT385B	24	SBXST6C	9
SBT408	16	SBXST6D	9
SBTBB33"X"	12	SBXST7D	9
SBTBB34"X"	12	SBXSTB4A	11
SBTBB36"X"	12	SBXSTB5A	13
SBTBB54"X"	12	T304	32
SBTBBU4A	12	T305	32
SBTBCU412	12	T313	32
SBTBJ33"X"	12	T320	32
SBTBJ34"X"	12	T320A	32
SBTBJ36"X"	12	T328	32
SBTBJ54"X"	12	T332	32
SBTBS33"X"	12	T334	32
SBTBS34"X"	12	T369	16
SBTBS36"X"	12	T375	20
SBTBS54"X"	12	T403	32
SBTBT21B	13	TDF10A120V	39
SBTBT21C	13	TDF10A240V	39
SBTBT21D	13	TDF20A120V	39
SBTBT21E	13	TDF20A240V	39
SBTBT6A	9	TDF3A120V	39
SBTBT6B	9	TDF3A240V	39
SBTBT6C	9	UTB110SP	40
SBTBT6D	9	UTB15SP	40
SBTBT6E	9	UTB30SP	40
SBTBT7B	9	UTB5SP	40
SBTBT7F	9	UTB60SP	40
SBTBT7G	9	UTBTA	40
SBTBTB4B	11		
SBTBTB4C	11		
SBTBTB4D	11		

Product Literature

CAPABILITIES

R195S	Six Point Plan of Protection for Railway Facilities
R503B	Rail Products Brochure
X7A	Facility Electrical Protection Solutions

GROUNDING

E1A	Cadweld - Welded Electrical Connections
RT7F	GEM - Ground Enhancement Material

LIGHTNING PROTECTION

E256C	nVent ERICO SYSTEM 2000 - Passive Protection
E429B	nVent ERICO SYSTEM 3000 - Active Protection
R196S	Terminal Block
RT7J	Lightning Protection for Railway Electrical Equipment

SURGE PROTECTION

E430C	Catalog
R199S	EPD Primary Surge Protection Device
R558S	Electronic Track Circuit Protection
R601S	EPD 120V & 240V Secondary AC Surge Protection
R604S	EPD 12/24VDC 30A Secondary DC Surge Protection

Product Literature

TOOLS

R337S	SBG150 Portable Grinder
R408C	nVent ERICO ERICONCONTACT Mechanical Connections to Rail
R464S	SBG100 Portable Grinder
R474S	SBG200 Portable Grinder

TRAINING

R383D	Signal Bond Training CD
SBA7D	Installers & Inspectors Guide

Notes

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER



nVent.com/ERICO

WARNING: nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at nVent.com/ERICO and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and/or death, and void your warranty.

©2018 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice. ERICO-CAT-R603C-R358LT16NAEN-EN-1805