

## Butt Splices



- Rated at 600 Volt Max.
- Temperature rating: 167 °F (75 °C).

| 22-18 Gauge | Part # | Pkg Qty  |
|-------------|--------|----------|
|             | 10-121 | 100/clam |
|             | 15-121 | 15/clam  |
|             | 20-121 | 22/clam  |
|             | 75-121 | 75/clam  |



| 16-14 Gauge | Part # | Pkg Qty  |
|-------------|--------|----------|
|             | 10-123 | 100/clam |
|             | 15-123 | 15/clam  |
|             | 20-123 | 21/clam  |
|             | 75-123 | 75/clam  |



| 12-10 Gauge | Part # | Pkg Qty |
|-------------|--------|---------|
|             | 10-126 | 50/clam |
|             | 15-126 | 15/clam |
|             | 20-126 | 15/clam |
|             | 75-126 | 50/clam |



## Tap Splices

- Secure connections without stripping wire.
- Rated at 600 Volt Max.
- Temperature rating: 221 °F (105 °C).

| 22-18 Gauge | Part #  | Pkg Qty              |
|-------------|---------|----------------------|
|             | 15-2218 | 5/clam               |
|             | 20-2218 | 5/clam <sup>12</sup> |



| 18-14 Gauge | Part # | Pkg Qty              |
|-------------|--------|----------------------|
|             | 10-100 | 25/clam              |
|             | 20-100 | 5/clam <sup>12</sup> |
|             | 21-100 | 5/clam <sup>13</sup> |



| 12-10 Gauge | Part #  | Pkg Qty              |
|-------------|---------|----------------------|
|             | 20-1210 | 4/clam <sup>12</sup> |



<sup>12</sup>10 clams/master    <sup>13</sup>5 clams/master

## Terminal Blocks



- Rated at 30 Amp/600 Volt max.
- Temperature rating: -40 °F (-40 °C) to 260 °F (130 °C).
- Wire range 22-10 AWG.
- Accepts #8 stud size.

| Part #  | No. of Poles | Pkg Qty |
|---------|--------------|---------|
| GTB-406 | 6            | 1/clam  |
| GTB-408 | 8            | 1/clam  |
| GTB-410 | 10           | 1/clam  |



GTB-406



GTB-408



GTB-410