



Kwikflex® NMLT Straight Conduit Connectors

FEATURES & BENEFITS


- Available 3/8" through 2"
- All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease, & common solvents
- No disassembly required. Instead, the installer simply pushes the conduit or tubing onto the ferrule, tightening the domed sealing nut. The completed assembly can then be secured in the chassis by the locknut (or first secure the connector into an NPT threaded hole)
- No threading of the conduit or tubing required to install, eliminating the possibility of cutting the conduit & creating leak paths
- Standard color - Gray
- Complete conduit/connector system is reusable. Conduit will not wind tight onto the connector during assembly & can be easily removed by pulling while turning in a clockwise direction
- Suitable for indoor/outdoor use; for original equipment manufacturers or field installers
- Lower installed cost
- Molded of type nylon 6. Flammability classification 94V-2; temperature index 125°C
- "O" Ring & steel locknut included

APPLICATIONS

- HVAC equipment
- Machine tools
- Marine equipment
- Motors & controls
- Printing equipment
- Pumps
- Refrigeration equipment
- Assemblies
- Wire hook-up



SPECIFICATIONS



Part No.	Product Code	Trade Size	K.O. Size	Std. Pkg.	Weight / Pkg.	Part Dimensions (inches)		
						A	B	C
LTS03	065326	3/8"	1/2"	25/100	5	2.000	0.540	1.400
LTS10	065327	1/2"	1/2"	25/100	5	2.000	0.540	1.400
LTS15	065330	3/4"	3/4"	10/100	7	2.200	0.635	1.700
LTS20	065332	1"	1"	5/50	7	2.280	0.740	2.000
LTS25	065334	1-1/4"	1-1/4"	5/25	5	2.440	0.760	2.400
LTS30	065337	1-1/2"	1-1/2"	2/10	3	2.700	0.800	2.670
LTS35	065340	2"	2"	2/10	4	2.990	0.850	3.280

Available in Black upon request



We build tough products for tough environments®

Toll Free: 1-800-463-9572