



XR3 Male
Reducing Fitting,
XR3REDFTG-X-X

Gastite Division
1116 Vaughn Drive
Portland, TN. 37148
Telephone 800-662-0208
www.gastite.com

Description (Sample Specification Language)

FlashShield™ is metallically shielded corrugated stainless steel tubing system complying with ANSI LC 1 "Fuel Gas Piping Systems Using CSST" and listed with CSA®, ICC and IAPMO. The FlashShield system is also listed to protective jacket standards, ICC-ES PMG LC1024, and LC1027. All mechanical tube fittings are SAE CA360 brass incorporating double wall flare sealing. The Jacket-Lock™ and Metal locking features provide steel tubing protection and continuous conductivity.

Features:

- Male NPT Reducing Adapter, Split Bushing, Nut
- Approved for Concealed Use
- Tool-Less Flare Fitting Design
- Metal-to-Metal Seal
- Multi-Point Seal
- Self-Guiding Fitting Assembly
- Jacket-Lock™ Feature
- Metal Locking Feature
- Fully Reusable Fitting




Applicable Standards & Listings:

- CSA: Certificate No. 2728525
- ICC-ES Report No. PMG 1066 and PMG 1155
- IAPMO: File No. C-3250 and Report No. 0239

Technical Data:

General

Max. Approved Operating Pressure	25 psi
Operating Temperature Range	-40°F to 160°F
Fitting Material	CA360



Dimensional Characteristics

Size	P/N	Assembled Length	Pipe Thread (FNPT)	Nut Hex	Fitting Hex	Assembly Torque (ft-lbs)	Weight (lbs)
3/4"	XR3REDFTG-11-08	1.598"	1/2"	1-9/16"	1-3/8"	35	0.4
1"	XR3REDFTG-16-12	1.83"	3/4"	1-15/16"	1-3/4"	45	0.64