



## XR3 Termination Fitting with Bronze Flange, XR3TRM-XX-CB


**Gastite Division**  
1116 Vaughn Parkway  
Portland, TN 37148  
Telephone 800-662-0208  
www.gastite.com

### Description

FlashShield™ is metallically shielded corrugated stainless steel tubing system complying with ANSI LC 1 "Fuel Gas Piping Systems Using CSST" and listed with CSA®, ICC and IAPMO. The FlashShield system is also listed to protective jacket standards, ICC-ES PMG LC1024, and LC1027. All mechanical tube fittings are SAE CA360 brass incorporating double wall flare sealing. The Jacket-Lock™ and Metal locking features provide steel tubing protection and continuous conductivity

### Features:

- Male NPT Adapter, Bushing, Termination Nut, with Cast Bronze Flange
- For "Fixed-Point" Termination on Floor or Wall
- Approved for Concealed Use
- Tool-Less Flare Fitting Design
- Metal-to-Metal Seal
- Self-Guiding Fitting Assembly
- Jacket Lock™ Feature
- Metal Locking Feature
- Fully Reusable Fitting




### Listings:

- CSA Certificate 2728525
- ICC-ES Report No. PMG 1066 and PMG 1155
- IAPMO: File No. C-3250 and Report No. 0239

### Technical Data:

Max. Approved Operating Pressure	25 psi
Operating Temperature Range	-40°F to 160°F
Fitting Material	CA360



### Dimensional Characteristics

Size	P/N	Assembled Length	Pipe Thread	Flange Thread	Nut Hex	Fitting Hex	Flange O.D.	Flange Screw Circle	Assembly Torque (ft-lbs)
1/2"	XR3TRM-8-CB	2.5"	1/2"	3/4"	1-1/4"	1-1/8"	3-1/2"	2-1/2"	35
3/4"	XR3TRM-11-CB	2.7"	3/4"	1"	1-9/16"	1-3/8"	4"	3"	45
1"	XR3TRM-16-CB	2.8"	1"	1-1/4"	1-15/16"	1-3/4"	4"	3"	65
1-1/4"	XR3TRM-20-CB	3.1"	1-1/4"	1-1/2"	2-3/16"	2-1/16"	4"	3"	95
1-1/2"	XR3TRM-24-CB	3.2"	1-1/2"	2"	2-1/2"	2-5/16"	5-5/8"	4-1/4"	120