

4" Miniature Non-IC Remodel Housing

C	Catalog Number:	
F	Project Name:	Туре:
	Note:	elite

LAMP WATTAGE: (1) MAXIMUM 50W R/PAR20/A19








DESCRIPTION

Small aperture thermally protected, specification grade recessed housing. For remodel application non-insulated ceilings or where insulation can be kept 3" from housing. For fast and easy installation in existing plaster or mechanical ceilings from ½" to 1-3/8" thick. Four remodel clips are easily retractable for fixture removal if necessary. Junction box is provided with eight ½" KOs and four Romex knockouts with strain relief. Accommodates up to 50W PAR20, R20, and A19 lamps.

SPECIFICATION

- A. HOUSING High temperature painted 22 gauge deep drawn single piece housing. Accommodate lamps up to 50W depending on trim used.
- B. SOCKET Medium base screw shell porcelain socket preinstalled on adjustable mounting bracket is designed to allow usage of different lamp types, as well as proper and consistent lamp positioning.
- C. INSTALLATION Four preinstalled spring clips which secure the housing firmly into ceiling to accommodate different ceiling thicknesses from 1/2" to 1-3/8".
- D. JUNCTION BOX UL and ETL for feed through wiring with eight 1/2" KOs and four Romex knockouts with strain relief.
- E. THERMAL PROTECTION Standard thermal protection device guards against improper installation, overlamping and misuse of insulation material.



BEAM DIA. MEASURED AT 50% OF NADIR F.C.

FEATURES

- Thermally Protected Non-IC remodel housing.
- · Dependable, favorable design and effortless installation.
- Unit slips through 4-1/4" ceiling opening.
- · Four preinstalled spring clips which secure the housing firmly into ceiling to accommodate different ceiling thicknesses from 1/2" to 1-3/8".
- · Can be installed from below the ceiling.
- 5 ½" height allows use in 2" x 6" joist construction.
- · Preinstalled socket cap provides electrical contact protection against dust, paint and over spray.
- · Adjustable socket bracket.

OPTIONS

AIR-SHUT

- · Gasket to prevent air flow from heated or air conditioned spaces.
- . Meets all national air flow requirements.





ITEM SELECTOR: (Please check the boxes below for the option desired)

ТҮРЕ	AIR-SHUT	OPTION	TRIM TYPE			BAFFLE	REFLECTOR	TRIM/RING	GLASS
B4R	□ AT	☐ (W) With quick connects	□ B401	□ B406	☐ AF402	□ W	□ CL	□ WH	□ Green
			□ B421	□ B407	□ B471	□ P	□ RG	□ BK	☐ Yellow
			□ B402	□ B462	□ B472	□ SN	□ W	□ SN	□ Pink
			□ B432	□ B452	□ B473	□ CP	□ МВ	□ CP	☐ Brown
			□ B420	□ B455	□ B474	□ BZ	□ BZ	□ CH	☐ Navy Blue
			□ B496	□ B451	□ B441		□ CP	□ PB	☐ Orange
			□ B497	□ B454	□ B443		□ SN	□ BZ	□ Blue
			□ B403	□ B437	□ B442		□ SHZ		☐ White
			□ B461	□ B438	□ B444				□ Red
			□ B405	□ B439					
			□ B422	☐ AF401					

Specifications:

B4R

AIR-SHUT

BAFFLE

REFLECTOR

TRIM/RING

GLASS

BAFFLE W W P Bla Black W MB BZ CP SN CP BZ Copper Copper

REFLECTOR

TRIM/RING WH BK SN CP CH PB BZ Satin Nickel Polish Brass

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory



Sample of Catalog Number: B4R-AT-W-B401-W-WH





W White SN Satin Nickel CP Copper

REFLECTOR FINISH: Chrome

RG Gold W White MB Black CP Copper SN Satin Nickel SHZ Satin Haze

RING/TRIM FINISH: WH White RK Rlack SN Satin Nickel CP Copper

Chrome PR Polish Brass ΒZ Bronze

General













Task Lighting



Exotic Glass Collection

Elite Lighting now offers a new line of exotic glass trims. The new series of glass trims can elegantly complement any color scheme in any environment. We are certain that with such a wide selection, you will find the perfect colored trim for your project.









AVAILABLE EXOTIC GLASS COLORS: GREEN, YELLOW, PINK, BROWN, NAVY BLUE, ORANGE, BLUE, WHITE, RED

PATENT #: D570,531



BAFFLE FINISH: REFLECTOR FINISH: RING/TRIM FINISH: GUIDE HOUSING COMPATIBILITY MAX. LAMP WATTAGE White Chrome Bronze WH White CH Chrome B4IC-AT-W, B4-AT-W, B4R-AT-W 50W R/PAR20 Rlack RG Gold Copper RK Rlack PR Polish Brass SN SN Satin Nickel W SN Satin Nickel Satin Nickel ΒZ White Bronze B4IC-AT-W, B4-AT-W, B4R-AT-W 35W R/PAR20 CP CP MB SHZ Black Satin Haze Copper Copper

Bronze

TRIM:

PB, BZ

HOUSING COMPATIBILITY GUIDE:





HOUSING COMPATIBILITY GUIDE:

WH- WHITE SELF FLANGE

AF402CP-WH Self Flange Reflector **AIR SHUT**











B474CL-WH

B444CL-WH



GUIDE HOUSING COMPATIBILITY MAX. LAMP WATTAGE B4IC-AT-W, B4-AT-W, B4R-AT-W 50W R/PAR20 B4IC-AT-W, B4-AT-W, B4R-AT-W 35W R/PAR20 EZ4IC, EZ4, EZ4R 50W R/PAR20













Square Reflector w/ Socket Bracket















BAFFLE FINISH:					
W	White				
P	Black				
SN	Satin Nickel				
CP	Copper				

Bronze

REFLECTOR FINISH:				
CL	Chrome			
RG	Gold			
W	White			

Black

MB

Bronze CP Copper SN Satin Nicke SHZ Satin Haze

RING/TRIM FINISH: WH White RK Rlack SN Satin Nickel CP Copper

Chrome PR Polish Brass ΒZ Bronze

PATENT #: D510,151

HOUSING COMPATIBILITY GUIDE:

Wall Wash









HOUSING COMPATIBILITY GUIDE: