



EASY 3 COLORS
SELECTOR
3500K • 4000K • 5000K



NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
10000	10512	82 W
8000	8855	68 W
6000	6680	50 W

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

FEATURES

The Architectural LED Suspended Linear combines a slim profile with clean lines, making it an ideal choice for library stacks or narrow aisles. The flexibility of the luminaire allows for continuous, uniform and glare-free illumination. Available in single pendant or continuous mounting for a seamless connection from luminaire to luminaire, with adjustable mounting heights. This distinct luminaire is a perfect solution for educational, healthcare, office, commercial and retail spaces.

LUMENS	6000/8000/10000
CCT	35K/40K/50K
CRI	85+
COLOR QUALITY	3 Step MacAdam Ellipse
LENGTH	4', 8'
MOUNTING	Suspended or Surface
FINISH	WH (White standard), BK (Black), SI (Silver), Custom Colors
DIMMING & CONTROL	0-10V Flicker Free 1% Dimming Standard (DIM10)
EMERGENCY	10W - Up to 1000L output
LIFETIME	L70 at 167,000 Hours
OPERATING TEMPERATURE	-20° C to 50°C ambient temperature
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21



OPTICS & PERFORMANCE

The optical system delivers high efficiency LED light that passes through a high quality, frosted acrylic lens for optimal performance, creating a glare-free and even distribution.

CONSTRUCTION

Body is constructed of heavy-duty 20-gauge cold rolled steel, painted with a high-gloss baked white enamel finish, with a frosted extruded lens that delivers highly efficient illumination.

CRM INSTALLATION

For continuous row mounting, the first luminaire in the row will always be the power supply feed. After plugging in the male and female harnesses, which are supplied with each luminaire, they will easily slide together, then secured with two screws from opposite directions in the connecting brackets.

DRIVER ELECTRICAL INFORMATION

Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00. Male and female 18-gauge 6 wire plug connectors are included with every luminaire to allow for simple hassle-free continuous wiring. Each luminaire must be installed male to female.

OPTIONS

Luminaires can be shipped pre-installed with daylight harvesting controls, occupancy sensors, and/or power packs for individual or room control solutions.

DIMMING & DRIVER INFORMATION

DIM10 - Flicker Free 1% Dimming Standard (DIM10) 0-10V dimming on either MVOLT 120, 277V

WARRANTY

Five-year warranty for parts and components. (Labor not included)

LISTINGS

c-UL-us - Listed for Feed Through Wiring.

Listed for DLC, California Title 24 compliant.

c UL us Listed for Damp location

Product not allowed to be in direct contact with water, sprinkler or rain

Example: **8-OC4-LED-6000L/8000L/10000L-DIM10-MVOLT-35K/40K/50K-85**

8	OC4	LED											
FIXTURE SIZE	SERIES	TYPE	LUMENS	DIMMING	VOLTAGE	CCT	CRI	EMERGENCY	FINISH	MOUNTING	WIRING OPTIONS		
8 - 8'	OC4 - LED General Linear	LED	6000L/8000L/10000L	DIM10 - 0-10V Dimming	MVOLT	35/40K/50K	85	O-EMG-LED-10W	WH - White (Standard) BK - Black SI - Silver <small>*Custom colors available Consult factory</small>	CRM - Continuous Row Mounting	FBF - Internal Fast Blow Fuse SBF - Internal Slow Blow Fuse RIS - Radio Interference Suppressor	OTHER OPTIONS	
												CONTROLS	
												SIDE MOUNT	
												INTEGRATED	
												OSM3D-V1W - Line Voltage Microwave Sensor OSM3D-DDW-20 - HF Microwave Sensor 0-10 20% Dim OSM3D-DDW-50 - HF Microwave Sensor 0-10 50% Dim FS-205 - Low Voltage Pir Fixture Integrated Occupancy Sensor FD-301 - Low VolatgeDaylight Dimming Photosensor - High Frequency Microwave Occupancy FM-105 Sensor with 0-10V Dimming - Fixture Sensor Power Pack FS-PPV2	
												OSFHU-LTW - ON/OFF Line Voltage HB011-PDX - Occupancy Sensor with 0-10V Dimming FSP-311-B-D - 0-10V continuous dimming PIR photo/motion sensor with bluetooth control option.	

*FD-301 & FS-205 require FS-PPV2- Power Pack

INTEGRATED SENSOR AND CONTROL OPTIONS

With the Integration of controls, Elite Lighting now offers its products with controls-ready performance that increases energy efficiency, smarter space planning, and the enhancement of safety and productivity in the workplace. By utilizing these controls, Elite Lighting luminaires enable your customer's facility to run smarter, with the use of an easily controlled system through any platform.


Luminaire will be shipped with Powerpacks pre-installed, ready to be Integrated to designated control systems

Luminaire will be shipped with Sensors installed on the luminaire, allowing for individual luminaire control. Luminaires will be ready to be Integrated with designated control systems

Luminaire will be shipped with Sensors to be remotely installed on the ceiling. Luminaires will be ready to be Integrated with designated control systems

BRAND	LEVITON	legrand®
MICROWAVE INTEGRATED SENSOR	<input type="checkbox"/> OSM3D-DDW High Frequency Microwave Occupancy Sensor with 0-10V Dimming	<input type="checkbox"/> FM-105 High Frequency Microwave Occupancy Sensor with 0-10V Dimming
	<input type="checkbox"/> OSM3D-V1W Line Voltage Microwave Sensor	<input type="checkbox"/> FS-205 Low Voltage Pir Fixture Integrated Occupancy Sensor <input type="checkbox"/> FD-301 Low Voltage Daylight Dimming Photosensor
PIR INTEGRATED SENSOR	<input type="checkbox"/> OSFHU-LTW PIR Fixture Mount Occupancy Sensor	<input type="checkbox"/> FSP-311-B-D 0-10V continuous dimming PIR photo/motion sensor with bluetooth control option.
	<input type="checkbox"/> HB011-PDX PIR Fixture Mount Occupancy Sensor with Daylight Harvesting	

SIDE MOUNT



LEGRAND


☐ FSP-311-B-D
0-10V continuous dimming PIR photo/motion sensor with bluetooth control option.

LEVITON

☐ HB011-PDX
PIR Fixture Mount Occupancy Sensor with Daylight Harvesting

☐ OSFHU-LTW
PIR Fixture Mount Occupancy Sensor

IntegratedED



LEGRAND

☐ FM-105
High Frequency Microwave Occupancy Sensor with 0-10V Dimming

☐ FS-205
Low Voltage Pir Fixture Integrated Occupancy Sensor

☐ FD-301
Low Voltage Daylight Dimming Photosensor

LEVITON

☐ OSM3D-DDW
High Frequency Microwave Occupancy Sensor with 0-10V Dimming

☐ OSM3D-V1W
Line Voltage Microwave Sensor