



ABRASION RESISTANT



"COLD-FLEX" MATERIALS



OIL RESISTANT



TRANSPARENT CONSTRUCTION



# "Ground Cover"

## GC-C™ Series

### Heavy Duty Polyurethane Lined Material Handling Hose

#### General Applications:

- Material handling – heavy duty abrasive
- Mulch, bark, wood chips and other surfacing material delivery
- Soil, seed and compost delivery

**Construction:** PVC cover with Polyurethane liner and rigid PVC helix.

#### Service Temperature Range:

-40°F (-40°C) to +150°F (+65°C)\*



#### Features and Advantages:

- **Abrasion Resistant Polyurethane Liner** – Designed for dry applications where severe abrasion is a factor. Provides longer hose life and lower operating costs versus rubber or PVC hoses.
- **"Cold-Flex" Materials** – Hose remains flexible in sub-zero temperatures.
- **Phthalate Free**
- **Transparent Construction** – "See-the-flow." Allows for visual confirmation of material flow.
- **Convolute Outer Cover** – Provides increased hose flexibility. Allows for easier unwinding and winding on hose reels.
- **Oil Resistant Polyurethane Liner** – Resists most animal and petroleum based oils.

## Nominal Specifications

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F			
GC-C400	4	101.6	4.59	116.6	30	15	28	25	6	100	1.00
GC-C500	5	127.0	5.57	141.5	30	15	25	20	10	100	1.80

**NOTE:** Service life may vary depending on operating conditions and type of material being conveyed.

**NOTE:** For details of the following compliances, refer to footnotes listed on page 63.

\*Actual service temperature range is application dependent.

**PHthalate FREE<sup>(10)</sup>, RoHS<sup>(11)</sup>**

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

