

KURIYAMA INDUSTRIAL RUBBER HOSES

Redi-MOR[™]





Medium Oil-Resistant General Service Hose

General Applications:

- Excellent general purpose hose
- Oil mist applications
- Pneumatic air tool hose

Construction:

- Cover: Red limited oil and ozone-resistant.
- Reinforcement: Spiral polyester yarn.
- Tube: Black Class C medium oil-resistant.
- ★ Not recommended for fuel applications.

Service Temperature Range:

-40°F (-40°C) to +200°F (+93°C)

Features and Advantages:

• Long lengths on reels.

Branding:

MED. OIL RESIST. - SIZE - WP - MADE IN USA

Packaging:

Maximum 2 pcs. on reel.

1/4" – 3/4" ID hoses supplied on plastic reels.

1" – 1 1/2" ID hoses supplied on wooden reels.

* Cut lengths of 25 & 50 feet available on select sizes.

Note: For Quick Disconnect Couplings and Worm Gear Clamps refer to pages 15, 18-19 of this catalog.

Nominal Specifications						
Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Reel Length (ft)	Weight (Ibs/pc)
MORGP-025X700	Red	1/4	1/2	300	700	105
MORGP-031X700	Red	5/16	5/8	300	700	98
MORGP-038X700	Red	3/8	11/16	300	700	126
MORGP-050X700	Red	1/2	27/32	300	700	175
MORGP-062X700	Red	5/8	1	300	700	210
MORGP-075X700	Red	3/4	1 5/32	300	700	259
MORGP-100X700	Red	1	1 7/16	300	700	350
MORGP-125X300	Red	1 1/4	1 3/4	200	300	243
MORGP-150X300	Red	1 1/2	2	200	300	282

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

KIRAHCA1018

🚫 Kuriyama of America, Inc.