



Flexible "Floppy Guard" Interlocked Metal Hose – HT1100

Highly-flexible interlocked metal armor hose provides maximum protection for hydraulic hoses in the most severe applications.

Construction – A single metal strip is loosely interlock-wound to create an extremely flexible interlocked metal hose.

Available in galvanized steel and stainless steel.

Applications – Armor shielding for hoses where maximum flexibility and protection from abrasion and damage are important.



Maximum Service Temperature:

Galvanized Steel: Up to 750°F

Stainless Steel: Up to 1800°F

SPECIFICATIONS (Lengths and Weights are based on extended hose and are approximate)

HTG1100 – Galvani	i zed – .01	0" – .012" str	ip thickness	HTS1100 – Stainles	s Steel –	.010"012"	strip thickness
Part Number	ID (in)	Std. Length Colis (ft)	Weight (Ibs/coil)	Part Number	ID (in)	Std. Length Colis (ft)	Weight (Ibs/coil)
HTG1100-018X25	3/16	25	2.00	HTS1100-018X25	3/16	25	2.00
HTG1100-025X25	1/4	25	2.50	HTS1100-025X25	1/4	25	2.50
HTG1100-031X25	5/16	25	3.00	HTS1100-031X25	5/16	25	3.00
HTG1100-037X25	3/8	25	3.50	HTS1100-037X25	3/8	25	3.50
HTG1100-050X25	1/2	25	4.00	HTS1100-050X25	1/2	25	4.00
HTG1100-062X25	5/8	25	4.50	HTS1100-062X25	5/8	25	4.50
HTG1100-075X25	3/4	25	5.00	HTS1100-075X25	3/4	25	5.00
HTG1100-087X25	7/8	25	5.75	HTS1100-087X25	7/8	25	5.75
HTG1100-100X25	1	25	7.00	HTS1100-100X25	1	25	7.00
HTG1100-112X25	1 1/8	25	8.00	HTS1100-112X25	1 1/8	25	8.00
HTG1100-125X25	1 1/4	25	9.00	HTS1100-125X25	1 1/4	25	9.00
HTG1100-137X25	1 3/8	25	10.50	HTS1100-137X25	1 3/8	25	10.50
HTG1100-150X25	1 1/2	25	12.00	HTS1100-150X25	1 1/2	25	12.00
HTG1100-162X25	1 5/8	25	13.00	HTS1100-162X25	1 5/8	25	13.00
HTG1100-175X25	1 3/4	25	14.50	HTS1100-175X25	1 3/4	25	14.50
HTG1100-187X25	1 7/8	25	15.50	HTS1100-187X25	1 7/8	25	15.50
HTG1100-200X25	2	25	16.50	HTS1100-200X25	2	25	16.50
HTG1100-225X25	2 1/4	25	19.00	HTS1100-225X25	2 1/4	25	19.00

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



QUICK

NFORMATION

FECHNICAL

B SERIES

D SERIES

ONE-PIECE F & P SERIES

TWO-PIECE FERRULES

TWO-PIECE INSERTS (A SERIES)

(A & PFR SERIES)

DNE-PIECE

ONE-PIECE

Technical Information Index

Assembly Length 300 - 301	
Cautionary Statement & Limited Warranty323	
Conversion Charts 319 - 320	
Fitting Identification	
Fitting Identification - American 306 - 310	
Fitting Identification - British	
Fitting Identification - French	
Fitting Identification - German313 - 314	
Fitting Identification - Japanese	

Hex Dimensions	321
Hydraulic Hose Sizing Nomogram	297
Installation & Assembly	302-303
Pressure & Distance Conversions	
Pressure Drop International Chart	299
Pressure Drop U.S. Chart	298
Safety Guide	294 - 296
Temperature Conversions	320
Thread Type	305
Torque Data	317 - 318



Notes



HOSES
ONE-PIECE B SERIES
ONE-PIECE D SERIES
ONE-PIECE F & P SERIES
TWO-PIECE FERRULES (A & PFR SERIES)
TWO-PIECE INSERTS (A SERIES)
TWO-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)
QUICK Release
ASSEMBLY EQUIPMENT

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



TECHNICAL INFORMATION

Safety Guide



Safety Guide and Basic Factors for Selecting, Installing & Maintaining Hose and Hose Assemblies

Hydraulic hose (and hose assemblies) has a limited life dependent on service conditions to which it is applied. Subjecting hose (and hose assemblies) to conditions more severe than the recommended limits significantly reduce service life. Exposure to combinations of recommended limits (i.e., continuous use at maximum rated working pressure, maximum recommended operating temperature and minimum bend radius) will also reduce service life.

WARNING: FAILURE TO FOLLOW PROPER SELECTION, INSTALLATION AND MAINTENANCE PROCEDURES MAY RESULT IN PREMATURE FAILURES, BODILY INJURY, AND DAMAGE TO PROPERTY.

1. SELECTION – The following is a list of factors which must be considered before the selection of a hose can be made:

1.1 Line size:

In order to achieve maximum efficiency in a hydraulic system, it is necessary to keep pressure losses (resistance to the volumetric flow) to a minimum when a fluid is conveyed by the different types of flow lines.

When a fluid flows through a flow line, heat is generated by friction. Thus part of the energy is lost as heat energy, which results in a pressure loss.



These pressure losses depend upon:

- Flow velocity (for a given volumetric flow, the fluid flow velocity increases with a decrease in the cross sectional area of a flow line and vice versa) · length of the flow line
- The viscosity of the fluid flowing
- The density of the fluid flowing
- The type of flow (laminar or turbulent)

Types of flow – The type of flow changes from laminar to turbulent at a certain flow velocity. This velocity is given by the Reynold's Number Re.

For cylindrical flow lines the following formula applies:

$$\operatorname{Re} = \frac{\operatorname{vxd}}{\upsilon}$$

where v = velocity (m/s)

- d = flow line internal dia. (m)
- $\upsilon =$ kinematic viscosity (m2/s)

As soon as the value for Re exceeds 2300, the laminar flow changes to turbulent flow.

Laminar flow – In laminar flow, the individual fluid particles move up to certain speeds in uniform layers alongside each other. They scarcely disturb or influence each other.

Turbulent flow – If the value for Re exceeds 2300, flow becomes whirling and turbulent. The individual particles no longer move in one direction in an orderly fashion, but influence and hinder each other.



Certain fluid flow velocities have proved to be most suitable for hydraulic flow lines.

Recommended flow velocities:

Suction lines: 0.5 1.2 m/s	1.6 4 feet/s
Return lines: 2 3 m/s	6.5 10 feet/s
Pressure lines: 4 7.5 m/s	13 25 feet/s

It is therefore important to calculate correctly the required flow line sizes. Undersized pressure lines result in high fluid velocity causing an excessive pressure drop, and heat build up, which impair overall system performance. Undersized suction lines can cause cavitation at the hydraulic pump inlet, affecting performance, shortening pump life, and creating excessive noise levels.

The flow capacity nomogram on page 14 is an aid to determine the correct hose internal diameter size, desired flow rate and recommended velocity. By the use of any two known factors, the third can be determined.

1.2 Pressure:

After determining the system pressure for a hydraulic system, hose selection must be made so that the recommended maximum operating pressure specified by a given hose, is equal or greater than the system pressure. Dynamic pressure is common for all hydraulic systems.

Pressure surges which exceed the maximum working pressure (pressure relief valve setting) affect the service life of system components, including a hose assembly and therefore need to be taken into consideration. Hoses used for suction lines must be selected to ensure the hose will withstand the negative pressure of the system.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



ASSEMBLY

NFORMATIOI

TECHNICAI

HOSES

ONE-PIECE B SERIES

D SERIES

F & P SERIES

TWO-PIECE FERRULES

(A SERIES)

(A & PFR SERIES

Safety Guide

HOSES

NFORMATION

<u>ECHNICA</u>

1.3 Temperature:

Care must be taken to ensure that the operating temperature of the fluid being conveyed and ambient temperatures, do not exceed the limitations of the hose. Special care must be taken when routing near hot manifolds or molten metal.

1.4 Fluid Compatibility:

Hose selection must assure compatibility of the hose tube, cover, reinforcement, and fittings with the fluid used. Additional caution must be observed in hose selection for gaseous applications. Some fire resistant fluids require the same hose as petroleum oil. Some use a special hose, while a few fluids will not work with any hose at all.

1.5 Permeation:

Permeation (that is, seepage through the hose) will occur from inside the hose to outside when hose is used with gases, liquid and gas fuels, and refrigerants (including but not limited to such materials such as helium, fuel oil, natural gas, or freon). This permeation may result in high concentrations of vapors which are potentially flammable, explosive, or toxic, and in loss of fluid.

Even though the fluid compatibility is acceptable, you must take into account the fact that permeation will occur and could be hazardous. Permeation of moisture from outside the hose to inside the hose will also occur. If this moisture permeation would have detrimental effects (particularly but not limited to refrigeration and air conditioning systems), incorporation of sufficient drying capacity in the system or other appropriate system safeguards should be selected and used.

1.6 Routina:

Attention must be given to optimum routing to minimize inherent problems. Restrain, protect or guide hose with the use of clamps if necessary to minimize risk or damage due to excessive flexing, whipping or contact with other moving parts or corrosives. Determine hose lengths and configurations that will result in proper routing and protection from abrasion, snagging or kinking and provide leak resistant connections.

1.7 Environment:

Care must be taken to ensure that the hose and fittings are either compatible with or protected from the environment to which they are exposed. Environmental conditions including but not limited to ultraviolet light, heat, ozone, moisture, water, salt water, chemicals, and air pollutants can cause degradation and premature failure and, therefore, must be considered.

1.8 Mechanical Loads:

External forces can significantly reduce hose life. Mechanical loads which must be considered include excessive flexing, twist, kinking, tensile or side loads, bend radius, and vibration. Use of swivel type fittings or adaptors may be required to ensure no twist is put into the hose. Unusual applications may require special testing prior to hose selection.

1.9 Abrasion:

While a hose is designed with a reasonable level of abrasion resistance, care must be taken to protect the hose from excessive abrasion which can result in erosion, snagging, and cutting of the hose cover. Exposure of the reinforcement will significantly accelerate hose failure.

1.10 Proper End Fitting:

Care must be taken to ensure proper compatibility exists between the hose and coupling selected based on the manufacturer's recommendations substantiated by testing to industry standards such as

1.11 Length:

When establishing proper hose length, motion absorption, hose length changes due to pressure, as well as hose and machine tolerances must be considered.

1.12 Specifications and Standards:

When selecting hose and fittings, government, industry, and manufacturer's specifications and recommendations must be reviewed as applicable.

1.13 Hose Cleanliness:

Hose components may vary in cleanliness levels. Care must be taken to ensure that the assemblies selected have an adequate level of cleanliness for the application.

1.14 Welding and Brazing:

Heating of plated parts, including hose fittings and adaptors, above 232°C (450°F) such as during welding, brazing, or soldering may emit deadly gases.

1.15 Electrical Conductivity:

Certain applications require that a hose be non-conductive to prevent electrical current flow. Other applications require the hose to be sufficiently conductive to drain off static electricity.

Extreme care must be exercised when selecting hose and fittings for these or any other applications in which electrical conductivity or non-conductivity is a factor.

For applications that require hose to be electrically non-conductive, including but not limited to applications near high voltage electric lines, only special non-conductive hose can be used.

The manufacturer of the equipment in which the non-conductive hose is to be used must be consulted to be certain that the hose and fittings that are selected are proper for the application.

Do not use any ALFAGOMMA hose or fitting for any application requiring non-conductive hose, including but not limited to applications near high voltage electric lines, unless the application is expressly approved in the ALFAGOMMA technical publication for the product, the hose is both orange in color and marked "non-conductive," and the manufacturer of the equipment on which the hose is to be used specifically approves the particular ALFAGOMMA hose and fitting for such use.

ALFAGOMMA does not supply any hose or fittings for conveying paint in airless paint spraving or similar applications and therefore should not be used. A special hose and fitting assembly is required for this application, to avoid static electricity buildup which could cause a spark that may results in an explosion and/or fire.



Safety Guide



HOSES

ONE-PIECE B SERIES

QUICK

ASSEMBLY EQUIPMENT

NFORMATION

TECHNICAL

The electrical conductivity or non-conductivity of hose and fittings is dependant upon many factors and may be susceptible to change. These factors include but are not limited to the various materials used to make the hose and the fittings, manufacturing methods (including moisture control), how the fittings contact the hose, age and amount of deterioration of damage or others changes, moisture content of the hose at a particular time, and other factors.

2. INSTALLATION – After the selection of the correct hose, the following factors must be considered prior to hose and fitting assembly and installation:

2.1 Pre-Installation Inspection:

Prior to installation, a careful examination of the hose must be performed. All components must be checked for correct style, size, and length. The hose must be examined for cleanliness, obstructions, blisters, cover looseness, or any other visible defects.

2.2 Hose and Fitting Assembly:

Do not assemble an ALFAGOMMA fitting on an ALFAGOMMA hose that is not specified by ALFAGOMMA for that hose. Do not assemble ALFAGOMMA fittings on another manufacturer's hose or an ALFAGOMMA hose on another manufacturer's fitting unless ALFAGOMMA approves the assembly in writing, and the user verifies the assembly and the application through analysis and testing. The ALFAGOMMA published hose assembly instructions must be followed for assembling the fittings on the hose.

2.3 Related Accessories:

Crimp or swage ALFAGOMMA hose or fittings only with ALFAGOMMA approved swage or crimp machines and in accordance with the ALFAGOMMA published hose assembly instructions.

2.4 Parts:

Do not use any ALFAGOMMA hose fitting part (including but not limited to sockets, or inserts) except with the correct ALFAGOMMA mating parts, in accordance with ALFAGOMMA published hose assembly instructions, unless authorized in writing by ALFAGOMMA.

2.5 Reusable/Permanent:

Do not reuse any reusable hose coupling that has blown or pulled off a hose. Do not reuse an ALFAGOMMA permanent (that is, crimped or swaged) hose fitting or any part thereof.

2.6 Minimum Bend Radius:

Installation of a hose at less than the minimum listed bend radius may significantly reduce the hose life. Particular attention must be given to avoid sharp bending at the hose/fitting juncture.

2.7 Twist Angle and Orientation:

Hose installations must be such that relative motion of machine components does not produce twisting.

2.8 Hose Restraints:

In many applications, it may be necessary to restrain, protect, or guide the hose to protect it from damage by unnecessary flexing, pressure surges, and contact with other mechanical components. Care must be taken to ensure such restraints do not introduce additional stress or wear points.

2.9 Proper Connection of Parts:

Proper physical installation of the hose requires a correctly installed port connection while ensuring that no twist or torque is transferred to the hose.

2.10 External Damage:

Proper installation is not complete without ensuring that tensile loads, side loads, kinking, flattening, potential abrasion, thread damage, or damage to sealing surfaces are corrected or eliminated.

2.11 System Checkout:

After completing the installation all air entrapment must be eliminated and the system pressurized to the maximum system pressure and checked for proper function without any leaks. Personnel must stay out of potential hazardous areas while testing.

3. HOSE AND FITTING MAINTENANCE INSTRUCTIONS

Even with proper selection and installation, hose life may be significantly reduced without a continuing maintenance program. Frequency should be determined by the severity of the application and risk potential. A maintenance program must be established and followed to include the following as a minimum:

3.1 Visual Inspection Hose/Fitting:

Any of the following conditions require immediate shutdown and replacement of the hose assembly:

- Fitting slippage on hose.
- Damaged, cut, or abraded cover (any reinforcement exposed).
- Hard, stiff, heat cracked, or charred hose.
- Cracked, damaged, or badly corroded fittings.
- Leaks at fitting or in hose.
- Kinked, crushed, flattened, or twisted hose.
- Blistered, soft, degraded, or loose cover.

3.2 Other Visual Inspection:

The following items must be tightened, repaired or replaced as required:

- Leaking port conditions.
- Remove excess dirt build-up.
- Clamp, guards, shields.
- System fluid level, fluid type, and any air entrapment.

3.3 Functional Test:

Operate the system at maximum operating pressure and check for possible malfunctions and freedom from leaks. Personnel must stay out of potential hazardous areas while testing.

3.4 Replacement Intervals:

Specific replacement intervals must be considered based on previous service life, government or industry recommendations, or when failures could result in unacceptable downtime, damage, or injury risk.



BALFACOMMN

/min

400

300

200

Hydraulic Hose Sizing Nomogram

HOSES

DNE-PIECE B SERIES

DNE-PIECE D SERIES

ONE-PIECE F & P SERIES

TWO-PIECE FERRULES

TWO-PIECE INSERTS

TWO-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)

RELEASE

ASSEMBLY EQUIPMENT

NFORMATION

TECHNICAL

QUICK

(A SERIES)

(A & PFR SERIES)

Use the nomogram below to determine Hose ID Size based on Flow (Q) and Velocity.

Gal/min *

80

60

50

40

Conversely, it can be uesd to determine Velocity, based on Flow (Q) and Hose ID, or Flow (Q) based on Velocity and Hose ID.

To use the nomogram, draw a straight line across the entire nomogram, intersecting the scale for the two known quantities.

In the example shown by the red line below, the desired Velocity of 25 feet per second and the desired Flow of 10 Gallons per minute were known. The straight line intersecting the two known quantities intersects the Hose ID scale at $1/2^{"}$. Therefore, a hose with $1/2^{"}$ ID (-08) would be selected.



 * Gallons shown are Imperial (British) Gallons. To convert to US Liquid Gallons, multiply by 1.2009.
Other Conversions: Gal/min (Brit) x 4.546 = I/min feet/s x 0.3048 = m/s Recommended Velocities shown are based on hydraulic fluids with maximum viscosity of 315 SSU at 100°F (38°C) working at room temperatures within the range 65°F (18°C) and 155°F (68°C).

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

Kuriyama of America, Inc. www.kuriyama.com

Pressure Drop US Chart



Hose Pressure Drop*

HOSES

ONE-PIECE B SERIES

D SERIES

ONE-PIECE F & P SERIES

(A & PFR SERIES)

TWO-PIECE INSERTS (A SERIES)

> TWO-PIECE INTERLOCK FERRULES & INSERTS

(X & Z SERIES)

QUICK

ASSEMBLY EQUIPMENT The chart below shows pressure drop in **PSI** for 10 feet of hose (smooth bore) without fittings. Fluid specification: Specific gravity = .85; Viscosity = v = 20 centistokes (C.S.), (20 C.S. = 97 S.S.U.); ref MIL – H 5606, +70°F (+21°C). Flow: US gallons per minute (gpm)

Hose pressure drop in PSI per 10 feet of hose length

Hose Size		-03	-04	-05	-06	-08	-10	-12	-16	-20	-24	-32	-40	-48
Hose I.	D. (in.)	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1-1/4	1-1/2	2	2-1/2	3
	DN	5	6	8	10	12	16	20	25	32	40	50	63	80
	.25	10	3.1											
	.50	19	6	2.7										
	1	40	12	5.5	2.4									
	2	95	24	10	4.8									
	3	185	46	17	7	2.2								
	4		78	29	12	3	1.2							
	5		120	44	18	4.5	1.6	0.7						
	8			95	39	10	3.6	1.4						
Ð	10				59	15	5.7	2	0.6					
nt	12				80	20	7.2	2.6	0.8					
Ē	15					30	10	4.2	1.2	0.4				
, n	18					40	15	6.3	1.5	0.6				
	20					49	19	8	2	0.7	0.3			
e	25					72	26	11	3	1	0.4			
Q	30						34	14	3.6	1.3	0.5	0.1		
S	35						47	19	5	1.7	0.7	0.2		
	40							25	6.5	2.2	0.9	0.2		
≅	50							36	9	3.3	1.3	0.4	0.2	
a	60							50	12	4.4	1.8	0.5	0.2	
D	70								17	6	2.4	0.7	0.3	
S	80								21	7.1	3	0.8	0.3	0.1
	90								27	9	3.8	1	0.5	0.1
	100								33	12	4.7	1.3	0.6	0.2
	150								60	22	8.5	2.2	1	0.3
	200									36	15	3.9	1.7	0.6
	250									54	22	5.3	2.5	0.8
	300										29	7.5	4	1.1
	400										51	14	6.5	2.2
	500											20	10	3
	800												18	5
	1000													10

★ Pressure drop values listed are typical of many petroleum based hydraulic oils at approximately +100°F (+38°C). Differences in fluids, fluid temperature and viscosity can increase or decrease actual pressure drop compared to the values listed.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

298



Pressure Drop International Chart

Hose Pressure Drop*

Pressure drop in **KPa** (Kilo Pascal) for a 10 meter length of hose (smooth bore) without fittings. Fluid specification: specific gravity = 0.85; Viscosity = 20 centistokes (C.S.); ref MIL – H 5606 at +21°C (+70°F). Flow: Litres per minute (L/min)

Hose pressure drop in KPa per 10 meters of hose length

Hose si	ze	-03	-04	-05	-06	-08	-10	-12	-16	-20	-24	-32	-40	-48
DN real		4.8	6.4	8.0	9.5	12.7	15.9	19.0	25.4	31.8	38.1	50.8	63.5	76.2
	DN	5	6	8	10	12	16	20	25	32	40	50	63	80
	1	242	75											
	2	466	146	66										
	4	996	293	133	59									
	8	2433	613	250	117									
	10	3540	880	335	144	45								
	15		1776	660	273	69	27							
	20		3080	1129	462	116	41	18						
	30			2159	887	228	82	32						
Φ	40				1496	379	141	50	14					
ut	50					555	192	75	22					
n	60					756	263	111	30	10				
n	70					970	373	154	37	13				
	80					1250	475	200	49	17	7			
e	90					1531	560	237	66	21	9			
Q	100						653	274	73	24	10	3		
S	125						964	393	103	36	15	4		
er	150							567	147	50	19	5		
it.	175							735	186	60	27	7	3	
	200							920	228	83	33	9	4	
	250								347	124	50	13	6	
	300								475	162	68	17	8	3
	400								832	303	118	32	14	5
	500								1159	425	164	43	19	6
	600									562	222	57	26	8
	700									733	301	78	35	11
	800									924	383	98	43	14
	900									1144	468	118	53	16
	1000										553	140	68	20

★ Pressure drop values listed are typical of many petroleum based hydraulic oils at approximately +100°F (+38°C). Differences in fluids, fluid temperature and viscosity can increase or decrease actual pressure drop compared to the values listed.

Kuriyama of America, Inc. www.kuriyama.com

B SERIES HOSES

NFORMATION

TECHNICAL

Assembly Length

How to Determine Correct Assembly Length



For most assemblies, the correct assembly length may be determined by direct measurement of the equipment or a drawing. Minimum bend radii as shown in the hose specification tables should be observed.

Assemblies are measured to the end of the seal.



Swivel female and male union

Length between centre lines of angle and banjo



Swivel female 90° swept union

Banjo coupling

Length between centre line of S.P. and end of nipple



Remember that hydraulic hose under pressure will elongate up to 2% of its length or contract up to 4% depending on pressure, type and size. Sufficient allowance should be made to permit such changes in length.

To determine the length of hose needed in making assemblies with permanent or reusable couplings, subtract Dimension "C" (Cut off factor) for each coupling from the required overall assembly length. Dimension "C" may be found in the coupling specification tables.



Straight standpipe

Length between male nipple and centre of female nipple



Swivel female 45° swept union

Length between centre of angle and nipple end



Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

HOSES ONE-PIECE B SERIES

FERRULES & INSERTS TWO-PIECE INTERLOCK (X & Z SERIES)



EQUIPMENT ASSEMBLY

INFORMATION

300

ALFAGOMMA

Assembly Length

Occasionally an assembly will be required similar to the sketches to the right. The following equations are helpful in determining the correct length:

FOR 180° TURN APPLICATIONS

 $#1 L = 2A + \pi R$

 $#2 L = 2A + \pi R + T$

L = Overall length of the hydraulic hose assembly, inmm or inches.

A = Allowance for a minimum straight section of hydraulic hose at each end of the assembly, measure from the outer end of each coupling, in mm or inches. These two straight sections are necessary to prevent excessive stress concentrations directly back of the couplings. See table below.

R = Bending radius of the hose, in mm or inches. See hose specifications tables.

T = Amount of travel, in mm or inches.

Often right angle adapters provide a convenient means of avoiding a bend radius that is too small.

Hose	in.	1/4	5/16	3/8	1/2	5/8	3/4	1	1 1/4	1 1/2	2
ID	mm	6.4	7.9	9.5	12.7	15.9	19	25	31.8	38.1	50.8
Min.	in.	5	5	5	6	6	7	8	9	10	11
"A"	mm	127	127	127	152	152	178	203	229	254	279



Length

For lengths from 0 up to and including 12" (305 mm) For lengths > 12" (305 mm) < 18" (457 mm) For lengths > 18" (457 mm) < 36" (914 mm) For lengths > 36" (914 mm) < 48" (1219 mm) For lengths > 48" (1219 mm) < 72" (1830 mm) For lengths > 72" (1830 mm)

Elbow angle and angle of Orientation.

Angle Couplings

A – To measure angle of offset of a hose assembly, point one end of coupling "A" (the nearest) to a vertical position downward. The angle can then be measured from the centerline of this vertical coupling "B" (the far coupling). See illustration at right.

Relationships can then be expressed from 0° to 360°. If angle is not given, elbows are positioned at 0°.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



Tolerance ± 1/8" ± 3 mm $\pm 3/16" \pm 5 \text{ mm}$ ± 1/4" ± 6 mm ± 3/8" ± 10 mm ± 1/2" ± 13 mm

±1% Tolerance ± 3 Angle in degrees Measure angle counter-clockwise END VIEW A

KHCCA1020

Kuriyama of America, Inc. www.kuriyama.com

TWO-PIECE INSERTS (A SERIES)

IWO-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)



ASSEMBLY

NFORMATION

ECHNICAL

Installation & Assembly



Correct Assembly & Installation

Satisfactory performance and appearance depend upon proper hose installation. Excessive length destroys the trim appearance of an installation and adds unnecessarily to the cost of the equipment. Hose assemblies of insufficient length to permit

WRONG 881 1880 RIGHT

Since hose may change in length from +2% to -4% under the surge of high pressure, provide sufficient slack for expansion and contraction.

adequate flexing, expansion or contraction will cause poor power transmission and shorten the life of the hose.

The diagrams below offer suggestions for proper hose installations to obtain the maximum in performance and economy.





Obtain direct routing of hose through use of 45° and 90° adapters and fittings. Improve appearance by avoiding excessive hose length.





Avoid a sharp twist or bend in the hose by using the proper angle adaptors.



Due to changes in the length when a hose is pressurized, do not clamp at bends so curves absorb changes and protect the hose with a spring guard. Do not clamp high and low pressure lines together and protect the hose with a spring guard.





Where the radius falls below the required minimum, an angle adapter should be used as shown above to avoid a sharp bend in the hose.



Adequate hose length is most important to distribute movement on flexing applications and to avoid abrasion.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

HOSES

ONE-PIECE B SERIES

D SERIES NE-PIECE

F & P SERIES **ONE-PIECE**

TWO-PIECE FERRULES

TWO-PIECE INSERTS

FERRULES & INSERTS TWO-PIECE INTERLOCK

(X & Z SERIES)

RELEASE QUICK

EQUIPMENT ASSEMBLY

(A SERIES)

(A & PFR SERIES)

BALFACOMMA

Installation & Assembly

Correct Assembly & Installation



To avoid twisting in hose lines bent in two planes, clamp hose at change of plane, as shown.



Hose should not be twisted.

Hose is weakened when installed in a twisted position. Also pressure in twisted hose tends to loosen fitting connections. Design so that machine motion produces bending rather than twisting.



To prevent twisting and distortion, hose should be bent in the same plane as the motion of the boss to which the hose is connected.

Never use a bending radius less than the minimum shown in the hose specification tables. Avoid sharp bends in hoses to reduce collapsing of lines and restriction of flow by using a proper spring guard. Exceeding minimum bend radius will greatly reduce hose assembly life.

HOSES

DNE-PIECE

ONE-PIECE D SERIES

F & P SERIES **ONE-PIECE**

TWO-PIECE FERRULES (A & PFR SERIES)

NFORMATION **ECHNICA** 303



Fitting Identification



Measuring Threads and Seat Angles

Measuring Threads

HOSES

ONE-PIECH B SERIES

D SERIES **NE-PIECE**

F & P SERIES **ONE-PIECE**

TWO-PIECE FERRULES

TWO-PIECE INSERTS (A SERIES)

> FERRULES & INSERTS TWO-PIECE INTERLOCK

(X & Z SERIES)

RELEASE QUICK

EQUIPMENT ASSEMBLY

NFORMATION

TECHNICAL

(A & PFR SERIES)

With the calliper, measure the thread diameter at the largest point. (O.D. of male threads - I.D. of female threads). See illustration at right.







Use a thread pitch gauge (see illustration below) to determine the number of threads per inch or the distance between threads in metric connections. Place the gauge on the threads (see illustrations at right) until the fit is snug. Match the measurement to the chart.



Thread Pitch Gauge





Compare the measurements taken to the couplings shown in the coupling specification tables that appear in this catalog.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

304

Measuring Seat Angles

match. See illustration at right.

When the centerline of the seat gauge extends

parallel to the projected longitudinal axis of the coupling, then the angles of the gauge and seat



Thread Type

HOW TO DETERMINE THE THREAD TYPE USING CALLIPERS

By measuring with a caliper the outside diameter of the thread of a male or the inside diameter of the thread of a female you will get a measure in mm. By finding this value in mm on the below table, you'll be able to find the relevant thread type.

Male OD	mm	Female ID	Male OD	mm	Female ID
	8,7	G1/8" BSP		27,9	1 3/16" – 12 JIC
1/8" – 27 NPTF	9,5			28,0	M 30 x 2
G1/8" BSP	9,6			28,5	30 x 1,5 DKF
M 10 x 1	9,8		M 30 x 2	29,8	,
	9.9	7/16" – 20 JIC	30 x 1.5 CEF	29.9	
	10.5	M 12 x 1.5	1 3/16" – 12 JIC	30.1	
7/16" – 20 JIC	11.0			30.7	G1" BSP
	11.4	1/2" – 20 SAE		31.2	1 5/16" – 12 JIC
	11.6	G1/4" BSP	1" – 11 1/2 NPTF	31.4	
M 12 x 1.5	11.9			31.5	M 33 x 1.5
1/4" – 18 NPTF	12.5		G1" BSP	33.1	
	12.5	M 14 x 1.5	1 5/16" – 12 JIC	33.2	
1/2" – 20 SAF	12.6			34.0	M 36 x 2
	12.9	9/16" – 18 JIC		34.5	36 x 1.5 DKF
G1/4" BSP	13.0	0.10 10010	M 36 x 2	35.8	00 X 1,0 211
M 14 x 1 5	13.9		36 x 1.5 CEF	35.9	
9/16" – 18 JIC	14.2			36.5	M 36 x 1 5
0/10 10 010	14.5	M 16 x 1 5	M 38 x 1 5	37.9	W 00 X 1,0
	15.1	G3/8" BSP		38.8	1 5/8" – 12 JIC
M 16 x 1 5	15.8			39.4	G1 1/4" BSP
3/8" – 18 NPTF	15.9			39.8	M 42 x 2
	16.5	M 18 x 1 5	1 1/4"–11 1/2 NPTE	40.2	
G3/8" BSP	16.6	W 10 X 1,0		40.5	M 42 x 1 5
	17.5	3/4" – 16 JIC	1 5/8" – 12 JIC	41 1	
M 18 x 1 5	17,0	0/4 10010	1 1/4" – 11 BSP	41 7	
W 10 X 1,0	18.4	20 x 1 5 DKF	M 42 x 2	41.8	
3/4" – 16 JIC	18.8	Lo X 1,0 Diti		42.4	M 45 x 2
0/4 10 010	18.8	G1/2" BSP		43.3	45 x 1 5 DKF
1/2" – 14 NPT	19.8		M 45 x 2	44.8	-10 X 1,0 DIV
20 x 1 5 CEE	19.0		45 x 1 5 CFF	44.9	
20 x 1,0 021	20.4	7/8" – 14 SAF		45.1	1 7/8" – 12 IIC
	20.5	<u> </u>		45.2	G1 1/2" BSP
G1/2" BSP	20,5		1 1/2"_11 1/2 NPTE	46.3	
	20,0	G5/8" BSP	1 7/8" – 12 JIC	47.5	
M 22 x 1 5	21.9		G1 1/2" BSP	47,3	
7/8" - 14 SAF	22.1			49.6	M 52 x 2
	22 5	24 x 1 5 DKF		50.3	52 x 1 5 DKF
G5/8" RSP	22,5		M 52 x 2	51.8	52 A 1,5 DIN
24 x 1 5 CFF	23.0		52 x 1 5 CFF	51.0	
	24.5	G3/4" RSP		57.4	G2" BSP
	24,5		2" _ 11 1/2 NPTE	58.3	
3/4" - 14 NPTE	24,0	1 1/10 - 12 010	G2" RCP	50,5	
	25,1	M 26 x 1 5		61.1	2 1/2" - 12 110
M 26 x 1 5	25,5			62.5	M 65 x 2
1VI 20 X 1,3	20,9		2 1/2" _ 12 110	63.2	
	20,3		2 1/2 - 12 310	00,0	

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

305





ASSEMBLY EQUIPMENT



Fitting Identification -American

Fitting Identification

Dash Numbers

Most fluid piping system sizes are measured by dash numbers. These are universally used abbreviations for the size of a component expressed as the numerator of the fraction with the denominator always being 16. For example, a -04 port is 4/16 or 1/4 inch. Dash numbers are usually nominal (in name only) and are abbreviations that make the ordering of components easier.

American Thread Types

NPTF – (National Pipe Tapered Fuel)

This is a dryseal thread, the National pipe tapered thread for fuels. This is used for both male and female ends. This connection is still widely used in fluid power systems, even though it is not recommended by the National Fluid Power Associations (N.F.P.A.) for use in hydraulic applications.

The NPTF male will mate with the NPTF. NPSF. or NPSM female.

The NPTF male has tapered threads and a 30° inverted seat. The NPTF female has tapered threads and no seat. The seal takes place by deformation of the threads. The NPSM female has straight threads and a 30° inverted seat. The seal takes place on the 30° seat.

The NPTF connector is similar to, but not interchangeable with, the BSPT connector. The thread pitch is different in most sizes. Also, the thread angle is 60° instead of the 55° angle found on BSPT threads.

NPSF – (National Pipe Straight Thread for Fuels)

The National pipe straight thread for fuels. This is sometimes used for female ends and properly mates with the NPTF male end. However, the SAE recommends the NPTF thread in preference to the NPSF for female ends.

NPSM – (National Pipe Straight Mechanical)

National pipe straight thread for mechanical joint. This is used on the female swivel nut of iron pipe swivel adapters. The leak-resistant joint is not made by the sealing fit of threads, but by a tapered seat in the coupling end. This connection is sometimes used in fluid power systems.

There are a few coupling systems used for hydraulic connections. They are identified as:

American, British, French, German, Japanese

This section lists the origin and coupling style. Descriptions and dimensional data follow each coupling style.



Thread Identification Table National Pipe Straight Mechanical (NPSM) National Pipe Tapered for Fuels (NPTF)

Dash Size	Inch Size	Thread Size	Female II	Thread D	Male Thread OD		
	(in.)	(in - TPI)	(mm)	(in.)	(mm)	(in.)	
-02	1/8	1/8 - 27	8.7	0.34	10.3	0.41	
-04	1/4	1/4 - 18	11.9	0.47	14.3	0.56	
-06	3/8	3/8 - 18	15.1	0.59	17.5	0.69	
-08	1/2	1/2 - 14	18.3	0.72	21.4	0.84	
-12	3/4	3/4 - 14	23.8	0.94	27.0	1.06	
-16	1	1 - 11 1/2	30.2	1.19	33.3	1.31	
-20	1 1/4	1 1/4 - 11 1/2	38.9	1.53	42.9	1.69	
-24	1 1/2	1 1/2 - 11 1/2	44.5	1.75	48.4	1.91	
-32	2	2 - 11 1/2	57.2	2.25	60.3	2.38	

ONE-PIECE B SERIES

HOSES

RELEASE EQUIPMENT ASSEMBLY

NFORMATION

ECHNICAL

QUICK



ALFACOMMA

Fitting Identification -American

American

SAE J514 Straight Thread O-Ring Boss (ORB)

This port connection is recommended by the N.F.P.A. for optional leakage control in medium and high pressure hydraulic systems. The O-ring boss male will mate with an O-ring boss female only.

The female is generally found on ports.

Thread Identification Table SAE J514 Straight Thread O-Ring Boss

Dash Size	Inch Size	Thread Size	Female II	Thread D	Male Thread OD		
	(in.)	(in - TPI)	(mm)	(in.)	(mm)	(in.)	
-02	1/8	5/16 - 24	6.9	0.27	7.8	0.31	
-03	3/16	3/8 - 24	8.5	0.34	9.4	0.37	
-04	1/4	7/16 - 20	9.9	0.39	11.2	0.44	
-05	5/16	1/2 - 20	11.5	0.45	12.6	0.49	
-06	3/8	9/16 - 18	12.9	0.51	14.1	0.56	
-08	1/2	3/4 - 16	17.5	0.69	18.9	0.74	
-10	5/8	7/8 - 14	20.5	0.81	22.1	0.87	
-12	3/4	1 1/16 - 12	24.9	0.98	26.9	1.06	
-14	7/8	1 3/16 - 12	28.1	1.11	30.0	1.18	
-16	1	1 5/16 - 12	31.3	1.23	33.1	1.31	
-20	1 1/4	1 5/8 - 12	39.2	1.54	41.1	1.62	
-24	1 1/2	1 7/8 - 12	45.6	1.79	47.4	1.87	
-32	2	2 1/2 - 12	61.4	2.42	63.3	2.49	

SAE J514 37° (JIC)

The Society of Automotive Engineers (SAE) specifies a 37° angle flare or seat be used with high pressure hydraulic tubing. These are commonly called JIC couplings.

The JIC 37°Flare male will only mate with a JIC female.

The JIC male has straight threads and a 37°Flare seat.

Thread Identification Table SAE J514 37°Flare (JIC)

Dash Size	Inch Size	Thread Size	Female II	Thread D	Male Thread OD		
	(in.)	(in - TPI)	(mm)	(in.)	(mm)	(in.)	
-02	1/8	5/16 - 24	6.9	0.27	7.8	0.31	
-03	3/16	3/8 - 24	8.5	0.34	9.4	0.37	
-04	1/4	7/16 - 20	9.9	0.39	11.2	0.44	
-05	5/16	1/2 - 20	11.5	0.45	12.6	0.49	
-06	3/8	9/16 - 18	12.9	0.51	14.1	0.56	
-08	1/2	3/4 - 16	17.5	0.69	18.9	0.74	
-10	5/8	7/8 - 14	20.5	0.81	22.1	0.87	
-12	3/4	1 1/16 - 12	24.9	0.98	26.9	1.06	
-14	7/8	1 3/16 - 12	28.1	1.11	30.0	1.18	
-16	1	1 5/16 - 12	31.3	1.23	33.1	1.31	
-20	1 1/4	1 5/8 - 12	39.2	1.54	41.1	1.62	
-24	1 1/2	1 7/8 - 12	45.6	1.79	47.4	1.87	
-32	2	2 1/2 - 12	61.4	2 4 2	63.3	2 4 9	

The male has straight threads and an O-ring. The female has straight threads and a sealing face. The seal is made at the O-ring on the male and sealing face on the female.

The threads hold the connection mechanically.

ONE-PIECE D SERIES

NFORMATION

ECHNICAL

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

KHCCA1020

SAE Straight Thread O-Ring Boss





"O" Ring Boss Male

"O" Ring Boss Female Port

The JIC female has straight threads and a 37°Flare seat.

The seal is made on the 37°Flare seat by establishing a line contact between the male flare and the female cone seat. The threads hold the connection mechanically.

CAUTION: In the -02, -03, -04, -05, -08 and -10 sizes, the threads of the SAE 45°Flare and the SAE 37°Flare are the same. However, the sealing surface angles are not the same. Carefully measure the seat angle to differentiate.



Fitting Identification -American



American (Continued)

SAE J512 45°

A term usually applied to fittings having a 45° angle flare or seat. Soft copper tubing is generally used in such applications as it is easily flared to the 45° angle. These are for low pressure applications commonly used in refrigeration, automotive and truck piping systems. The SAE 45°Flare male will mate with an SAE 45°Flare female only

The SAE male has straight threads and a 45°Flare seat.

Thread	Identification	Table
SAE J5 ⁻	12 45°	

Dash Size	Inch Size	Thread Size	Female II	Thread D	Male Thread OD	
	(in.)	(in - TPI)	(mm)	(in.)	(mm)	(in.)
-02	1/8	5/16 - 24	6.9	0.27	7.9	0.31
-03	3/16	3/8 - 24	8.6	0.34	9.6	0.38
-04	1/4	7/16 - 20	9.9	0.39	11.2	0.44
-05	5/16	1/2 - 20	11.4	0.45	12.7	0.50
-06	3/8	5/8 - 18	14.2	0.56	15.7	0.62
-07	7/16	11/16 - 16	15.7	0.62	17.3	0.68
-08	1/2	3/4 - 16	17.0	0.68	19.0	0.75
-10	5/8	7/8 - 14	20.3	0.80	22.3	0.88
-12	3/4	1 1/16 - 14	25.1	0.99	26.9	1.06
-14	7/8	1 1/4 - 12	29.5	1.16	31.7	1.25
-16	1	1 3/8 - 12	32.5	1.28	35.0	1.38

The SAE female has straight threads and a 45°Flare seat.

The seal is made on the 45°Flare seat.

The threads hold the connection mechanically.

CAUTION: In the -02, -03, -04, -05, -08 and -10 sizes, the threads of the SAE 45°Flare and the SAE 37°Flare are the same. However, the sealing surface angles are not the same. Carefully measure the seat angle to differentiate.



SAE 45° Flare Male

SAE 45° Flare Swivel Female

SAE J1453 O-Ring Face Seal (ORFS)

A seal is made when the O-ring in the male contacts the flat face on the female. Couplings are intended for hydraulic systems where elastomeric seals are acceptable to overcome leakage and leak resistance is crucial. This connection offers the very best leakage control available today.

The male connector has a straight thread and a machined flat face. The female has a straight thread and a machined flat face. The seal takes place by compressing the O-ring onto the flat face of the female, similar to the split flange type fitting. The threads hold the connection mechanically.

Thread Identification Table SAE J1453 O-Ring Face Seal (ORFS)

Dash Size	Inch Size	Thread Size	Female II	Thread C	Male Thread OD		
	(in.)	(in - TPI)	(mm)	(in.)	(mm)	(in.)	
-04	1/4	9/16 - 18	12.9	0.51	14.1	0.56	
-06	3/8	11/16 - 16	15.9	0.63	17.3	0.68	
-08	1/2	13/16 - 16	19.1	0.75	20.5	0.81	
-10	5/8	1 - 14	23.6	0.93	23.2	0.99	
-12	3/4	1 3/16 - 12	28.1	1.11	30.0	1.18	
-16	1	1 7/16 - 12	34.4	1.36	36.3	1.43	
-20	1 1/4	1 11/16 - 12	40.8	1.61	42.7	1.68	
-24	1 1/2	2 - 12	48.7	1.92	50.6	1.99	

O-Ring Face Seal (ORFS)



Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

NE-PIECE

EQUIPMENT ASSEMBLY

RELEASE QUICK

308



BALFACOMMN°

- Fitting Identification American

American (Continued)

SAE J512 Inverted Flare

This connection is frequently used in automotive systems. The male connector can either be a 45°Flare in the tube fitting form or a 42° seat in the machined adapter form.

Thread Identification Table SAE J512 Inverted Flare

Dash Inch Size Size		Thread Size	Female II	Thread D	Male Thread OD	
	(in.)	(in - TPI)	(mm)	(in.)	(mm)	(in.)
-02	1/8	5/16 - 28	6.9	0.27	7.9	0.31
-03	3/16	3/8 - 24	8.6	0.34	9.6	0.38
-04	1/4	7/16 - 24	9.9	0.39	11.2	0.44
-05	5/16	1/2 - 20	11.4	0.45	12.7	0.50
-06	3/8	5/8 - 18	14.2	0.56	15.7	0.62
-07	7/16	11/16 - 18	15.7	0.62	17.3	0.68
-08	1/2	3/4 - 18	17.0	0.68	19.0	0.76
-10	5/8	7/8 - 18	20.3	0.80	22.3	0.88
-12	3/4	1 1/16 - 16	25.1	0.99	26.9	1.06

The female has a straight thread with a 42° inverted flare. The seal takes place on the flared surface. The threads hold the connection mechanically.



Male Half

Female Half

HOSES

ONE-PIECE

DNE-PIECE D SERIES

ONE-PIECE F & P SERIES

TWO-PIECE FERRULES (A & PFR SERIES)

TWO-PIECE INSERTS (A SERIES)

TW0-PIECE INTERLOCK FERRULES & INSERTS

(X & Z SERIES)

QUICK

ASSEMBLY EQUIPMENT

NFORMATION

ECHNICAL

B SERIES

SAE J1467 Clip Fastener (Press-Lok Connector)

This is a radial O-ring seal connection commonly used for hydraulic applications in underground mines. The male contains an exterior O-ring and backup ring, plus, a groove to accept the "staple." The female has a smooth bore with two holes for the staple. A "U" shaped staple or retaining clip is inserted through the two holes, passing through the groove in the male to lock the connection together. The seal takes place by contact between the O-ring in the male and the smooth bore of the female.

Connector	Identification Table
SAE J1467	Clip Fastener

Dash Size	Inch Size	Ma O	ale D	Female ID			
		(in.)	(mm)	(in.)	(mm)		
-04	1/4	19/32	14.9	19/32	15.1		
-06	3/8	25/32	19.9	51/64	20.1		
-08	1/2	15/16	23.9	61/64	24.1		
-12	3/4	1 9/64	28.9	1 9/64	29.1		
-16	1	1 17/32	38.9	1 35/64	39.1		
-20	1 1/4	1 13/16	45.9	1 13/16	46.1		
-24	1 1/2	2 5/32	54.9	2 11/64	55.2		
-32	2	2 33/64	63.9	2 17/32	64.2		

Press-Lok Connectors



Staple Holes



Connector

Fitting Identification -American



American (Continued)

SAE J518/DIN20066/ISO-DIS 6162/JIS B8363 O-ring Flanges

This connection is commonly used in fluid power systems. There are two pressure ratings. Code 61 Form R, PN 35/350 bar, Type I, is referred to as the "standard" series and Code 62 Form S, PN 415 bar, Type II, is the "heavy duty" "6000 psi" series. The design concept for both series is the same, but the bolt hole spacing and flanged head diameters are larger for the higher pressure, Code 62 connection.

The female (port) is an unthreaded hole with four bolt holes in a rectangular pattern around the port.

The male consists of a flanged head, grooved for an O-ring, and either a captive flange or split flange halves with bolt holes to match the port. The seal take place on the O-ring, which is compressed between the flange head and the flat surface surrounding the port. The threaded bolts hold the connection together.

SAE J518, DIN 20066, ISO/ DIS 6162 and JIS B 8363 are interchangeable, except for bolt sizes.

SAE Code 61 and Code 62 flange 4 holes



Flange 4 holes

Flange Head Guide

		Cod	e 61		Code 62				Super CAT							
Flange Dash	Fla Si	nge ze	Flange Thickness		Flange Thickness		Flange Thickness		Fla Si	Flange Flang Size Thickr		nge Flange kness Size		nge ze	Flange Thickness	
Size	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)				
-08	1.19	30.2	.265	6.7	1.25	31.8	.305	7.7								
-10*	1.34	34.0	.265	6.7												
-12	1.50	38.1	.265	6.7	1.63	41.3	.345	8.7	1.63	41.3	.56	14.2				
-16	1.75	44.5	.315	8.0	1.88	47.6	.375	9.5	1.88	47.6	.56	14.2				
-20	2.00	50.8	.315	8.0	2.13	54.0	.405	10.3	2.13	54.0	.56	14.2				
-24	2.38	60.3	.315	8.0	2.50	63.5	.495	12.6	2.50	63.5	.56	14.2				
-32	2.81	71.4	.375	9.5	3.13	79.4	.495	12.6	3.13	79.4	.56	14.2				
-40	3.31	84.1	.375	9.5												

* -10 is a non-SAE size flange.

Note: All Code 61 flange head hose couplings meet or exceed SAE J518 Code 61 requirements for hydraulic split flange connections. The Code 61 flange head design can withstand a maximum operating pressure of 3000 to 5000 psi, depending on size.

How to Measure

Four Bolt Flange – First measure the port hole diameter using the calliper. Next, measure the longest bolt hole spacing from centre-to-centre (Dimension "A") or measure the flanged head diameter. OD

There are three exceptions:

- 1. The size -10, which is common outside of North America is not an SAE Standard size.
- 2. Caterpillar flanges, which are the same flange OD as SAE Code 62, have a thicker flange head.
- 3. Poclain flanges, which are completely different from SAE flanges.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.





NFORMATION

TECHNICAL

ALFACOMME

Fitting Identification -British

British Connections

British Standard Pipe Parallel

Popular couplings British Standard Pipe (BSP) threads, also known as Whitworth threads,

The BSPP (parallel) male will mate with a BSPP (parallel) female or a female port.

The BSPP male has straight threads and a 30° seat.

The BSPP female has straight threads and a 30° seat.

The female port has straight threads and a spotface. The seal on the port is made with an O-Ring or soft metal washer on the male.

The BSPP (parallel) connector is similar to, but not interchangeable with, the NPSM connector. The thread pitch is different in most sizes, and the thread angle is 55° instead of the 60° angle found on NPSM threads. The female swivel is BSPP has a tapered nose which seals on the cone seat of the male.

British Standard Pipe Tapered

The BSPT (tapered) male will mate with a BSPT (tapered) female, or a BSPP (parallel) female.

The BSPT male has tapered threads. When mating with either the BSPT (tapered) female or the BSPP (parallel) female port, the seal is made on the threads accomplished by thread distortion. A thread sealant is recommended.

The BSPT connector is similar to, but not interchangeable with, the NPTF connector. The thread pitch is different in most cases, and the thread angle is 55° instead of the 60° angle found on NPTF threads.

Thread Identification Table	
British Standard Pipe Parallel & Tapered (BS	SPP & PSPT)

Dash Inch Size Size		Thread Size	Female II	Thread D	Male Thread OD		
	(in.)	(in - TPI)	(mm)	(in.)	(mm)	(in.)	
-02	1/8	1/8 - 28	8.71	0.34	9.5	0.38	
-04	1/4	1/4 - 19	11.1	0.44	13.5	0.53	
-06	3/8	3/8 - 19	15.1	0.59	16.7	0.66	
-08	1/2	1/2 - 14	18/3	0.72	20.6	0.81	
-10	5/8	5/8 - 14	20.6	0.81	23.0	0.91	
-12	3/4	3/4 - 14	23.8	0.94	26.2	1.03	
-16	1	1 - 11	30.2	1.19	33.3	1.31	
-20	1 1/4	1 1/4 - 11	38.9	1.53	42.1	1.66	
-24	1 1/2	1 1/2 - 11	45.2	1.78	47.6	1.88	
-32	2	2 - 11	56.4	2.22	59.5	2.34	

BSPT Male

Thread

O.D.

British Standard Pipe Parallel (BSPP)



HOSES

ONE-PIECE

ONE-PIECE D SERIES

ONE-PIECE

B SERIES



Thread I.D.

British Standard Pipe Tapered (BSPT)

BSPT Female

NFORMATION

TECHNICAL



Fitting Identification -French



French Connections

French GAZ have a 24° seat and metric threads. These are similar to German DIN couplings, but the threads are different in some sizes, the French use fine threads in all sizes. French flanges are different than SAE, they have a lip that protrudes from the flange face. These are Poclain style flanges.

Millimetrique and GAZ 24°

This connection consists of a common male and two different females.

The French Metric (GAZ) male will mate with the female 24°Cone or the female tube fitting.

The male has a 24° seat and straight metric threads. The female has a 24° seat or a tubing sleeve and straight metric threads. The Millimetrique Series is used with whole number metric O.D. tubing and the GAZ Series is used with fractional number metric O.D. pipe size tubing.



GAZ Poclain 24°Flange

The Poclain (French GAZ) 24° high pressure flange is usually found on Poclain equipment.

The male flange will mate with a female flange or port.

The seal is made on the 24° seat.

Thread Identification Table French Metric Millimetrique

Metric Thread	Female II	Thread D	Male ⁻ 0	Thread)D	Tu O	be D
(Dia. X Pitch)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)
M12 X 1.0	11.0	0.43	12.0	0.47	6	0.24
M14 X 1.5	12.5	0.49	14.0	0.55	8	0.31
M16 X 1.5	14.5	0.57	16.0	0.63	10	0.39
M18 X 1.5	16.5	0.65	18.0	0.71	12	0.47
M20 X 1.5	18.5	0.73	20.0	0.79	14	0.55
M22 X 1.5	20.5	0.81	22.0	0.87	15	0.59
M24 X 1.5	22.5	0.89	24.0	0.94	16	0.63
M27 X 1.5	25.5	1.00	27.0	1.06	18	0.71
M30 X 1.5	28.5	1.12	30.0	1.18	22	0.87
M33 X 1.5	31.5	1.24	33.0	1.30	25	0.98
M36 X 1.5	34.5	1.36	36.0	1.42	28	1.10
M39 X 1.5	37.5	1.48	39.0	1.54	30	1.18
M42 X 1.5	40.5	1.59	42.0	1.65	32	1.26
M45 X 1.5	43.5	1.71	45.0	1.77	35	1.38
M48 X 1.5	46.5	1.83	48.0	1.89	38	1.50
M52 X 1.5	50.5	1.99	52.0	2.05	40	1.57
M54 X 2.0	51.9	2.04	54.0	2.13	45	1.77

Thread Identification Table French Metric GAZ 24°Cone

Dash Size	Inch Female Thread		Male 1 0	「hread D	Tube OD 60°Cone		
(Dash)	(Dia. X Pitch)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)
-6	M20 X 1.5	18.5	0.73	20.0	0.78	13.25	0.52
-8	M24 X 1.5	22.5	0.89	24.0	0.94	16.75	0.66
-10	M30 X 1.5	28.5	1.12	30.0	1.18	21.25	0.83
-12	M36 X 1.5	34.5	1.36	36.0	1.41	26.75	1.05
-16	M45 X 1.5	43.5	1.71	45.0	1.77	33.50	1.32
-20	M52 X 1.5	50.5	1.99	52.0	2.04	42.25	1.66

NFORMATION

<u>-ECHNICAI</u>

ALFACOMMA®

Fitting Identification -German

German DIN Connections

A coupling referred to as metric, usually means a DIN coupling. Flanges are standard Code 61 or Code 62.

DIN 2353 24°Cone

The DIN 24°Cone male will mate with any of the three females shown below.

The male has a 24° seat, straight metric threads, and a recessed counterbore which matches the tube O.D. used with it. The mating female may be a 24°Cone with O'Ring, (DKO type) a metric tube fitting or a universal 24° or 60°Cone.

Thread Identification Table DIN 24°Cone

	Ferr	nale	M	ale	Tube OD				
Metric	Thread		Thr	Thread		Light		Heavy	
(Die V Diteh))	0	U	Ser	ies	Ser	ies	
(Dia. X Pilcii)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	
M12 X 1.5	10.5	0.41	12	0.47	6	0.24			
M14 X 1.5	12.5	0.49	14	0.55	8	0.31	6	0.24	
M16 X 1.5	14.5	0.57	16	0.63	10	0.39	8	0.31	
M18 X 1.5	16.5	0.65	18	0.71	12	0.47	10	0.39	
M20 X 1.5	18.5	0.73	20	0.79			12	0.47	
M22 X 1.5	20.5	0.81	22	0.87	15	0.59	14	0.55	
M24 X 1.5	22.5	0.89	24	0.94			16	0.63	
M26 X 1.5	24.5	0.96	26	1.02	18	0.71			
M30 X 2.0	27.9	1.10	30	1.18	22	0.87	20	0.79	
M36 X 2.0	33.9	1.33	36	1.42	28	1.10	25	0.98	
M42 X 2.0	39.9	1.57	42	1.65			30	1.18	
M45 X 2.0	42.9	1.69	45	1.77	35	1.38			
M52 X 2.0	49.9	1.96	52	2.05	42	1.65	38	1.50	

DIN 3863 60°Cone

This connection is frequently used in hydraulic systems. The DIN 60°Cone male will mate with the female universal 24° or 60°Cone only.

The male has a 60° seat and straight metric threads.

Thread Identification Table DIN 60°Cone

Metric Thread	Female I	e Thread D	Male ⁻ C	Thread D	Tu O	be D
(Dia. X Pitch)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)
M12 X 1.5	10.5	0.41	12	0.47	6	0.24
M14 X 1.5	12.5	0.49	14	0.55	8	0.31
M16 X 1.5	14.5	0.57	16	0.63	10	0.39
M18 X 1.5	16.5	0.65	18	0.71	12	0.47
M22 X 1.5	20.5	0.81	22	0.87	15	0.59
M26 X 1.5	24.5	0.96	26	1.02	18	0.71
M30 X 1.5	28.5	1.12	30	1.18	22	0.87
M38 X 1.5	36.5	1.44	38	1.50	28	1.10
M45 X 1.5	43.5	1.71	45	1.77	35	1.38
M52 X 1.5	50.5	1.99	52	2.05	42	1.65

There is a light and heavy series DIN coupling. Proper identification is made by measuring both the thread size and the tube O.D. (The heavy series has a smaller tube O.D. than the light, but has a thicker wall section).

DIN 24° Male and Mating Females





The female has a 24° and 60° universal seat and straight metric threads. The seal takes place by contact between the cone of the male and the nose of the flareless swivel. The threads hold the connection mechanically.

DIN 60° Male and Mating Female





Universal 24° or 60° Cone

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



Kuriyama of America, Inc. www.kuriyama.com

EQUIPMENT ASSEMBLY

NFORMATION

ECHNICA

HOSES

Fitting Identification -German

HOSES

ONE-PIECE B SERIES

ONE-PIECE D SERIES

F & P SERIES **ONE-PIECE**

TWO-PIECE FERRULES

TWO-PIECE INSERTS (A SERIES)

> FERRULES & INSERTS TWO-PIECE INTERLOCK

(X & Z SERIES)

RELEASE QUICK

EQUIPMENT ASSEMBLY

INFORMATION TECHNICAL

(A & PFR SERIES)

German DIN Connections (Continued)

Metric Standpipe

A metric standpipe is comprised of three components attached to a male fitting. The components are: a Standpipe, Bite Sleeve and Metric Nut. The nut is placed over the Standpipe, followed by the Bite Sleeve (see illustration below). For DIN light assemblies, a DIN light metric nut is used. For DIN heavy assemblies, a DIN heavy metric nut is used. The Bite Sleeve and Standpipe are selected on the basis of tube O.D.



Tube O.D.	Metric Nut Thread	
(mm)	Light	Heavy
6	M12 x 1.5	
8	M14 x 1.5	M16 x 1.5
10	M16 x 1.5	M18 x 1.5
12	M18 x 1.5	M20 x 1.5
15	M22 x 1.5	
16		M24 x 1.5
18	M26 x 1.5	
20		M30 x 2.0
22	M30 x 2.0	
25		M36 x 2.0
28	M36 x 2.0	
30		M42 x 2.0
35	M45 x 2.0	
38		M52 x 2.0
42	M52 x 2.0	

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



314

ALFAGOMME

Fitting Identification -Japanese

Japanese Connections

Japanese equipment uses JIS (Japanese Industrial Standard) couplings with a 30° seat and British Standard Pipe Parallel threads. All flanges are code 61 or Code 62 (except -10).

JIS 30°Flare Parallel Pipe Threads

JIS B 0202

These Japanese 30°Flare male coupling will mate with a Japanese 30°Flare female only.

The male and female have straight threads and a 30° seat. The seal is made on the 30° seat.

The threads on the Japanese 30°Flare connector conform to JIS B 020, the same as the BSPP threads. Both the British and Japanese connectors have a 30° seat, but they are not interchangeable, because the British seat is inverted.

JIS 30° Inverted Seat, Parallel Pipe Threads **JIS B 0202**

The JIS parallel is similar to the BSPP connection. The JIS parallel thread and the BSPP connection are interchangeable.

JIS Tapered Pipe Thread (PT)

Thread Identification Table

Thread

Size

(in - TPI)

1/8 - 28

1/4 - 19

3/8 - 19

1/2 - 14

5/8 - 14

3/4 - 14

1 - 11

1 1/4 - 11

1 1/2 - 11

2 - 11

Inch

Size

(in.)

1/8

1/4

3/8

1/2

5/8

3/4

1

1 1/4

1 1/2

2

JIS B 0203

Dash

Size

-02

-04

-06

-08

-10

-12

-16

-20

-24

-32

The JIS tapered pipe thread connection is similar to the BSPT connection and fully interchangeable. The Japanese connection does not have a 30°Flare. and will not mate with the BSPP female. The threads conform to JIS B 0203, same as BSPT threads.

The seal on the JIS tapered pipe thread connection is made on the threads.

(mm)

8.7

11.9

15.1

19.1

20.6

23.8

30.2

38.9

45.2

56.4

JIS Tapered Pipe, 30°Flare Parallel Pipe, and 30° Male Inverted Seat

(in.)

0.34

0.47

0.59

0.75

0.81

0.94

1.19

1.53

1.78

2.22

Female Thread

ID

Male Thread

Π

(in.)

0.38

0.53

0.66

0.81

0.91

1.03

1.31

1.66

1.88

2.34

(mm)

9.5

13.5

16.7

20.6

23.1

26.2

33.3

42.1

47.6

59.5







Female





Female

TW0-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)

HOSES

ONE-PIECE

DNE-PIECE

SERIES

F & P SERIES **ONE-PIECE**

TWO-PIECE FERRULES

TWO-PIECE INSERTS

(A SERIES)

(A & PFR SERIES)

QUICK	RELEASE

<u> VFORMATION</u>

ECHNICA

		AS





Fitting Identification -Japanese

Japanese Connections (Continued)

The Komatsu style 30°Flare Parallel thread coupling is identical to the Japanese 30°Flare parallel except

Male

Thread

0. D.

(mm)

18

22

24

30

33

36

42

Metric

Thread

Size

M18 x 1.5

M22 x 1.5

M24 x 1.5

M30 x 1.5

M33 x 1.5

M36 x 1.5

M42 x 1.5

В

Thread

I.D.

(mm)

16.4

20.4

22.4

28.4

31.4

34.4

40.4

Komatsu Style 30°Flare Parallel Threads

for the threads. The Komatsu uses Metric fine

The Komatsu connector seals on the 30°Flare.

(mm)

9.5

13

16

19

25

32

38

threads which conform to JIS B 0207.

Nominal Size

(in.)

3/8

1/2

5/8

3/4

1

1 1/4

 $1 \frac{1}{2}$

HOSES

ONE-PIECE B SERIES

D SERIES

Komatsu Flange Fitting

The Komatsu Flange fitting is nearly identical to and fully interchangeable with the SAE Code 61 flange fitting. In all sizes the O-ring dimensions are different. When replacing a Komatsu flange with an SAE style flange, an SAE style O-ring must be used.

Flange Dash	Nomin	al Size	Flange Size	А	В
Size	(in.)	(mm)	(in.)	(in.)	(in.)
-08	1/2	12.7	1.19	.73	.98
-10*	5/8	15.9	1.34	.73	1.10
-12	3/4	19.1	1.50	.85	1.22
-16	1	25.4	1.75	1.12	1.50
-20	1 1/4	31.8	2.00	1.36	1.73
-24	1 1/2	38.1	2.38	1.75	2.12
-32	2	50.8	2.81	2.22	2.56

This is a non-SAE size flange



Male

Female

Komatsu Style Flange Fitting



Flange

Dash

Size

-06

-08

-10

-12

-16

-20

-24

(X & Z SERIES)

EQUIPMENT ASSEMBLY

INFORMATION **TECHNICAL**

ALFACOMME

Torque Data

Recommended Fitting and Adapter Installation Torque

Please note that the recommended values shown on this page change on a periodic basis. These are the known recommended values as set by the appropriate agency standards at the time of this catalog printing.

BSPP

SAE J514 37°Flare (JIC)

Dash	Thread	lb.	ft.	N.	m
Size	Size	Min	Max	Min	Max
-04	7/16 - 20	11	12	15	16
-05	1/2 - 20	14	15	19	21
-06	9/16 - 18	18	20	24	28
-08	3/4 - 16	36	39	49	53
-10	7/8 - 14	57	63	77	85
-12	1 1/16 - 12	79	88	107	119
-14	1 3/16 - 12	94	103	127	140
-16	1 5/16 - 12	108	113	147	154
-20	1 5/8 - 12	127	133	172	181
-24	1 7/8 - 12	158	167	215	226
-32	2 1/2 - 12	245	258	332	350

Dash	Thread	Torque	e lb. Ft.	Torque N m	
Size	Size	With 0-Ring	Without 0-Ring	With 0-Ring	Without O-Ring
-02	1/8-28	N/A	7	N/A	10
-04	1/4-19	15	15	20	20
-06	3/8-19	26	26	35	35
-08	1/2-14	37	44	50	60
-10	5/8-14	44	52	60	70
-12	3/4-14	63	85	85	115
-16	1-11	85	103	115	140
-20	1 1/4-11	140	155	190	210
-24	1 1/2-11	177	214	240	290
-32	2-11	221	295	300	400

SAE J1453 O-Ring Face Seal

Dash	Thread	lb.	ft.	N. m	
Size	Size	Min	Max	Min	Max
-04	9/16 - 18	10	12	14	16
-06	11/16 - 16	18	20	24	27
-08	13/16 - 16	32	35	43	47
-10	1 - 14	46	50	60	68
-12	1 3/16 - 12	65	70	90	95
-16	1 7/16 - 12	92	100	125	135
-20	1 11/16 - 12	125	140	170	190
-24	2 - 12	150	165	200	225

SAE J518 Code 61 Flange Half Bolt

Dash	Thread	lb. ft.		Thread Ib. ft. N. m		m
Size	Size	Min	Max	Min	Max	
-08	1/2	15	19	20	25	
-12	3/4	21	29	28	40	
-16	1	27	35	37	48	
-20	1 1/4	35	46	48	62	
-24	1 1/2	46	58	62	79	
-32	2	54	66	73	90	
-40	2 1/2	79	91	107	124	
-48	3	137	149	186	203	

SAE J518 Code 62 Flange Half Bolt

Dash	Thread	lb.	ft.	N. m	
Size	Size	Min	Max	Min	Max
-08	1/2	15	19	20	25
-12	3/4	25	33	34	45
-16	1	42	50	56	68
-20	1 1/4	62	75	85	102
-24	1 1/2	116	133	158	181
-32	2	199	216	271	294

JIS (B8363)

Dash Size	Thread Size	lb. ft.	N.m
-04	1/4 - 19	19	25
-06	3/8 - 19	25	34
-08	1/2 - 14	49	64
-10	5/8 - 14	100	132
-12	3/4 - 14	100	132
-16	1 - 11	149	196
-20	1 1/4 - 11	171	225
-24	1 1/2 - 11	194	255
-32	2 - 11	240	316

Metric		
Thread mm	lb. ft.	N. m
M12 x 1.5	15	15
M14 x 1.5	19	25
M16 x 1.5	33	45
M18 x 1.5	37	50
M20 x 1.5	52	70
M22 x 1.5	55	75
M24 x 1.5	74	100
M26 x 1.5	81	110
M30 x 2	96	160
M36 x 2	162	220
M42 x 2	170	230
M45 x 2	220	300
M52 x 2	367	500

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



Kuriyama of America, Inc. www.kuriyama.com

HOSES

ONE-PIECE B SERIES

TECHNICAL INFORMATION

Torque Data



JIC FFFT TORQUE METHOD

The FFFT (Flats From Finger Tight) method allows to assemble fittings and adapters at the correct torque value without a dynamometric wrench. The rotation applied according the value shown in Tab.1 ensures a good sealing, avoid unscrewing and over torque that can cause nut or cone crack.

Assembling instruction:

HOSES

ONE-PIECE B SERIES

D SERIES

ONE-PIECE F & P SERIES

TWO-PIECE FERRULES (A & PFR SERIES)

TWO-PIECE INSERTS (A SERIES)

FERRULES & INSERTS

QUICK

ASSEMBLY EQUIPMENT

TECHNICAL INFORMATION

(X & Z SERIES)

- hand tighten the joint
- make a longitudinal mark on one of the flats of hex and continue it on the body hex as shown in Fig.1
- tighten the joint further by the number of flat as shown in Tab.1



Fig.1

Assembling value - carbon steel material - SAE J514 JIC 37° flare												
Dash	Thread	Lb)*ft	N ³	N*m							
size		min	max	min	max	0/+0.25						
-4	7/16-20	11	12	15	16	2						
-5	1/2-20	14	15	19	21	2						
-6	9/16-18	18	20	24	28	2						
-8	3/4-16	36	39	49	53	1.5						
-10	7/8-14	57	63	77	85	1.5						
-12	1 1/16-12	79	88	107	119	1						
-14	1 3/16-12	94	103	127	140	1						
-16	1 5/16-12	108	113	147	154	1						
-20	1 5/8-12	127	133	172	181	1						
-24	1/78-12	158	167	215	226	1						
-32	2 1/2-12	245	258	332	350	1						

Tab.1





Pressure & Distance Conversions

	Pressure Metri (1 kPa =	Conversic c to PSI 0.145 PSI)	on		Pressure Conversion PSI to Metric (1 PSI = 6.89 kPa)								
Kilo Pascals (kPa)	Mega Pascals (MPa)	Bar (Bar)	Pounds per Square Inch (PSI)	Pound Square (PS	ls per e Inch SI)	Kilo Pascals (kPa)	Mega Pascals (MPa)	Bar (Bar)					
100	0.1	1	14.5		10	68.9	0.07	0.7					
200	0.2	2	29.0		20	137.9	0.14	1.4					
300	0.3	3	43.5		30	206.8	0.21	2.1					
400	0.4	4	58.0		40	275.8	0.28	2.8					
500	0.5	5	72.5		50	344.7	0.34	3.4					
600	0.6	6	87.0		60	413.7	0.41	4.1					
700	0.7	7	101.5		70	482.6	0.48	4.8					
800	0.8	8	116.0		80	551.6	0.55	5.5					
900	0.9	9	130.5		90	620.5	0.62	6.2					
1,000	1.0	10	145.0		100	689	0.7	6.9					
2,000	2.0	20	290.1		200	1,379	1.4	13.8					
3,000	3.0	30	435.1		300	2,068	2.1	20.7					
4,000	4.0	40	580.2		400	2,758	2.8	27.6					
5,000	5.0	50	725.2		500	3,447	3.4	34.5					
6,000	6.0	60	870.2		600	4,137	4.1	41.4					
7,000	7.0	70	1,015		700	4,826	4.8	48.3					
8,000	8.0	80	1,160		800	5,516	5.5	55.2					
9,000	9.0	90	1,305		900	6,205	6.2	62.1					
10,000	10	100	1,450	1,	,000	6,895	6.9	68.9					
20,000	20	200	2,901	2,	000	13,790	13.8	147.9					
30,000	30	300	4,351	3,	,000	20,684	20.7	206.8					
40,000	40	400	5,802	4,	000	27,579	27.6	275.8					
50,000	50	500	7,252	5,	000	34,474	34.5	344.7					
60,000	60	600	8,702	6,	000	41,369	41.4	413.7					
70,000	70	700	10,153	7,	,000	48,263	48.3	482.6					
80,000	80	800	11,603	8,	000	55,158	55.2	551.6					
90,000	90	900	13,053	9,	,000	62,053	62.1	620.5					
100,000	100	1,000	14,504	10,	,000	68,948	68.9	689.0					
200,000	200	2,000	29,008	20,	,000	137,895	147.9	1,379.0					
300,000	300	3,000	43,511	30,	,000	206,843	206.8	2,068.0					
				40,	,000	275,790	275.8	2,758.0					

Decimal and Millimeter Equivalents of Fractions

Inc	ches	mm	Inches		mm]	Inches		mm	Inc	ches	mm	
1/64	.0156	.397	17/64	.2656	6.747		33/64	.5156	13.097	49/64	.7656	19.447	
1/32	.0312	.794	9/32	.2812	7.144		17/32	.5312	13.494	25/32	.7812	19.844	
3/64	.0468	1.191	19/64	.2968	7.541		35/64	.5468	13.891	51/64	.7968	20.241	
1/16	.0625	1.588	5/16	.3125	7.938		9/16	.5625	14.288	13/16	.8125	20.638	
5/64	.0781	2.381	21/64	.3281	8.334		37/64	.5781	14.684	53/64	.8281	21.034	
3/32	.0937	2.381	11/32	.3437	8.731		19/32	.5937	15.081	27/32	.8437	21.431	
7/64	.1093	2.778	23/64	.3593	9.128		39/64	.6093	15.478	55/64	.8593	21.828	
1/8	.1250	3.175	3/8	.3750	9.525		5/8	.6250	15.875	7/8	.8750	22.225	
9/64	.1406	3.572	25/64	.3906	9.922		41/64	.6406	16.272	57/64	.8906	22.622	
5/32	.1562	3.969	13/32	.4062	10.319		21/32	.6562	16.669	29/32	.9062	23.019	
11/64	.1718	4.366	27/64	.4218	10.716		43/64	.6718	17.066	59/64	.9218	23.416	
3/16	.1875	4.763	7/16	.4375	11.113		11/16	.6875	17.463	15/16	.9375	23.813	
13/64	.2031	5.159	29/64	.4531	11.509		45/64	.7031	17.859	61/64	.9531	24.209	
7/32	.2187	5.556	15/32	.4687	11.906		23/32	.7187	18.256	31/32	.9687	24.606	
15/64	.2343	5.963	31/64	.4843	12.303		47/64	.7343	18.653	63/64	.9843	25.003	
1/4	.2500	6.350	1/2	.5000	12.700		3/4	.7500	19.050	1	1.0000	25.400	

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



ONE-PIECE B SERIES

HOSES

TECHNICAL INFORMATION

Temperature Conversions



HOSES

TECHNICAL INFORMATION

Temperature Conversion Tables

		-4	459 to	0				0 t	o 1	00			1 [100 t	o 1	,000,		
BS			°C				°C				°C		1 [°C				°C	
	°(0	°F	°F		°C	°F	°F		°C	°F	°F	┥┟	°C	°F	°F		°C	°F	°F
S R	-2	73	-459.4			-17.8	0	32.0		10.0	50	122.0		38	100	212		260	500	932
	-20	50 62	-450 -440			-17.2	2	35.6		10.6	51 52	123.0		43 49	120	230		200	520	950 968
	-2	57	-430			-16.1	3	37.4		11.7	53	127.4		54	130	266		277	530	986
SH I	-2	51	-420			-15.6	4	39.2		12.2	54	129.2		60	140	284		282	540	1004
	-24	46	-410			-15.0	5	41.0		12.8	55	131.0		66	150	302		288	550	1022
S H	-24	40 34	-400			-14.4	0 7	42.8		13.3	50 57	132.8		/ I 77	160	320		293	560 570	1040
-71	-2	29	-380			-13.3	8	46.4		14.4	58	136.4		82	180	356		304	580	1076
~ S	-22	23	-370			-12.8	9	48.2		15.0	59	138.2		88	190	374		310	590	1094
P S F	-2	18	-360			-12.2	10	50.0		15.6	60	140.0		93	200	392		316	600	1112
E	-2	12	-350			-11.7	11	51.8		16.1	61	141.8		99	210	410		321	610	1130
S 🖷	-20		-340			-10.6	12	55.0		17.2	63	145.0		100	212	413		332	630	1140
	-19	96	-320			-10.0	14	57.2		17.8	64	147.2		110	230	446		338	640	1184
T N	-19	90	-310			-9.4	15	59.0		18.3	65	149.0		116	240	464		343	650	1202
(A \approx	-18	84	-300			-8.9	16	60.8		18.9	66 67	150.8		121	250	482		349	660	1220
* PF	-1	73	-290			-0.3 -7.8	18	64.6		19.4 20.0	68 68	152.0		132	200	518		354	670 680	1230
REF	-10	59	-273	-459		-7.2	19	66.2		20.6	69	156.2		138	280	536		366	690	1274
	-1(68	-270	-454		-6.7	20	68.0		21.1	70	158.0		143	290	554		371	700	1292
	-1(62	-260	-436		-6.1	21	69.8		21.7	71	159.8		149	300	572		377	710	1310
S.	-1:	57 51	-250 -240	-418 -400		-5.6 -5.0	22	73.4		22.2	72	163.4		154 160	310	590 608		382	720	1328
	-14	46	-230	-382		-4.4	24	75.2		23.3	74	165.2		166	330	626		393	740	1364
TW	-14	40	-220	-364		-3.9	25	77.0		23.9	75	167.0		171	340	644		399	750	1382
~ P	-1;	34	-210	-346		-3.3	26	78.8		24.4	76	168.8		177	350	662		404	760	1400
ASE	-12	29	-200	-328		-2.8	27	80.6		25.0 25.6	// 78	170.6		182 188	360	080 808		410	770	1418
	-1	18	-180	-292		-1.7	29	84.2		26.1	79	174.2		193	380	716		421	790	1454
^{s)} ISE	-1	12	-170	-274		-1.1	30	86.0		26.7	80	176.0		199	390	734		427	800	1472
RTS	-1(07	-160	-256		-0.6	31	87.8		27.2	81	177.8		204	400	752		432	810	1490
	-1(-150	-238		0	32	89.6		27.8	82 83	1/9.6		210	410 420	788		438	820 830	1508
	-9		-140	-202		1.1	33 34	93.2		28.9	84	183.2		221	420	806		443	840	1544
Ë₽	-8	4	-120	-184		1.7	35	95.0		29.4	85	185.0		227	440	824		454	850	1562
× Pli	-7	9	-110	-166		2.2	36	96.8		30.0	86	186.8		232	450	842		460	860	1580
ES ES	-/	3	-100	-148		2.8	37	98.6		30.6	87	188.6		238	460	860		466	870	1598
SER & N	-6	2	-80	-112		3.9	39	102.2		31.7	89	192.2		243 249	470	896		477	890	1634
ES) RER	-5	7	-70	-94		4.4	40	104.0		32.2	90	194.0		254	490	914		482	900	1652
폭티	-5	1	-60	-76		5.0	41	105.8		32.8	91	195.8						488	910	1670
∾ ¥	-4	6	-50	-58		5.6	42	107.6		33.3	92	197.6						493	920	1688
	-4	4	-40 -30	-40 -22		0.1 6.7	43 44	109.4		33.9 34.4	93 94	201 2						499 504	930 940	1700
Ro	-2	9	-20	-4		7.2	45	113.0		35.0	95	203.0						510	950	1742
EA C	-2	3	-10	14		7.8	46	114.8		35.6	96	204.8						516	960	1760
ŚН 🗶	-17	7.8	0	32		8.3	47	116.6		36.1	97	206.6						521	970	1778
						8.9 0.4	48 10	118.4		36.7 37 2	98	208.4						527 522	980	1/95
۳×۵						5.4	49	120.2		37.8	100	212.0						538	1000	1832
SSEMBLY	Look up the reading in the middle (shaded) column. To determine equivalent in Fahrenheit, look in right hand column; to determine equivalent in Centigrade, look in left hand column. Example: -20°F = -29°C (left).																			

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

320



ALFACOMME

Hexagon Across Corner Dimensions

The across corner dimensions are calculated using the factor 1.1547. Should the corners be rounded, the across corner dimensions will be smaller than shown in the table below.

Metric H	lex Sizes			н	exagons i	n inches ar	Inch He	x Sizes	er dimens	sions in mn	1		
S	e	s			e		S		e		е		
mm	mm	In	In	mm	mm	In			mm	In	In	mm	mm
10	11.5	1/4	0.25	6.4	7.4	1 1/4	1.25	31.8	36.7	2 5/16	2.31	58.7	67.8
12	13.8	9/32	0.28	7.1	8.2	1 9/32	1.28	32.5	37.5	2 3/8	2.38	60.3	69.6
14	16.2	5/16	0.31	7.9	9.1	1 5/16	1.31	33.3	38.5	2 7/16	2.44	61.9	71.5
17	19.6	11/32	0.34	8.7	10.0	1 11/32	1.34	34.1	39.4	2 1/2	2.50	63.5	73.3
19	21.9	3/8	0.38	9.2	10.6	1 3/8	1.38	34.9	40.3	2 9/16	2.56	65.1	75.2
22	25.4	13/32	0.41	10.3	11.9	1 13/32	1.41	35.7	41.2	2 5/8	2.63	66.7	77.0
24	27.7	7/16	0.44	11.1	12.8	1 7/16	1.44	36.5	42.1	2 11/16	2.69	68.3	78.9
27	31.2	15/32	0.47	11.9	13.7	1 15/32	1.47	37.3	43.1	2 3/4	2.75	69.9	80.7
30	34.6	1/2	0.50	12.7	14.7	1 1/2	1.50	38.1	44.0	2 13/16	2.81	71.4	82.4
32	36.9	17/32	0.53	13.5	15.6	1 17/32	1.53	38.9	44.9	2 7/8	2.88	73.0	84.3
36	41.6	9/16	0.56	14.3	16.5	1 9/16	1.56	39.7	45.8	2 15/16	2.94	74.6	86.1
41	47.3	19/32	0.59	15.1	17.4	1 19/32	1.59	40.5	46.8	3	3.00	76.2	88.0
46	53.1	5/8	0.63	15.9	18.4	1 5/8	1.63	41.3	47.7	3 1/16	3.06	77.8	89.8
50	57.7	21/32	0.66	16.7	19.3	1 21/32	1.66	42.1	48.6	3 1/8	3.13	79.4	91.7
55	63.5	11/16	0.69	17.5	20.2	1 11/16	1.69	42.9	49.5	3 3/16	3.19	81.0	93.5
60	69.3	23/32	0.72	18.3	21.1	1 23/32	1.72	43.7	50.5	3 1/4	3.25	82.6	95.4
65	75.0	3/4	0.75	19.1	22.0	1 3/4	1.75	44.5	51.4	3 5/16	3.31	84.1	97.1
70	80.0	25/32	0.78	19.8	22.9	1 25/32	1.78	45.2	52.2	3 3/8	3.38	85.7	99.0
75	86.5	13/16	0.81	20.6	23.8	1 13/16	1.81	46.0	53.1	3 7/16	3.44	87.3	100.8
80	92.4	27/32	0.84	21.4	24.7	1 27/32	1.84	46.8	54.0	3 1/2	3.50	88.9	102.7
85	98.0	7/8	0.88	22.2	25.6	1 7/8	1.88	47.6	55.0	3 9/16	3.56	90.5	104.5
90	104	29/32	0.91	23.0	26.6	1 29/32	1.91	48.4	55.9	3 5/8	3.63	92.1	106.3
95	110	15/16	0.94	23.8	27.5	1 15/16	1.94	49.2	56.8	3 11/16	3.69	93.7	108.2
100	116	31/32	0.97	24.6	28.4	1 31/32	1.97	50.0	57.7	3 3/4	3.75	95.3	110.0
105	121	1	1.00	25.4	29.3	2	2.00	50.8	58.7	3 13/16	3.81	96.8	11.8
110	127	1 1/32	1.03	26.2	30.3	2 1/32	2.03	51.6	59.6	3 7/8	3.88	98.4	113.6
115	133	1 1/16	1.06	27.0	31.2	2 1/16	2.06	52.4	60.5	3 15/16	3.94	100.0	115.5
120	139	1 3/32	1.09	27.8	32.1	2 3/32	2.09	53.2	61.4	4	4.00	101.6	117.3
130	150	1 1/8	1.13	28.6	33.0	2 1/8	2.13	54.0	62.4	4 1/8	4.13	104.8	121.0
135	156	1 5/32	1.16	29.4	33.9	2 5/32	2.16	54.8	63.3	4 1/4	4.25	108.0	124.7
145	167	1 3/16	1.19	30.2	34.9	2 3/16	2.19	55.6	64.2	4 3/8	4.38	111.1	128.3
150	173	1 7/32	1.22	31.0	35.8	2 1/4	2.25	57.5	66.0	4 1/2	4.50	114.3	132.0

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.





ONE-PIECE B SERIES

DNE-PIECE D SERIES

F & P SERIES **ONE-PIECE**

TWO-PIECE FERRULES (A & PFR SERIES)

TWO-PIECE INSERTS (A SERIES)

TWO-PIECE INTERLOCK FERRULES & INSERTS (X & 2 SERIES)

QUICK RELEASE

ASSEMBLY EQUIPMENT

TECHNICAL INFORMATION

Notes



HOSES	
ONE-PIECE B SERIES	
one-piece D series	
one-piece F & P Series	
TWO-PIECE FERRULES (A & PFR SERIES)	
TWO-PIECE INSERTS (A SERIES)	
TWO-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)	
QUICK RELEASE	
ASSEMBLY EQUIPMENT	

INFORMATION

TECHNICA





Cautionary and Warranty Statement

Cautionary Statement

AII Products sold and distributed by Kuriyama of America, Inc. are commodities and are sold based on their ability to perform within each product's published specifications. The Products are not sold for particular purposes, uses or applications. Purchasers and users are solely responsible for determining whether the Products are suitable for the purchaser's or user's intended purposes, uses or applications. Purchasers and users shall conduct their own engineering studies or tests, or retain qualified engineers, consultants or test-ing laboratories before determining the proper use, suitability or propriety of the Products. Alfagomma and Piranha Hose hoses and fittings are designed, engineered and tested to be used together in an assembly. Alfagomma and Piranha Hose do not recommend or authorize the use of their hoses or fittings with another manufacturer's hoses or fittings, as doing so may result in unreliable or unsafe assemblies.

Purchasers and users should follow all instructions contained in the catalogs, brochures, technical bulletins and other documents of Kuriyama of America, Alfagomma and Piranha Hose. Kuriyama of America, Alfagomma and Piranha Hose recommend only those hose and coupling combinations specified in the applicable Hydraulic Products Catalogs. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation, and all sections of hose and tubing – including connections, couplings, clamps, conductivity and bonding – should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened to avoid leakage, prevent injuries or damage, and for general safety purposes.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

Kuriyama of America, Alfagomma and Piranha Hose shall not be liable or responsible for hose assemblies that have not been produced in conformance with their assembly recommendations and current crimp data charts.

Limited Warranty and Limitation of Liability

The Products sold or distributed by Kuriyama of America are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions. ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER KURIYAMA OF AMERICA SHIPPED THE PRODUCTS. KURIYAMA OF AMERICA'S LIABILITY HEREUNDER IS LIMITED, AT KURIYAMA OF AMERICA'S EXCLUSIVE DISCRETION, TO 1) REFUND OF THE PURCHASE PRICE PAID TO IT FOR DEFECTIVE PRODUCTS; OR 2) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO KURIYAMA OF AMERICA.

THIS LIMITED WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESSED, IM-PLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIM-ITED TO, ANY WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICU-LAR PURPOSE. IN NO EVENT SHALL KURIYAMA OF AMERICA, ALFAGOMMA OR PIRANHA HOSE BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF KURIYAMA OF AMERICA, ALFAGOMMA OR PIRANHA HOSE.

IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPERED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCONSISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS, MATERIALS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

Kuriyama of America, Inc. www.kuriyama.com

323

HOSES

DNE-PIECE B SERIES

QUICK

ASSEMBLY

NFORMATION

ECHNICAL