


T902AA

150 PSI High Quality Hot Air Blower Hose

Applications:
Hot air transfer between the air compressor and dry bulk tank on bulk material carriers.

Cover:
Black EPDM – heat, abrasion and ozone resistant.

Reinforcement:
Spiraled high tensile textile cords with flexible steel helix wire.

Tube:
Black EPDM – heat-resistant.

Working Pressure:
Constant Pressure – 10 Bar (150 PSI)

Temperature Range:
-40°F (-40°C) to 356°F (+180°C)

Branding:
ALFAGOMMA – ITALY T902 10 BAR (150 PSI) – HOT AIR SERVICE (in white letters)

Standard Length:
100 feet

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Vacuum HG (in.)	Min. Bending Radius (in. @ 68°F)	Weight (lbs./ft.)
T902AA200	2	51	2.48	63	150	30	6	1.01
T902AA300	3	76	3.54	90	150	27	9	1.60
T902AA400	4	102	4.57	116	150	27	12	2.23

COUPLING SUGGESTIONS
Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.