Kuri Tec[®]

HS1171, HS1174, HS1176 Series

General Service PVC Pneumatic Air Tool Hose Assemblies



Service Temperature Range: -15°F (-26°C) to +150°F (+65°C)

| Nominal Specifications | | | | | | | | | | | | | |
|------------------------|---------------|----------------|------|------------|------|------------|------|------------------------------------|------------------|---------------|-------------------------|----------|-----------|
| Standard Stock Colors | | | Size | Nominal ID | | Nominal OD | | Maximum Working Pressure† (PSI) | | Assembled | Approx. Wt. per Pkg. | | |
| HS1171 Yellow | HS1174 Red | HS1176 Blue | | (ln) | (mm) | (ln) | (mm) | @70°F (20°C) | @122°F (50°C) | Lengths | 25 ft. | 50 ft. | 100 ft. |
| ~ | ~ | V | 04 | 1/4 | 6.5 | .475 | 12.1 | 300 | 150 | 25/50/100 ft. | | 3.7 lbs. | |
| ~ | / | / | 06 | 3/8 | 9.5 | .600 | 15.2 | 300 | 150 | | | | 10.2 lbs. |
| V | / | V | 08 | 1/2 | 12.7 | .750 | 19.1 | 300 | 150 | 25/50/100 ft. | 3.5 lbs. | 7.0 lbs. | 14.0 lbs |

Note: Hose assemblies are furnished with the following fittings: 1/4" ID -1/4" X 1/4"M NPT, 3/8" ID -3/8" X 1/4"M NPT, 1/2" ID -1/2" X 3/8"M NPT.

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

Note: Refer to page 33 for Technical Information.

HS1181, HS1184, HS1186 Series Utility-Grade PVC Air Tool Hose Assemblies



Service Temperature Range: +14°F (-10°C) to +150°F (+65°C)

| Noi | Nominal Specifications | | | | | | | | | | | |
|-----------------------|------------------------|------------------------|----------|------------|------------|--------------|--------------|------------------------------------|--------------------------------|-------------------------|---------|--|
| Standard Stock Colors | | | Size | Nominal ID | | Nominal OD | | Maximum Working Pressure† (PSI) | Assembled | Approx. Wt. per Pkg. | | |
| HS1181 Yellow | | IS1184 HS1186 Code | (ln) | (mm) | (In) | (mm) | @70°F (20°C) | Lengths | 25 ft. | 50 ft. | 100 ft. | |
| ~ | ~ | ~ | 04 06 | 1/4 3/8 | 6.5 9.5 | .475 .600 | 12.1 15.2 | 300 300 | 25/50/100 ft. 25/50/100 ft. | 1.9 lbs. 2.6 lbs. | | |

Note: Hose assemblies are furnished with the following fittings: 1/4" ID - 1/4" X 1/4"M NPT, 3/8" ID - 3/8" X 1/4"M NPT.

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

Note: Refer to page 34 for Technical Information.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

PHTHALATE FREE⁽¹⁵⁾

Please refer to the back page for the location of your nearest warehouse for availability of products/sizes shown.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

KKTCA0617 41