# Redi-Transfer™




## Red Fuel Oil Discharge Hose

**General Applications:**

- A high quality hose to handle oil, diesel, fuel oil and other petroleum products for home delivery. Also suitable for handling regular and unleaded gasolines up to 93 octane and bio-diesels up to B20.

**Construction:**

- **Cover –** Red Class A Nitrile/PVC, high oil resistance.
- **Reinforcement –** Spiral polyester yarn with static wire.
- **Tube –** Black Class A Nitrile, high oil resistance.

**Service Temperature Range:**
-40°F (-40°C) to +212°F (+100°C)

**Features and Advantages:**

- **Long lengths on reels.**
- **High oil resistance (Class A ) rated tube and cover.**

**Branding:**
REDI-TRANSFER FUEL OIL DELIVERY SIZE-WP-MADE IN USA

**Packaging:**
Cut lengths and bulk reels (maximum 3 pcs. on reel).

## Redi-Transfer™ Cut Lengths

**Nominal Specifications**

| Part Number | Color | ID (in) | OD (in) | Working Pressure (psi) | Length (ft) | Weight (lbs/pc) |
|---|---|---|---|---|---|---|
| REDITFR-100x100 | RED | 1 | 1.50 | 250 | 100 | 47 |
| REDITFR-100x150 | RED | 1 | 1.50 | 250 | 150 | 71 |
| REDITFR-100x200 | RED | 1 | 1.50 | 250 | 200 | 94 |
| REDITFR-125x100 | RED | 1 1/4 | 1.78 | 250 | 100 | 59 |
| REDITFR-125x125 | RED | 1 1/4 | 1.78 | 250 | 125 | 74 |
| REDITFR-125x150 | RED | 1 1/4 | 1.78 | 250 | 150 | 89 |
| REDITFR-137x125 | RED | 1 3/8 | 1.88 | 250 | 125 | 81 |
| REDITFR-137x150 | RED | 1 3/8 | 1.88 | 250 | 150 | 98 |
| REDITFR-150x125 | RED | 1 1/2 | 2.09 | 250 | 125 | 100 |
| REDITFR-150x150 | RED | 1 1/2 | 2.09 | 250 | 150 | 120 |
| REDITFR-150x175 | RED | 1 1/2 | 2.09 | 250 | 175 | 140 |

## Redi-Transfer™ Bulk Hose on Reels

**Nominal Specifications**

| Part Number | Color | ID (in) | OD (in) | Working Pressure (psi) | Reel Length (ft) | Weight (lbs/pc) |
|---|---|---|---|---|---|---|
| REDITFR-100x500 | Red | 1 | 1.50 | 250 | 500 | 235 |
| REDITFR-125x450 | Red | 1 1/4 | 1.78 | 250 | 450 | 265 |
| REDITFR-137x450 | Red | 1 3/8 | 1.88 | 250 | 450 | 293 |
| REDITFR-150x400 | Red | 1 1/2 | 2.09 | 250 | 400 | 320 |

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.