

OROFLEX® BANDAMA









Ideal for traveling irrigators.

BD Series PVC/Nitrile Rubber Irrigation Hose

General Applications:

- Flexible pipeline
- Heavy duty dredge discharge
- High abrasion resistant applications
- Irrigation supply lines
- Slurry, sludge, liquid manure pumping
- Traveling irrigators

Construction:

Black PVC/Nitrile hose using an extruded throughthe-weave process with circular woven high tenacity polyester reinforcement.

Service Temperature Range:

-20°F (-29°C) to +176°F (+80°C)

Features and Advantages:

- Proprietary PVC/Nitrile Material Specially developed PVC/Nitrile material provides superior abrasion, UV, chemical and oil resistance compared to PVC hoses.
- Superior Snaking Resistance! Specially designed to virtually eliminate instances of hose snaking, making the hose ideal for use on traveling irrigators.
- Unique Woven Construction Specially designed weave pattern provides resistance to kinking, stretching and twisting.
- Longer Lengths Manufactured in special 660 foot lengths to reduce possible leaking points.
- Compact Design Flat hose design rolls up into tight coils for easy storage and transport, takes up less space than other hoses.

| Nominal Specifications | | | | | | | | | | |
|------------------------|-------|-------|---------|-------|-------------------|---------------------------|------------------------------|----------------|-------------------|--------------------|
| Series Number | Size | | Hose ID | | Wall | Working | Burst | Coil | Tensile | Majahi |
| | (in) | (mm) | (in) | (mm) | Thickness (in) | Pressure (psi) at 68°F | Pressure (psi) at 68°F | Length (ft) | Strength (lbs) | Weight (Ibs/ft) |
| BD250 | 2 1/2 | 63.5 | 2.598 | 66.0 | 0.120 | 290 | 725 | 660 | 11,728 | 0.57 |
| BD300 | 3 | 76.2 | 3.051 | 77.5 | 0.120 | 261 | 653 | 660 | 18,475 | 0.67 |
| BD350 | 3 1/2 | 88.9 | 3.543 | 90.0 | 0.130 | 232 | 580 | 660 | 20,503 | 0.77 |
| BD400 | 4 | 101.6 | 4.067 | 103.3 | 0.130 | 202 | 507 | 660 | 22,046 | 0.94 |
| BD450 | 4 1/2 | 114.3 | 4.626 | 117.5 | 0.130 | 174 | 435 | 660 | 25,353 | 1.08 |
| BD500 | 5 | 127.0 | 5.020 | 127.5 | 0.140 | 174 | 435 | 660 | 27,161 | 1.21 |
| BD600 | 6 | 152.4 | 6.043 | 153.5 | 0.140 | 174 | 435 | 660 | 33,069 | 1.41 |

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.