ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SYN FG DRILL & TAP

"This product is certified OU Kosher Pareve"
"This product is Halal certified"

**NSF International H-1 Registered*
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE Synthetic Food Grade Drilling & Tapping Fluid is a full synthetic fluid designed specifically for drilling & tapping. This product is NSF H1 Registered making it ideal for food processors, food package manufacturers and the pharmaceutical industry.

APPLICATIONS

- ⇨ Drilling and Tapping

ADVANTAGES

- ⇨ NSF H1 Registered Food Grade
- ⇨ Non-Toxic
- ⇨ Excellent performance on stainless steel, steel, and aluminum
- ⇨ Does not contain sulfur, chlorine, or mineral oil
- ⇨ Provides minimal smoke

STORAGE RECOMMENDATIONS

- ⇨ Products should be stored between 40°F-120°F
- ⇨ Products should be stored in a dry covered environment
- ⇨ Products should not be stored in warm, direct sunlight
- ⇨ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Consistency		Liquid
Odor		None
Viscosity:		
SUS @ 100°F	ASTM D-2161	112
cSt @ 40°C	ASTM D-445	21
SUS @ 210°F	ASTM D-2161	31
cSt @ 100°C	ASTM D-445	5
Viscosity Index	ASTM D-2270	141
API Gravity	ASTM D-287	18.7
Specific Gravity	ASTM D-1298	0.94
Flash Point	ASTM D-92	>480°F/ >249°C
Color	ASTM D-1500	<1.5
Color APHA	ISO 2211	75

PACKAGING AVAILABLE	PART NUMBER
Case of 12 4 oz. bottles	L0540-014
Case of 12 8 oz. bottles	L0540-018
Case of 12 16 oz. bottles	L0540-026
Case of 12 1 qt. bottles	L0540-054
Case of 4 1 gal. jugs	L0540-057
5 Gallon pail	L0540-060
55 Gallon Drum	L0540-062
Case of 12 8 oz. bottles	L0540-018

NSF International H-1 Registration No.'s ***163171***
(Meets former USDA 1998 Guidelines)

**Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

*"**LUBRIPLATE SYNTHETIC FOOD GRADE DRILLING & TAPPING FLUID** contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".*

Printed in USA
Revised 17-Mar-2023