ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center
Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center
Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support
Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE SFGO ULTRA 22

Synthetic Chain & Penetrating Fluid

"This product is certified OU Kosher Pareve"
"This product is Halal certified"

**NSF International H-1 Registered*
NSF ISO21469 Certification

DESCRIPTION

LUBRIPLATE SFGO Ultra-22 Synthetic Chain & Penetrating Fluid Spray is designed to lubricate all types of chain operating in extreme cold temperature environments, dusty environments. It delivers excellent performance as a penetrating fluid. This PAO, full synthetic hydrocarbon fluid, is NSF H1 Registered Food Grade. It and has an operating temperature range of -50F to 250F. LUBRIPLATE SFGO Ultra-22 Synthetic Chain & Penetrating Fluid Spray provides the penetrating, cleaning, flushing, and long-lasting lubricating film required to achieve increased life from all types of roller chain operating in adverse environments.

APPLICATIONS

- ⇨ Spiral Freezer Chain
- ⇨ Chain, Sliding, Rotating Applications Operating In Extreme Cold Temperature Environments
- ⇨ Similar Applications Operating in Dusty Environments
- ⇨ Penetrating Oil

ADVANTAGES

- ⇨ Full Synthetic Hydrocarbon (PAO) Fluid
- ⇨ Low Pour Point
- ⇨ Anti-Wear Additives
- ⇨ High Viscosity Index
- ⇨ Superior Creeping Ability to Improve Penetration
- ⇨ Excellent Cleaning & Flushing Ability
- ⇨ Ideal Viscosity to Provide Long Lasting Lubricating Film While Attracting Minimal Abrasive Airborne Contaminants
- ⇨ Utilizes LUBRIPLATE'S SECURE STRAW DUAL SPRAY NOZZLE

STORAGE RECOMMENDATIONS

- ⇨ Products should be stored between 40°F-120°F
- ⇨ Products should be stored in a dry covered environment
- ⇨ Products should not be stored in warm, direct sunlight
- ⇨ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	106
SUS @ 210°F	ASTM D-2161	41
cSt @ 40°C	ASTM D-445	20
cSt @ 100°C	ASTM D-445	4
Viscosity Index	ASTM D-2270	128
Pour Point °F/°C	ASTM D-97	-63/-53
Flash Point °F/°C	ASTM D-92	405/207
Fire Point °F/°C	ASTM D-92	430/221
API Gravity	ASTM D-287	41.1
Color	ASTM D-1500	1.0 max
Four Ball Wear Test	ASTM D-2266	0.4 mm
SAE Grade		5W
ISO Viscosity Grade		22

PACKAGING AVAILABLE	**Part No.**
Carton, 12/11 oz. Aerosol Cans	L0931-063

NSF International H-1 Registration No. ***138421***
(Meets former USDA 1998 Guidelines)

**Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.*

"LUBRIPLATE SFGO Ultra 22 Synthetic Chain & Penetrating Fluid contains no components derived from TSE/BSE relevant animal species; therefore, it is compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011."

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

Printed in USA
Revised 01-Jun-2022