

Models

Part No.	Size	Clamps	Install
Standard Duty NO-Hub			
NH-150	1-1/2"	2	60
NH-22	2"	2	60
NH-33	3"	2	60
NH-44	4"	2	60
NH-55	5"	4	60
NH-66	6"	4	60
NH-88	8"	4	60
NH-1010	10"	4	60
NH-1212	12"	6	120
NH-1515	15"	6	120
Reducing Size No-Hub			
NH-215	2"x1-1/2"	2	60
NH-32	3"x2"	2	60
NH-42	4"x2"	2	60
NH-43	4"x3"	2	60
Medium Duty No-Hub			
MD-150	1-1/2"	4	80
MD-22	2"	4	80
MD-33	3"	4	80
MD-44	4"	4	80
MD-55	5"	6	80
MD-66	6"	6	80
MD-88	8"	6	80
MD-1010	10"	6	80
HD-150	1-1/2"	4	80
Heavy Duty No-Hub			
HD-22	2"	4	80
HD-33	3"	4	80
HD-44	4"	4	80
HD-55	5"	6	80
HD-66	6"	6	80
HD-88	8"	6	80
HD-1010	10"	6	80

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent