

## T Series 16 A 600 VAC

**6, 10, 16 & 24 Contacts**

**+ Ground**

- High-temp 200°C rated inserts
- Silicone Viton® seals for molded edge gaskets\*
- Corrosion-resistant copper-free aluminum housings with special finish
- UL94V-0 ergonomic thermoplastic handles
- Electrostatic epoxy powder-coated finish

\*Viton® is a trademark of DuPont Performance Elastomers



### Crimp Terminal Inserts

	Screw Terminal Inserts*	6 + G	10 + G	16 + G	24 + G
	<b>Male – Pins</b> 20–14 AWG (0.5–2.5 mm <sup>2</sup> )	MS206T	MS210T	MS216T	MS224T
	<b>Female – Sleeves</b> 20–14 AWG (0.5–2.5 mm <sup>2</sup> )	FS106T	FS110T	FS116T	FS124T

\* Blocs de connexion may be dark brown or grey in colour

Bases — Standard Mount				6	10	16	24
Single Lever	Double Lever	Housing	NPT Entry (in.)	Lever Locking Type			
				Single	Double	Double	Double
		Panel Base		PB306T	PB110T	PB116T	PB124T
		Box Base (No Cover)	1 x 1/2	BB406Tmv	BB010Tmv		
			1 x 3/4			BB016Tmv	BB024Tmv
			2 x 1/2	BB506Tmv	BB110Tmv		
			2 x 3/4			BB116Tmv	BB124Tmv
Hoods— Standard Mount							
		Side Entry	1 x 1/2	SH606T	SH010Tmv		
			1 x 3/4			SH016Tmv	SH024Tmv SH124Tmv
			1 x 1				
		Top Entry	1 x 1/2	TH806T	TH210T		
			1 x 3/4			TH216T	TH224T
			1 x 1				TH324Tmv
Coupler Hoods — Inline For inline, portable or special service connections. Coupler Hoods mate to Standard Hoods ONLY.							
		Top Entry	1 x 1/2	CH806T	CH610T		
			1 x 3/4			CH616Tmv	CH624T
			1 x 1			CH716T	CH724T

BASE  
BASE TO HOOD  
HOODS  
HOOD TO COUPLER  
COUPLERS

Note: Hoods and Bases are black colored to denote special T Series