

Actual

 Catalog Number:
 035-72775-1

 Product ID:
 7TBD012360R0000

 UPC Number:
 78621086858

Status: Active

1/2 Inch Straight Die Cast Zinc Liquidtight Strain Relief Cord Connector, Cord Range 0.125 to 0.250

• Extended range with superior strain relief

UNSPSC Specifications	
UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B
Туре	Strain Relief Cord Connectors-Straight
Special Features	Throat Inner Diameter is Nylon Coated for Ease of Wire Pull
Application	Provide Means for Passing a Cord Cable, Armored or Unarmored, Into an Enclosure, Through a Bulkhead or Into a Rigid Conduit
Size	1/2 Inch
Material	Zinc Die Cast
ETIM Specifications	
ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1/2 inch
Model	Straight
Revolving thread	N
Construction type	External thread

Nominal size in inch	1/2 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Connection type screw connection to	Thread
housing	
Thread type	NPT
Thread connection size	None
Material housing	Zinc die-cast
Packaging	

Packaging	
Inner Quantity	25
Inner Dimensions (inches)	5.3x4.6x3.4
Outer Quantity	100
Outer Dimensions (inches)	10.9x9.9x4.2
Weight Uom	15 lbs. per 100

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com