



Representative



Line Art

Catalog Number: TY175-50-9-100
Product ID: 7TCG054360R0177
UPC Number: 78620986551
EAN Number: 05414363132943
Status: Active

Cable Tie, White Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 186.43mm (7.34 Inches), Width of 4.674mm (0.184 Inches), Thickness of 1.24mm (0.049 Inches), Tensile Strength Rating of 220 Newtons (50 Pounds), 100 Pack

North American Specifications (UNSPSC)

UNSPSC	39121703 Cable ties
IGCC	5034 Cable ties
Brand Name	Ty-Fast
Standard	UL E49405
Width	0.184 in ; 4.674 mm
Length	7.34 in ; 186.43 mm
Thickness	0.049 Inch/1.24mm
Bundle Diameter	1.75 Inches/44.45mm
Material	Nylon/Polyamide 6.6
Color	White
Lock Mechanism	Plastic Pawl
Tensile Strength	50 Pounds/222 Newtons

European Specifications (ETIM)

ETIM	EC000046 Cable tie
Band width	4.674mm
Length belt/tape/tie	186.43mm
Tie thickness	1.24mm
Min. holding force	220N
Model	Internal toothing
Band closure	Plastic lip/-cam
Material	Plastic
Material quality	Polyamide PA
Surface protection	Untreated
Halogen free	Y
Colour	White
Transparent	N
Reflective (fluorescent)	N
Text strip	None
Solvable fastener	N
MIL approval	N

Packaging

Inner Quantity	100
Inner Dimensions (inches)	12x5x1
Outer Quantity	10000
Outer Dimensions (inches)	23.6x15.4x11
Weight Uom	2.94 lbs. per 1000

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

