

Eaton DPF221R

Catalog Number: DPF221R

Eaton air conditioning disconnect, Fused pullout, 30A, 120/240V, 10 kAIC, #14-3 Cu/Al 60°C or 75°C, NEMA 3R Galvanized Steel enclosure, 2 hp at 120V, 3 hp at 240V, ANSI 61 gray



General specifications

Product Name	Catalog Number
Eaton air conditioning disconnect	DPF221R
UPC	Product Length/Depth
782113926865	5.4 in
Product Height	Product Width
8.7 in	3.15 in
Product Weight	Warranty
2.7 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Certifications	Catalog Notes
UL Listed CSA Certified	For replacement pullout head, order part number 96-3258-4.

Product specifications

Enclosure material

Galvanized steel

Interrupt rating

10 kAIC

Type

Fused pullout

Wire size

#14-3 AWG Cu/Al

Horsepower

2 hp at 120 V, 3 hp at 240 V

Color

ANSI 61 gray

Enclosure

NEMA 3R

Voltage rating

120/240 V

Amperage Rating

30A

Resources

Brochures

[Air Conditioning Disconnects](#)

Catalogs

[Eaton's Volume 1—Residential and Light Commercial](#)

Drawings

[Dimensional Drawing - SKT 200A 1P HCP](#)

Specifications and datasheets

[Eaton Specification Sheet - DPF221R](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
[Eaton.com](https://www.eaton.com)

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia