

Eaton DS7-340SX055N0-L

Catalog Number: DS7-340SX055N0-L

Eaton DS7 soft start controller, Standard Soft Starter with internal bypass, Inline or Inside-the-Delta wiring configuration, Frame 3, 55 A, 55 A, Three-pole, 480 V, 40 hp, Three-phase, IP20, Expanded temperature range down to -40°C



General specifications

Product Name	Catalog Number
Eaton DS7 soft start controller	DS7-340SX055N0-L
UPC	Product Length/Depth
786685887272	6.34 in
Product Height	Product Width
5.47 in	3.66 in
Product Weight	Warranty
3.97 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Certifications	
Contact Manufacturer	

Product specifications

Frame size

3

Options

Expanded temperature range down to -40 °C

Type

Standard soft starter with internal bypass

Phase

Three-phase

Horsepower

40 hp

Voltage rating

480 V

Amperage Rating

55A

Wiring connection

Inline or Inside-the-Delta wiring configuration

Protection

IP20

Number Of Poles

Three-pole

Resources

Brochures

[DS7 Series soft start controller](#)

Catalogs

[Eaton's Volume 6—Solid-State Motor Control](#)

[Product Datasheet - DS7-340SX055N0-L](#)

Installation instructions

[DS7 series soft start controllers, Frame 1 \(4–12A\)](#)

Multimedia

[Soft Starter Product Family Overview](#)

[Soft starter DS7 up to 200 A](#)

[Soft Starter DS7 up to 32 A](#)

Specifications and datasheets

[Eaton Specification Sheet - DS7-340SX055N0-L](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia