

# Eaton QCR2015HTV

Catalog Number: QCR2015HTV

Eaton Quicklag Type QCR 1/2-inch Industrial Thermal-Magnetic Circuit Breaker,Industrial circuit breaker,50° C Calibration,15 A,10 kAIC,Two-pole,240 V,Thermal-magnetic,Cable-in/cable-out,QCR, Ring or spade lug terminals



## General specifications

|                                            |                                                                                                                                                                                                                 |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Name</b>                        | <b>Catalog Number</b>                                                                                                                                                                                           |
| Eaton QCR thermal magnetic circuit breaker | QCR2015HTV                                                                                                                                                                                                      |
|                                            | <b>UPC</b>                                                                                                                                                                                                      |
|                                            | 782113681030                                                                                                                                                                                                    |
| <b>Product Length/Depth</b>                | <b>Product Height</b>                                                                                                                                                                                           |
| 5.7 in                                     | 3.5 in                                                                                                                                                                                                          |
| <b>Product Width</b>                       | <b>Product Weight</b>                                                                                                                                                                                           |
| 2 in                                       | 0.5 lb                                                                                                                                                                                                          |
| <b>Warranty</b>                            | <b>Compliances</b>                                                                                                                                                                                              |
| 1 year                                     | HACR Rated                                                                                                                                                                                                      |
| <b>Certifications</b>                      | <b>Catalog Notes</b>                                                                                                                                                                                            |
| UL Listed<br>CSA Certified                 | Standard breaker terminals are box type lugs. Suitable for line and load side ring terminal connection (#10-32 plus/minus terminal screw provided). Switching duty rated for fluorescent lighting applications. |

## Physical Attributes

### Circuit breaker type

QCR

### Connection

Cable-in/cable-out

### Mounting Method

Rear

### Number of poles

Two-pole

### Terminals

Ring or spade lug

### Type

Industrial circuit breaker

## Performance Ratings

### Amperage Rating

15 A

### Interrupt rating

10 kAIC

### Trip Type

Thermal-magnetic

### Voltage rating

240 V - 240 V

## Miscellaneous

### Special features

50° C Calibration

## Resources



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia