MCR400I, MCR675I, MCR1000I, MCR1500I, MCRB400I, MCRB675I, MCRB1000I, MCRB1500I

CSA Certified





SPECIFICATIONS:

Output Torque	400 Lb.-In.
	675 Lb.-In.
	1000 Lb.-In.
	1500 Lb.-In.
Cycle Time	10 Sec/90º Rotation
	15 Sec/90º Rotation
	30 Sec/90º Rotation
Duty Cycle	25%
Motor	115Vac, 60Hz, 1Ph. PSC (Optional Voltages Available)
Thermal Over-Load Protection	Std.
Enclosure	NEMA 4
Enclosure Option	NEMA 7
Enclosure Material	Cast Aluminum
Mounting Dim	ISO 5211 F07
Enclosure Coating	Thermally Bonded Polyester Powder
Fasteners	S.S.
Output Shaft	S.S.
Manual Override	Std. NEMA 4, Opt. NEMA 7
Friction Brake	Std.
Wired for light indication	Std.
Terminal Strip Connection	AWG 14
Lock Rotor Current	.75 Amp
	1.1 Amps
Weight	13 Lbs. NEMA 4, 16 Lbs. NEMA 7
Lubrication	Permanent
Installation	Universal
Temperature	-40º F. to +150º F.

Heater Required at 0º F. and Below
Switches: 15 A 1/2 HP 125, 250 Vac 0.5 A, 125 Vdc

NOTE: MCRB - Includes Motor Brake

	Enclosure	
	NEMA 4	NEMA 7
A	7.0	8.5
B	2.38	3.13
C	2.81	2.81
D	2.63	3.38

Dimensions in inches

NOTE:
ALLOW 4.0" FOR
COVER REMOVAL

