Specifications

Eaton PXM350MA6541-2B8A

Eaton enclosed meter, NEMA12(240V & 480V, w/CPT), 1-240V 3PH/4W Main Fuse Disconnect (1-PXM), 1-480V 3PH/4W Main Fuse Disconnect (7-PXM), Control Power Fuse Disconnect per PXM, CT Shorting Block per PXM

General specifications	
PRODUCT NAME	Eaton enclosed meter
CATALOG NUMBER	PXM350MA6541-2B8A
UPC	786689718770
PRODUCT LENGTH/DEPTH	12 in
PRODUCT HEIGHT	48 in
PRODUCT WIDTH	30 in
PRODUCT WEIGHT	100 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	ANSI/IEEE Std C12.20 (0.2% accuracy) ANSI/IEEE Std C62.41 IEC 687 (0.2% accuracy)

Powering Business Worldwide

Product specifications

VOLTAGE RATING	480V
POWER SUPPLY	480VAC
ENCLOSURE	NEMA 12
ENCLOSURE SIZE	48inH x 30inW x 10inD
NUMBER OF METERS	8
DISPLAY	Meter Faceplate
FREQUENCY RATING	50/60 Hz
COMMUNICATION	ModbusRTU,BACnet MSTP

Resources

BROCHURES	Eaton's enclosed meter family
CATALOGS	Power Distribution and Control Assemblies, Metering Devices, Protective Relays, Software and Connectivity, Volume 3, Tab 9
MULTIMEDIA	Eaton's Enclosed Meters
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - PXM350MA6541-2B8A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.