Specifications



Eaton PXM350MA6521-3A1A

Eaton enclosed meter, PXM350(MA6521), NEMA3R, NO CPT (120/240Vac), 3PH/4W Main Fused Voltage Disconnect, CT Shorting Block, Fused Control Power Disconnect

General specifications	
PRODUCT NAME	Eaton enclosed meter
CATALOG NUMBER	PXM350MA6521-3A1A
UPC	786689585631
PRODUCT LENGTH/DEPTH	8 in
PRODUCT HEIGHT	24 in
PRODUCT WIDTH	16 in
PRODUCT WEIGHT	100 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	ANSI/IEEE Std C12.20 (0.2% accuracy) ANSI/IEEE Std C62.41 IEC 687 (0.2% accuracy)

Powering Business Worldwide

Product specifications

VOLTAGE RATING	120-240 V L-L
POWER SUPPLY	120/240 Vac
ENCLOSURE	NEMA 3R
ENCLOSURE SIZE	24”H x 16”W x 8”D
NUMBER OF METERS	1
DISPLAY	Meter Faceplate
FREQUENCY RATING	50/60 Hz
COMMUNICATION	Modbus
DEGREE OF PROTECTION	NEMA 3R

Resources

BROCHURES	Eaton's enclosed meter family
CATALOGS	Power Distribution and Control Assemblies, Metering Devices, Protective Relays, Software and Connectivity, Volume 3, Tab 9
MULTIMEDIA	Eaton's Enclosed Meters
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - PXM350MA6521-3A1A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.