

Specifications



Photo is representative

Eaton

B48D28F5516QCULS55

500 kVA K-9 DOE 2016 Efficient General Purpose Ventd Transformer PV 480V Delta, 208Y/120, 115C rise, Copper windings, NEMA 1, 55 dB Sound Q

General specifications

PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	B48D28F5516QCULS55
UPC	786680236358
PRODUCT LENGTH/DEPTH	44.25 in
PRODUCT HEIGHT	80.25 in
PRODUCT WIDTH	64 in
PRODUCT WEIGHT	1.1 lb
COMPLIANCES	DOE2016 Efficient
CERTIFICATIONS	UL Listed
CATALOG NOTES	10 CFR Part 431 (2016) Efficient



Powering Business Worldwide

Physical Attributes	
COIL MATERIAL	Copper
ENCLOSURE	NEMA 1
FRAME	GPF
INSULATION	220 °C
MOUNTING	Floor
TAP SIZE	+2 at 2.5% FCAN, -2 at 2.5% FCBN

Miscellaneous	
MODIFICATION 1	K-9

Performance Ratings	
EFFICIENCY	10 CFR Part 431-2016 (DOE 2016)
FREQUENCY RATING	60 Hz
KVA RATING	500 kVA
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	208Y/120 V
SOUND LEVEL	55 dB
TEMPERATURE RISE	115 °C rise
VOLT AMPERE RATING	500 kVA

Resources	
	Eaton's high-efficiency dry-type transformers
BROCHURES	Eaton's low-voltage dry-type distribution transformers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - B48D28F5516QCULS55

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

