

Specifications



Photo is representative

Eaton B48M47T2216CU

Eaton K-Factor nonlinear ventilated transformer, Copper windings, NEMA 2, FRFloor, 60 Hz, 220C, 225 kVA, Three-Phase, 480 DELTA to 480Y/277, 150 C rise, Shielded, DOE 2016, WS62, 283B, K9

General specifications

PRODUCT NAME	Eaton K-Factor nonlinear ventilated transformer
CATALOG NUMBER	B48M47T2216CU
UPC	786680242649
PRODUCT LENGTH/DEPTH	33.5 in
PRODUCT HEIGHT	66.18 in
PRODUCT WIDTH	42.18 in
PRODUCT WEIGHT	2641 lb
COMPLIANCES	DOE2016 Efficient
CERTIFICATIONS	UL Listed
CATALOG NOTES	10 CFR Part 431 (2016) Efficient

Physical Attributes	
COIL MATERIAL	Copper
ENCLOSURE	NEMA 2
WIRING CONNECTION	283B
TYPE	Energy-efficient ventilated transformer
FRAME	Floor
INSULATION	220 °C
MOUNTING	Floor
TAP SIZE	2 at +2.5%, 4 at -2.5%

Miscellaneous	
EFFICIENCY	10 CFR Part 431-2016 (DOE 2016)
MODIFICATION 1	Electrostatic shield
SPECIAL FEATURES	K-factor 9
WEATHERSHIELD	WS62

Performance Ratings	
FREQUENCY RATING	60 Hz
KVA RATING	225 kVA
VOLT AMPERE RATING	225 kVA
PHASE	Three-phase
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	480Y/277 V
SOUND LEVEL	NEMA ST-20
TEMPERATURE RISE	150 °C rise

Resources	
MULTIMEDIA	Eaton's Transformer Flex Center
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - B48M47T2216CU

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

