

Enclosure Accessories - Hubs, Grounding Plates, and Grounding Bushings

Myers Hubs*

Ground Hub Basic Scru-Tite®

Zinc

ATEX Approval with DEMKO 07 ATEX 0618172U

II 2 G Ex e II

Class I, Zone 1, AEx e II

UL File No. 187273

Class I, Zone 1, Ex e II



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
STGK 1	1/2"	10	20
STGK 2	3/4"	10	30
STGK 3	1"	10	43
STGK 4	1 1/4"	5	55
STGK 5	1 1/2"	5	73
STGK 6	2"	5	95

Stainless Steel – Type 316

ATEX Approval with DEMKO 07 ATEX 0618172U

II 2 G Ex e II

Class I, Zone 1, AEx e II

UL File No. E-187273


Class I, Zone 1, Ex e II



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
SSTGK 1	1/2"	10	20
SSTGK 2	3/4"	10	30
SSTGK 3	1"	10	43
SSTGK 4	1 1/4"	5	55
SSTGK 5	1 1/2"	5	73
SSTGK 6	2"	5	95

Metric To NPT Adapter

Zinc




Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
STM 1	M20 to 1/2"	25	12
STM 2	M25 to 3/4"	25	32
STM 3	M32 to 1"	25	32
STM 4	M40 to 1 1/4"	10	40
STM 5	M50 to 1 1/2"	10	50
STM 6	M63 to 2"	10	70

Note: The Myers Metric to NPT hub adapter is used to convert a threaded metric entry to a NPT entry. The female thread is NPT and the male thread is metric.

Metric To NPT Adapter

Stainless Steel



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
SSTM 1	M20 to 1/2"	10	12
SSTM 2	M25 to 3/4"	10	20
SSTM 3	M32 to 1"	10	32
SSTM 4	M40 to 1 1/4"	5	40
SSTM 5	M50 to 1 1/2"	5	50
SSTM 6	M63 to 2"	5	70

Nonmetallic Hubs


Krydon® material hubs for conduit entrances, in sizes 1/2" through 3" are available for factory or field installation in all enclosures made of *Krydon* material. For factory installation, send drawing showing sizes and locations of hubs. Furnished with and gaskets to assure.

Standard Materials:

- Up to 1 1/2" – *Krydon* material with steel interiors
- 2", 2 1/2" and 3" – *Krydon* material with *Feraloy*® iron alloy interiors


Standard Finishes:

- *Krydon* material – natural
- Steel – electrogalvanized and bleached chromate
- *Feraloy* iron alloy – electrogalvanized



Conduit Size	Hole Size	Hub Cat. #
1/2"	7/8"	NHUB1
3/4"	1 1/8"	NHUB2
1"	1 3/8"	NHUB3
1 1/4"	1 3/4"	NHUB4
1 1/2"	2"	NHUB5
2"	2 1/2"	NHUB6
2 1/2"	3"	NHUB7
3"	3 5/8"	NHUB8

Grounding Plates and Grounding Bushings



Grounding Plates (1/2" through 1") and insulated bushings (1/2" through 3") permit use of the conduit as the grounding circuit. Both types have set screws and ground-wire terminals.

Standard Materials:

- Grounding plates – steel
- Grounding bushings – steel with thermoplastic insulating throat

Standard Finishes:

- Steel – electrogalvanized

Conduit Size	Grounding Plate Cat. #	Grounding Bushing Cat. #
1/2"	GP1	GLS1
3/4"	GP2	GLS2
1"	GP3	GLS3
1 1/4"		GLS4
1 1/2"		GLS5
2"		GLS6
2 1/2"		GLS7
3"		GLS8

*For a complete list of Myers Hubs available from Eaton's Crouse-Hinds, refer to Section CP.