

Specifications



Photo is representative

Eaton HRC2

Eaton Crouse-Hinds series HRC bimetal thermostat, 0.5 HP/1 HP, Copper-free alum, 1-pole, 2.5°F (1.5°C) temp. diff, 36° to 82°F (2° to 28°C) temp. range, Double-throw, 3/4", For heating or cooling/ventilation, 120/250 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series HRC bimetal thermostat
CATALOG NUMBER	HRC2
UPC	782274154619
PRODUCT LENGTH/DEPTH	4.92 in
PRODUCT HEIGHT	4.92 in
PRODUCT WIDTH	3.38 in
PRODUCT WEIGHT	3 lb

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2 Class II, Division 1 Class II, Division 2 Class III

Product specifications

TEMPERATURE RANGE	36°-82°F (2°-28°C)
TEMPERATURE DIFFERENTIAL	2.5°F (1.5°C)
THROW	Double-throw
NUMBER OF POLES	Single-pole
TRADE SIZE	3/4"
VOLTAGE RATING	120/250 Vac
HORSEPOWER	0.5 hp at 120 Vac, 1 hp at 250 Vac
MATERIAL	Copper-free aluminum
SPECIAL FEATURES	Bimetal sensing element
TYPE	For heating or cooling/ventilation applications

Resources

CATALOGS	HRC Series Explosionproof Thermostats catalog page
CERTIFICATION REPORTS	HRC Explosionproof Thermostats UL certification
INSTALLATION INSTRUCTIONS	IF 1234 - HRC Series Explosionproof Thermostats
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - HRC2

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

