

Specifications



Eaton PXBCM-MBB-2A2V-AC

PXBCM(-MB-BASIC),(2)PXBCM(-MME-X25-333mV),PXG900,NEMA12(240V), Vdc Power Supply: PXG,3PH/4W Main Fused Disconnect,ea MME cabled to MB,MB COM 1 RS485 to PXG COM 1

General specifications

PRODUCT NAME	Eaton enclosed meter
CATALOG NUMBER	PXBCM-MBB-2A2V-AC
UPC	786689589578
PRODUCT LENGTH/DEPTH	10 in
PRODUCT HEIGHT	20 in
PRODUCT WIDTH	20 in
PRODUCT WEIGHT	200 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	ANSI/IEEE Std C12.20 (0.2% accuracy) ANSI/IEEE Std C62.41 IEC 687 (0.2% accuracy)

Product specifications

VOLTAGE RATING	120-240 V
POWER SUPPLY	120-240VAC
ENCLOSURE	NEMA 12
NUMBER OF METERS	2
DISPLAY	None
FREQUENCY RATING	50/60 Hz
DEGREE OF PROTECTION	NEMA 12

Resources

BROCHURES	Eaton's enclosed meter family
CATALOGS	Power Distribution and Control Assemblies, Metering Devices, Protective Relays, Software and Connectivity, Volume 3, Tab 9
MULTIMEDIA	Eaton's Enclosed Meters
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - PXBCM-MBB-2A2V-AC

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

