

Specifications



Eaton PXM1200MA15-2B5CA

Eaton enclosed meter, 5-PXM1200(MA15,No Opt Comm,No Opt I/O),PXG900,NEMA12,CPT(480V), 3PH/4W Main Fused Disconnect,5-CT Shorting Blocks,Vdc PS:PXG,5 PXM RS485 to PXG COM 1

General specifications

PRODUCT NAME	Eaton enclosed meter
CATALOG NUMBER	PXM1200MA15-2B5CA
UPC	786689592745
PRODUCT LENGTH/DEPTH	12 in
PRODUCT HEIGHT	30 in
PRODUCT WIDTH	24 in
PRODUCT WEIGHT	100 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	ANSI/IEEE Std C12.20 (0.2% accuracy) ANSI/IEEE Std C62.41 IEC 687 (0.2% accuracy)

Product specifications

VOLTAGE RATING	480V
POWER SUPPLY	480 Vac
ENCLOSURE	NEMA 12
ENCLOSURE SIZE	30"H x 24"W x 12"D
NUMBER OF METERS	5
DISPLAY	Meter Faceplate
FREQUENCY RATING	50/60 Hz
COMMUNICATION	PXG900

Resources

BROCHURES

[Eaton's enclosed meter family](#)

CATALOGS

[Power Distribution and Control Assemblies, Metering Devices, Protective Relays, Software and Connectivity, Volume 3, Tab 9](#)

MULTIMEDIA

[Eaton's Enclosed Meters](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - PXM1200MA15-2B5CA](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

