

Specifications



Eaton PXM3000MA15-2A1A

Eaton enclosed meter, Eaton enclosed meter, PXM3000(Intgrl Disp, 100-277Vac/100-250Vdc Cntrl Pwr, Rog Coil Current In, 400VacL-N/690VacL-L, MRTU, MTCP), NEMA12, NoCPT(240V), 3PH/4W Main Fuse Volt Disc, Fused Cntrl Pwr Disc

General specifications

PRODUCT NAME	Eaton enclosed meter
CATALOG NUMBER	PXM3000MA15-2A1A
UPC	786689586195
PRODUCT LENGTH/DEPTH	8 in
PRODUCT HEIGHT	16.3 in
PRODUCT WIDTH	10.4 in
PRODUCT WEIGHT	100 lb
COMPLIANCES	CE Marked
CERTIFICATIONS	ANSI/IEEE Std C12.20 (0.2% accuracy) ANSI/IEEE Std C62.41 IEC 687 (0.2% accuracy)

Product specifications

VOLTAGE RATING	120-240 V
POWER SUPPLY	120-240VAC
ENCLOSURE	NEMA 12
ENCLOSURE SIZE	16.30inHx10.40inWx8inD
NUMBER OF METERS	1
DISPLAY	Meter Faceplate
FREQUENCY RATING	50/60 Hz
COMMUNICATION	ModbusTCP ModbusRTU BACnet/IP WebUI
DEGREE OF PROTECTION	NEMA 12

Resources

BROCHURES	Eaton's enclosed meter family
CATALOGS	Power Distribution and Control Assemblies, Metering Devices, Protective Relays, Software and Connectivity, Volume 3, Tab 9
MULTIMEDIA	Eaton's Enclosed Meters
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - PXM3000MA15-2A1A

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

